

GNU COBOL Sample Programs

For Version 2.1 [23NOV2013]

Gary L. Cutler (cutlergl@gmail.com).

This manual documents GNU COBOL 2.1, 23NOV2013 build.

GNU-COBOL Copyright 2002-2007 Keisuke Nishida

Copyright 2007-2012 Roger While

Copyright 2013-2013 Ron Norman (RWCS for GNU COBOL)

Document Copyright 2009-2014 Gary L. Cutler

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License [FDL], Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Table of Contents

1. FileStat-Msgs	1
2. COBDUMP	3
3. Colors	9
4. DAY-FROM-DATE	31
5. GCic	35
6. STREAMIO	151
7. GNU Free Documentation License	169

1. FileStat-Msgs

The FileStat-Msgs.cpy copybook contains an EVALUATE statement to translate the two-digit file status codes that may be generated by file I/O statements.

The copybook assumes that the file status data item name is "STATUS" and the error message data item is named "MSG". By using the COPY statement's REPLACING clause, however, you may use the data names you wish, as follows:

```
COPY FileStat-Msgs
  REPLACING STATUS BY file-status-data-item-name
                MSG   BY error-message-data-item-name
```

Here's the FileStat-Msgs.cpy copybook:

```
EVALUATE STATUS
  WHEN 00 MOVE 'SUCCESS' TO MSG
  WHEN 02 MOVE 'SUCCESS DUPLICATE' TO MSG
  WHEN 04 MOVE 'SUCCESS INCOMPLETE' TO MSG
  WHEN 05 MOVE 'SUCCESS OPTIONAL' TO MSG
  WHEN 07 MOVE 'SUCCESS NO UNIT' TO MSG
  WHEN 10 MOVE 'END OF FILE' TO MSG
  WHEN 14 MOVE 'OUT OF KEY RANGE' TO MSG
  WHEN 21 MOVE 'KEY INVALID' TO MSG
  WHEN 22 MOVE 'KEY EXISTS' TO MSG
  WHEN 23 MOVE 'KEY NOT EXISTS' TO MSG
  WHEN 30 MOVE 'PERMANENT ERROR' TO MSG
  WHEN 31 MOVE 'INCONSISTENT FILENAME' TO MSG
  WHEN 34 MOVE 'BOUNDARY VIOLATION' TO MSG
  WHEN 35 MOVE 'FILE NOT FOUND' TO MSG
  WHEN 37 MOVE 'PERMISSION DENIED' TO MSG
  WHEN 38 MOVE 'CLOSED WITH LOCK' TO MSG
  WHEN 39 MOVE 'CONFLICT ATTRIBUTE' TO MSG
  WHEN 41 MOVE 'ALREADY OPEN' TO MSG
  WHEN 42 MOVE 'NOT OPEN' TO MSG
  WHEN 43 MOVE 'READ NOT DONE' TO MSG
  WHEN 44 MOVE 'RECORD OVERFLOW' TO MSG
  WHEN 46 MOVE 'READ ERROR' TO MSG
  WHEN 47 MOVE 'INPUT DENIED' TO MSG
  WHEN 48 MOVE 'OUTPUT DENIED' TO MSG
  WHEN 49 MOVE 'I/O DENIED' TO MSG
  WHEN 51 MOVE 'RECORD LOCKED' TO MSG
  WHEN 52 MOVE 'END-OF-PAGE' TO MSG
  WHEN 57 MOVE 'I/O LINAGE' TO MSG
  WHEN 61 MOVE 'FILE SHARING FAILURE' TO MSG
  WHEN 91 MOVE 'FILE NOT AVAILABLE' TO MSG
END-EVALUATE.
```


2. COBDUMP

COBDUMP is a useful little utility subroutine to produce a formatted hexadecimal and character dump of the data area passed to it.

If you follow the GNU COBOL forums, you've undoubtedly heard about the CBL_OC_DUMP subroutine that was the winning entry in a GNU COBOL programming contest. It's a great tool for producing data dumps, and it's now included in the official GNU COBOL distributions.

For now though, I'll keep using my good ol' "COBDUMP" routine. It's been my travelling companion from COBOL job to COBOL job since 1971. Here it is, all tuned up for GNU COBOL, with new tires and a fresh coat of paint.

In addition to general GNU COBOL concepts, this program provides a useful demonstration of the following:

- Coding a GNU COBOL subroutine
- Using "USAGE POINTER" data items
- Using the "ANY LENGTH" data item attribute
- Coding for an "OPTIONAL" subprogram argument
- Using the "NUMBER-OF-CALL-PARAMETERS" special register
- Using the "C\$PRINTABLE" built-in system subroutine

The program source and cross-reference listing, produced using the GNU COBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement

Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      PROGRAM-ID.    COBDUMP.
4      *>*****
5      *> This is an OpenCOBOL subroutine that will generate a      **
6      *> formatted Hex/Char dump of a storage area.  To use this  **
7      *> subroutine, simply CALL it as follows:                    **
8      *>                                                            **
9      *> CALL "COBDUMP" USING <data-item>                          **
10     *> [ <length> ]                                             **
11     *>                                                            **
12     *> If specified, the <length> argument specifies how many   **
13     *> bytes of <data-item> are to be dumped.  If absent, all of **
14     *> <data-item> will be dumped (i.e. LENGTH(<data-item>) will **
15     *> be assumed for <length>).                                  **
16     *>                                                            **
17     *> >>> Note that the subroutine name MUST be specified in <<< **
18     *> >>> UPPERCASE                                           <<< **
19     *>                                                            **
20     *> The dump is generated to STDERR, so you may pipe it to a  **
21     *> file when you execute your program using "2> file".      **
22     *>                                                            **
23     *> AUTHOR:          GARY L. CUTLER                            **
24     *>                                                            **
25     *> NOTE:           The author has a sentimental attachment to **
26     *>                 this subroutine - it's been around since 1971 **
27     *>                 and it's been converted to and run on 10 dif- **
28     *>                 ferent operating system/compiler environments **
29     *>                                                            **
30     *> DATE-WRITTEN:  October 14, 1971                            **
31     *>                                                            **
32     *>*****
33     *>  DATE  CHANGE DESCRIPTION                                  **
34     *> ===== **
35     *> GC1071 Initial coding - Univac Dept. of Defense COBOL '68  **
36     *> GC0577 Converted to Univac ASCII COBOL (ACOB) - COBOL '74  **
37     *> GC1182 Converted to Univac UTS4000 COBOL - COBOL '74 w/    **
38     *>                 SCREEN SECTION enhancements                **
39     *> GC0883 Converted to Honeywell/Bull COBOL - COBOL '74      **
40     *> GC0983 Converted to IBM VS COBOL - COBOL '74              **
41     *> GC0887 Converted to IBM VS COBOL II - COBOL '85           **
42     *> GC1294 Converted to Micro Focus COBOL V3.0 - COBOL '85 w/ **
43     *>                 extensions                                  **
44     *> GC0703 Converted to Unisys Universal Compiling System (UCS) **
45     *>                 COBOL (UCOB) - COBOL '85                  **
46     *> GC1204 Converted to Unisys Object COBOL (OCOB) - COBOL 2002 **
47     *> GC0609 Converted to OpenCOBOL 1.1 - COBOL '85 w/ some COBOL **
48     *>                 2002 features                              **
49     *> GC0410 Enhanced to make 2nd argument (buffer length)     **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement

Page: 2

```

=====
50      *>          optional                      **
51      *> GC0211 Ported to IBM Enterprise COBOL      **
52      *> GC0612 Updated for OpenCOBOL 2.0          **
53      *>*****
54      ENVIRONMENT DIVISION.
55      CONFIGURATION SECTION.
56      REPOSITORY.
57          FUNCTION ALL INTRINSIC.
58      DATA DIVISION.
59      WORKING-STORAGE SECTION.
60      01 WS-Addr-PTR                      USAGE POINTER.
61      01 WS-Addr-NUM REDEFINES WS-Addr-PTR
62                                          USAGE BINARY-LONG.
63
64      01 WS-Addr-SUB                      USAGE BINARY-CHAR.
65
66      01 WS-Addr-Value-NUM                USAGE BINARY-LONG.
67
68      01 WS-Buffer-Byte-CHR.
69          05 WS-Buffer-Byte-NUM          USAGE BINARY-CHAR.
70
71      01 WS-Buffer-Length-NUM            USAGE BINARY-LONG.
72
73      01 WS-Buffer-SUB                    PIC 9(4) COMP-5.
74
75      01 WS-Hex-Digit-TXT VALUE '0123456789ABCDEF'.
76          05 WS-Hex-Digit-CHR            OCCURS 16 TIMES
77                                          PIC X(1).
78
79      01 WS-Nibble-SUB                    PIC 9(1) COMP-5.
80
81      01 WS-Nibble-Left-SUB               PIC 9(1) COMP-5.
82
83      01 WS-Nibble-Right-SUB              PIC 9(1) COMP-5.
84
85      01 WS-Output-Detail-TXT.
86          05 WS-OD-Addr-TXT.
87              10 WS-OD-Addr-Hex-CHR      OCCURS 8 TIMES PIC X.
88              05 FILLER                  PIC X(1).
89          05 WS-OD-Relative-Byte-NUM     PIC Z(3)9.
90          05 FILLER                      PIC X(1).
91          05 WS-OD-Hex-TXT                OCCURS 16 TIMES.
92              10 WS-OD-Hex-1-CHR         PIC X.
93              10 WS-OD-Hex-2-CHR         PIC X.
94              10 FILLER                  PIC X.
95          05 WS-OD-ASCII-Data-TXT.
96              10 WS-OD-ASCII-CHR        OCCURS 16 TIMES
97                                          PIC X.
98
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement Page: 3

```

=====
 99      01 WS-Output-SUB                                PIC 9(2) COMP-5.
100
101      >>SOURCE FORMAT IS FREE
102      01 WS-Output-Header-1-TXT.
103      05 VALUE '<-Addr-> Byte <----- Hexadecimal ''-----> <---
- Char ---->' PIC X(80).
104
105      01 WS-Output-Header-2-TXT.
106      05 VALUE '===== ====='
=====
' PIC X(80).
107      >>SOURCE FORMAT IS FIXED
108
109      LINKAGE SECTION.
110      01 L-Buffer-TXT                                PIC X ANY LENGTH.
111
112      01 L-Buffer-Length-NUM                          USAGE BINARY-LONG.
113
114      PROCEDURE DIVISION USING L-Buffer-TXT,
115                                  OPTIONAL L-Buffer-Length-NUM.
116      000-Main SECTION.
117          IF NUMBER-OF-CALL-PARAMETERS = 1
118              MOVE LENGTH(L-Buffer-TXT) TO WS-Buffer-Length-NUM
119          ELSE
120              MOVE L-Buffer-Length-NUM TO WS-Buffer-Length-NUM
121          END-IF
122          MOVE SPACES TO WS-Output-Detail-TXT
123          SET WS-Addr-PTR TO ADDRESS OF L-Buffer-TXT
124          PERFORM 100-Generate-Address
125          MOVE 0 TO WS-Output-SUB
126          DISPLAY WS-Output-Header-1-TXT UPON SYSERR
127          DISPLAY WS-Output-Header-2-TXT UPON SYSERR
128          PERFORM VARYING WS-Buffer-SUB FROM 1 BY 1
129              UNTIL WS-Buffer-SUB > WS-Buffer-Length-NUM
130              ADD 1 TO WS-Output-SUB
131              IF WS-Output-SUB = 1
132                  MOVE WS-Buffer-SUB TO WS-OD-Relative-Byte-NUM
133              END-IF
134              MOVE L-Buffer-TXT (WS-Buffer-SUB : 1)
135                  TO WS-OD-ASCII-CHR (WS-Output-SUB)
136                  WS-Buffer-Byte-CHR
137              DIVIDE WS-Buffer-Byte-NUM BY 16
138                  GIVING WS-Nibble-Left-SUB
139                  REMAINDER WS-Nibble-Right-SUB
140              ADD 1 TO WS-Nibble-Left-SUB
141                  WS-Nibble-Right-SUB
142              MOVE WS-Hex-Digit-CHR (WS-Nibble-Left-SUB)
143                  TO WS-OD-Hex-1-CHR (WS-Output-SUB)
144              MOVE WS-Hex-Digit-CHR (WS-Nibble-Right-SUB)
145                  TO WS-OD-Hex-2-CHR (WS-Output-SUB)
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement Page: 4

```
=====
146             IF WS-Output-SUB = 16
147                 CALL "C$PRINTABLE" USING WS-OD-ASCII-Data-TXT
148                 DISPLAY WS-Output-Detail-TXT UPON SYSERR
149                 MOVE SPACES TO WS-Output-Detail-TXT
150                 MOVE 0 TO WS-Output-SUB
151                 SET WS-Addr-PTR UP BY 16
152                 PERFORM 100-Generate-Address
153             END-IF
154         END-PERFORM
155     IF WS-Output-SUB > 0
156         CALL "C$PRINTABLE" USING WS-OD-ASCII-Data-TXT
157         DISPLAY WS-Output-Detail-TXT UPON SYSERR
158     END-IF
159     EXIT PROGRAM
160     .
161 100-Generate-Address SECTION.
162     MOVE 8 TO WS-Addr-SUB
163     MOVE WS-Addr-NUM TO WS-Addr-Value-NUM
164     MOVE ALL '0' TO WS-OD-Addr-TXT
165     PERFORM WITH TEST BEFORE UNTIL WS-Addr-Value-NUM = 0
166         DIVIDE WS-Addr-Value-NUM BY 16
167             GIVING WS-Addr-Value-NUM
168             REMAINDER WS-Nibble-SUB
169     ADD 1 TO WS-Nibble-SUB
170     MOVE WS-Hex-Digit-CHR (WS-Nibble-SUB)
171         TO WS-OD-Addr-Hex-CHR (WS-Addr-SUB)
172     SUBTRACT 1 FROM WS-Addr-SUB
173     END-PERFORM
174     .
=====
```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing 2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 5
COBDUMP	000-Main	116	PROCEDURE		
COBDUMP	100-Generate-Address	161	PROCEDURE	124	152
COBDUMP	L-Buffer-Length-NUM	112	LINKAGE	115	120
COBDUMP	L-Buffer-TXT	110	LINKAGE	114	118 123
				134	
COBDUMP	NUMBER-OF-CALL-PARAMETERS		PROCEDURE	117	
COBDUMP	WS-Addr-NUM	61	WORKING-STORAGE	163	
COBDUMP	WS-Addr-PTR	60	WORKING-STORAGE	61	123* 151*
COBDUMP	WS-Addr-SUB	64	WORKING-STORAGE	162*	171 172
COBDUMP	WS-Addr-Value-NUM	66	WORKING-STORAGE	163*	165 166
				167*	
COBDUMP	WS-Buffer-Byte-CHR	68	WORKING-STORAGE	136	
COBDUMP	WS-Buffer-Byte-NUM	69	WORKING-STORAGE	137	
COBDUMP	WS-Buffer-Length-NUM	71	WORKING-STORAGE	118*	120* 129
COBDUMP	WS-Buffer-SUB	73	WORKING-STORAGE	128*	129 132
				134	
COBDUMP	WS-Hex-Digit-CHR	76	WORKING-STORAGE	142	144 170
COBDUMP	WS-Hex-Digit-TXT	75	WORKING-STORAGE		
COBDUMP	WS-Nibble-Left-SUB	81	WORKING-STORAGE	138*	140* 142
COBDUMP	WS-Nibble-Right-SUB	83	WORKING-STORAGE	139*	141* 144
COBDUMP	WS-Nibble-SUB	79	WORKING-STORAGE	168*	169* 170
COBDUMP	WS-OD-Addr-Hex-CHR	87	WORKING-STORAGE	171*	
COBDUMP	WS-OD-Addr-TXT	86	WORKING-STORAGE	164*	
COBDUMP	WS-OD-ASCII-CHR	96	WORKING-STORAGE	135*	
COBDUMP	WS-OD-ASCII-Data-TXT	95	WORKING-STORAGE	147C	156C
COBDUMP	WS-OD-Hex-1-CHR	92	WORKING-STORAGE	143*	
COBDUMP	WS-OD-Hex-2-CHR	93	WORKING-STORAGE	145*	
COBDUMP	WS-OD-Hex-TXT	91	WORKING-STORAGE		
COBDUMP	WS-OD-Relative-Byte-NUM	89	WORKING-STORAGE	132*	
COBDUMP	WS-Output-Detail-TXT	85	WORKING-STORAGE	122*	148 149*
				157	
COBDUMP	WS-Output-Header-1-TXT	102	WORKING-STORAGE	126	
COBDUMP	WS-Output-Header-2-TXT	105	WORKING-STORAGE	127	
COBDUMP	WS-Output-SUB	99	WORKING-STORAGE	125*	130* 131
				135	143 145
				146	150* 155

3. Colors

Colors is a handy little GNU COBOL utility program that will produce a screen showing all possible combinations of:

- FOREGROUND-COLOR
- BACKGROUND-COLOR
- BLINKING (or absence of BLINKING)
- HIGHLIGHT, LOWLIGHT or absence of either (i.e. "Normal")
- REVERSE-VIDEO

Here is a sample of the screen generated by this program:

```

(Press ENTER when done)
LOWLIGHT  ----- HIGHLIGHT  LOWLIGHT  ----- HIGHLIGHT
-----
01234567  01234567  01234567  01234567  01234567  01234567
0 xxxxxxxx 0 xxxxxxxx 0 xxxxxxxx 0 xxxxxxxx 0 xxxxxxxx 0 xxxxxxxx
1 xxxxxxxx 1 xxxxxxxx 1 xxxxxxxx 1 xxxxxxxx 1 xxxxxxxx 1 xxxxxxxx
2 xxxxxxxx 2 xxxxxxxx 2 xxxxxxxx 2 xxxxxxxx 2 xxxxxxxx 2 xxxxxxxx
3 xxxxxxxx 3 xxxxxxxx 3 xxxxxxxx 3 xxxxxxxx 3 xxxxxxxx 3 xxxxxxxx
4 xxxxxxxx 4 xxxxxxxx 4 xxxxxxxx 4 xxxxxxxx 4 xxxxxxxx 4 xxxxxxxx
5 xxxxxxxx 5 xxxxxxxx 5 xxxxxxxx 5 xxxxxxxx 5 xxxxxxxx 5 xxxxxxxx
6 xxxxxxxx 6 xxxxxxxx 6 xxxxxxxx 6 xxxxxxxx 6 xxxxxxxx 6 xxxxxxxx
7 xxxxxxxx 7 xxxxxxxx 7 xxxxxxxx 7 xxxxxxxx 7 xxxxxxxx 7 xxxxxxxx

LOWLIGHT  ----- HIGHLIGHT  LOWLIGHT  ----- HIGHLIGHT
BLINK     BLINK     BLINK     BLINK     BLINK     BLINK
-----
01234567  01234567  01234567  01234567  01234567  01234567
0          0          0          0          0          0
1          1          1          1          1          1
2          2          2          2          2          2
3          3          3          3          3          3
4          4          4          4          4          4
5          5          5          5          5          5
6          6          6          6          6          6
7          7          7          7          7          7

```

The program source and cross-reference listing, produced using the GNU COBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 1

```

=====
1      >>SOURCE FREE
2 IDENTIFICATION DIVISION.
3 PROGRAM-ID. colors.
4 DATA DIVISION.
5 SCREEN SECTION.
6 01 S-COLORTST-SCR BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLANK SCREEN.
7 05 LINE 01.
8 10 COL 1 VALUE ' LOWLIGHT ----- HIGHLIGHT LOWLIGHT ----- HIGHLIGHT'.
9 05 LINE + 1.
10 10 COL 1 VALUE ' ----- ----- ----- ----- -----'.
11 05 LINE + 1.
12 10 COL 1 VALUE ' ----- ----- ----- REVERSE REVERSE REVERSE'.
13 05 LINE + 1.
14 10 COL 1 VALUE ' 01234567 01234567 01234567 01234567 01234567 01234567'.
15 05 LINE + 1.
16 10 COL 1 VALUE '0          0          0          0          0          0          '.
17 05 LINE + 1.
18 10 COL 1 VALUE '1          1          1          1          1          1          '.
19 05 LINE + 1.
20 10 COL 1 VALUE '2          2          2          2          2          2          '.
21 05 LINE + 1.
22 10 COL 1 VALUE '3      1      3      2      3      3      3      4      3      5      3      6      '.
23 05 LINE + 1.
24 10 COL 1 VALUE '4          4          4          4          4          4          '.
25 05 LINE + 1.
26 10 COL 1 VALUE '5          5          5          5          5          5          '.
27 05 LINE + 1.
28 10 COL 1 VALUE '6          6          6          6          6          6          '.
29 05 LINE + 1.
30 10 COL 1 VALUE '7          7          7          7          7          7          '.
31 05 LINE + 1.
32 10 COL 1 VALUE ' LOWLIGHT ----- HIGHLIGHT LOWLIGHT ----- HIGHLIGHT'.
33 05 LINE + 1.
34 10 COL 1 VALUE '      BLINK      BLINK      BLINK      BLINK      BLINK      BLINK'.
35 05 LINE + 1.
36 10 COL 1 VALUE ' ----- ----- ----- REVERSE REVERSE REVERSE'.
37 05 LINE + 1.
38 10 COL 1 VALUE ' 01234567 01234567 01234567 01234567 01234567 01234567'.
39 05 LINE + 1.
40 10 COL 1 VALUE '0          0          0          0          0          0          '.
41 05 LINE + 1.
42 10 COL 1 VALUE '1          1          1          1          1          1          '.
43 05 LINE + 1.
44 10 COL 1 VALUE '2          2          2          2          2          2          '.
45 05 LINE + 1.
46 10 COL 1 VALUE '3      7      3      8      3      9      3      10      3      11      3      12      '.
47 05 LINE + 1.
48 10 COL 1 VALUE '4          4          4          4          4          4          '.
49 05 LINE + 1.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 2

```

=====
50 10 COL 1 VALUE '5          5          5          5          5          5          '
51 05 LINE + 1.
52 10 COL 1 VALUE '6          6          6          6          6          6          '
53 05 LINE + 1.
54 10 COL 1 VALUE '7          7          7          7          7          7          '
55 *> #1
56 05 LINE 05.
57 10 COL 2  BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
58 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
59 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
60 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
61 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
62 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
63 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
64 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
65 05 LINE + 1.
66 10 COL 2  BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
67 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
68 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
69 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
70 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
71 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
72 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
73 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
74 05 LINE + 1.
75 10 COL 2  BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
76 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
77 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
78 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
79 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
80 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
81 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
82 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
83 05 LINE + 1.
84 10 COL 2  BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
85 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
86 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
87 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
88 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
89 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
90 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
91 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
92 05 LINE + 1.
93 10 COL 2  BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
94 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
95 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
96 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
97 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
98 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 3

```

=====
 99 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
100 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
101 05 LINE + 1.
102 10 COL 2 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
103 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
104 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
105 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
106 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
107 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
108 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
109 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
110 05 LINE + 1.
111 10 COL 2 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
112 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
113 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
114 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
115 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
116 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
117 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
118 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
119 05 LINE + 1.
120 10 COL 2 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
121 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
122 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
123 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
124 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
125 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
126 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
127 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
128 *> #2
129 05 LINE 05.
130 10 COL 12 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 VALUE 'X'.
131 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 VALUE 'X'.
132 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 VALUE 'X'.
133 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 VALUE 'X'.
134 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 VALUE 'X'.
135 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 VALUE 'X'.
136 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 VALUE 'X'.
137 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 VALUE 'X'.
138 05 LINE + 1.
139 10 COL 12 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 VALUE 'X'.
140 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 VALUE 'X'.
141 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 VALUE 'X'.
142 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 VALUE 'X'.
143 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 VALUE 'X'.
144 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 VALUE 'X'.
145 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 VALUE 'X'.
146 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 VALUE 'X'.
147 05 LINE + 1.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 4

```

=====
148 10 COL 12 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 VALUE 'X'.
149 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 VALUE 'X'.
150 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 VALUE 'X'.
151 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 VALUE 'X'.
152 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 VALUE 'X'.
153 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 VALUE 'X'.
154 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 VALUE 'X'.
155 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 VALUE 'X'.
156 05 LINE + 1.
157 10 COL 12 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 VALUE 'X'.
158 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 VALUE 'X'.
159 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 VALUE 'X'.
160 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 VALUE 'X'.
161 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 VALUE 'X'.
162 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 VALUE 'X'.
163 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 VALUE 'X'.
164 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 VALUE 'X'.
165 05 LINE + 1.
166 10 COL 12 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 VALUE 'X'.
167 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 VALUE 'X'.
168 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 VALUE 'X'.
169 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 VALUE 'X'.
170 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 VALUE 'X'.
171 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 VALUE 'X'.
172 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 VALUE 'X'.
173 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 VALUE 'X'.
174 05 LINE + 1.
175 10 COL 12 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 VALUE 'X'.
176 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 VALUE 'X'.
177 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 VALUE 'X'.
178 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 VALUE 'X'.
179 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 VALUE 'X'.
180 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 VALUE 'X'.
181 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 VALUE 'X'.
182 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 VALUE 'X'.
183 05 LINE + 1.
184 10 COL 12 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 VALUE 'X'.
185 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 VALUE 'X'.
186 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 VALUE 'X'.
187 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 VALUE 'X'.
188 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 VALUE 'X'.
189 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 VALUE 'X'.
190 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 VALUE 'X'.
191 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 VALUE 'X'.
192 05 LINE + 1.
193 10 COL 12 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 VALUE 'X'.
194 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 VALUE 'X'.
195 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 VALUE 'X'.
196 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 5

```

=====
197 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 VALUE 'X'.
198 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 VALUE 'X'.
199 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 VALUE 'X'.
200 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 VALUE 'X'.
201 *> #3
202 05 LINE 05.
203 10 COL 22 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
204 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
205 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
206 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
207 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
208 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
209 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
210 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
211 05 LINE + 1.
212 10 COL 22 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
213 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
214 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
215 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
216 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
217 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
218 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
219 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
220 05 LINE + 1.
221 10 COL 22 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
222 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
223 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
224 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
225 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
226 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
227 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
228 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
229 05 LINE + 1.
230 10 COL 22 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
231 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
232 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
233 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
234 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
235 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
236 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
237 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
238 05 LINE + 1.
239 10 COL 22 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
240 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
241 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
242 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
243 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
244 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
245 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 5

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 6

```

=====
246 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
247 05 LINE + 1.
248 10 COL 22 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
249 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
250 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
251 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
252 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
253 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
254 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
255 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
256 05 LINE + 1.
257 10 COL 22 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
258 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
259 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
260 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
261 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
262 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
263 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
264 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
265 05 LINE + 1.
266 10 COL 22 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
267 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
268 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
269 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
270 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
271 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
272 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
273 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
274 *> #4
275 05 LINE 05.
276 10 COL 32 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
277 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
278 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
279 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
280 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
281 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
282 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
283 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
284 05 LINE + 1.
285 10 COL 32 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
286 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
287 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
288 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
289 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
290 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
291 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
292 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
293 05 LINE + 1.
294 10 COL 32 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 6

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 7

```

=====
295 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
296 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
297 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
298 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
299 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
300 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
301 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
302 05 LINE + 1.
303 10 COL 32 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
304 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
305 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
306 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
307 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
308 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
309 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
310 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
311 05 LINE + 1.
312 10 COL 32 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
313 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
314 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
315 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
316 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
317 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
318 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
319 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
320 05 LINE + 1.
321 10 COL 32 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
322 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
323 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
324 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
325 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
326 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
327 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
328 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
329 05 LINE + 1.
330 10 COL 32 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
331 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
332 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
333 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
334 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
335 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
336 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
337 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
338 05 LINE + 1.
339 10 COL 32 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
340 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
341 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
342 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
343 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 7

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 8

```

=====
344 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
345 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
346 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
347 *> #5
348 05 LINE 05.
349 10 COL 42 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
350 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
351 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
352 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
353 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
354 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
355 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
356 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
357 05 LINE + 1.
358 10 COL 42 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
359 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
360 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
361 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
362 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
363 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
364 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
365 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
366 05 LINE + 1.
367 10 COL 42 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
368 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
369 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
370 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
371 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
372 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
373 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
374 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
375 05 LINE + 1.
376 10 COL 42 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
377 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
378 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
379 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
380 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
381 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
382 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
383 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
384 05 LINE + 1.
385 10 COL 42 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
386 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
387 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
388 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
389 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
390 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
391 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
392 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 8

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 9

```

=====
393 05 LINE + 1.
394 10 COL 42 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
395 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
396 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
397 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
398 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
399 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
400 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
401 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
402 05 LINE + 1.
403 10 COL 42 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
404 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
405 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
406 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
407 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
408 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
409 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
410 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
411 05 LINE + 1.
412 10 COL 42 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
413 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
414 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
415 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
416 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
417 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
418 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
419 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
420 *> #6
421 05 LINE 05.
422 10 COL 52 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
423 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
424 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
425 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
426 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
427 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
428 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
429 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
430 05 LINE + 1.
431 10 COL 52 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
432 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
433 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
434 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
435 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
436 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
437 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
438 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
439 05 LINE + 1.
440 10 COL 52 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
441 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 9

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 10

```

=====
442 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
443 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
444 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
445 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
446 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
447 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
448 05 LINE + 1.
449 10 COL 52 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
450 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
451 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
452 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
453 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
454 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
455 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
456 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
457 05 LINE + 1.
458 10 COL 52 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
459 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
460 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
461 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
462 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
463 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
464 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
465 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
466 05 LINE + 1.
467 10 COL 52 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
468 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
469 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
470 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
471 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
472 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
473 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
474 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
475 05 LINE + 1.
476 10 COL 52 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
477 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
478 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
479 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
480 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
481 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
482 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
483 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
484 05 LINE + 1.
485 10 COL 52 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
486 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
487 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
488 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
489 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
490 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 10

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 11

```

=====
491 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
492 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
493 *> #7
494 05 LINE 17.
495 10 COL 02 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
496 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
497 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
498 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
499 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
500 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
501 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
502 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
503 05 LINE + 1.
504 10 COL 02 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
505 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
506 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
507 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
508 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
509 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
510 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
511 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
512 05 LINE + 1.
513 10 COL 02 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
514 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
515 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
516 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
517 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
518 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
519 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
520 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
521 05 LINE + 1.
522 10 COL 02 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
523 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
524 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
525 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
526 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
527 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
528 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
529 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
530 05 LINE + 1.
531 10 COL 02 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
532 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
533 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
534 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
535 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
536 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
537 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
538 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
539 05 LINE + 1.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 11

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 12

```

=====
540 10 COL 02 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
541 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
542 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
543 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
544 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
545 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
546 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
547 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
548 05 LINE + 1.
549 10 COL 02 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
550 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
551 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
552 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
553 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
554 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
555 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
556 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
557 05 LINE + 1.
558 10 COL 02 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
559 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
560 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
561 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
562 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
563 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
564 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
565 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
566 *> #8
567 05 LINE 17.
568 10 COL 12 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
569 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
570 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
571 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
572 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
573 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
574 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
575 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
576 05 LINE + 1.
577 10 COL 12 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
578 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
579 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
580 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
581 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
582 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
583 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
584 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
585 05 LINE + 1.
586 10 COL 12 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
587 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
588 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 12

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 13

```

=====
589 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
590 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
591 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
592 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
593 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
594 05 LINE + 1.
595 10 COL 12 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
596 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
597 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
598 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
599 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
600 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
601 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
602 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
603 05 LINE + 1.
604 10 COL 12 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
605 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
606 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
607 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
608 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
609 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
610 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
611 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
612 05 LINE + 1.
613 10 COL 12 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
614 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
615 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
616 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
617 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
618 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
619 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
620 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
621 05 LINE + 1.
622 10 COL 12 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
623 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
624 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
625 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
626 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
627 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
628 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
629 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
630 05 LINE + 1.
631 10 COL 12 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
632 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
633 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
634 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
635 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
636 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
637 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 13

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 14

```

=====
638 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
639 *> #9
640 05 LINE 17.
641 10 COL 22 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
642 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
643 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
644 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
645 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
646 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
647 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
648 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
649 05 LINE + 1.
650 10 COL 22 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
651 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
652 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
653 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
654 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
655 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
656 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
657 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
658 05 LINE + 1.
659 10 COL 22 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
660 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
661 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
662 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
663 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
664 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
665 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
666 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
667 05 LINE + 1.
668 10 COL 22 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
669 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
670 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
671 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
672 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
673 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
674 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
675 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
676 05 LINE + 1.
677 10 COL 22 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
678 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
679 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
680 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
681 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
682 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
683 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
684 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
685 05 LINE + 1.
686 10 COL 22 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 14

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 15

```

=====
687 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
688 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
689 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
690 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
691 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
692 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
693 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
694 05 LINE + 1.
695 10 COL 22 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
696 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
697 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
698 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
699 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
700 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
701 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
702 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
703 05 LINE + 1.
704 10 COL 22 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
705 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
706 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
707 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
708 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
709 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
710 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
711 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
712 *> #10
713 05 LINE 17.
714 10 COL 32 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
715 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
716 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
717 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
718 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
719 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
720 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
721 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
722 05 LINE + 1.
723 10 COL 32 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
724 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
725 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
726 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
727 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
728 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
729 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
730 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
731 05 LINE + 1.
732 10 COL 32 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
733 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
734 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
735 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 15

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 16

```

=====
736 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
737 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
738 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
739 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
740 05 LINE + 1.
741 10 COL 32 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
742 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
743 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
744 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
745 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
746 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
747 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
748 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
749 05 LINE + 1.
750 10 COL 32 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
751 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
752 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
753 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
754 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
755 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
756 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
757 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
758 05 LINE + 1.
759 10 COL 32 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
760 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
761 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
762 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
763 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
764 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
765 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
766 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
767 05 LINE + 1.
768 10 COL 32 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
769 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
770 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
771 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
772 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
773 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
774 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
775 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
776 05 LINE + 1.
777 10 COL 32 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
778 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
779 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
780 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
781 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
782 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
783 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
784 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 16

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 17

```

=====
785 *> #11
786 05 LINE 17.
787 10 COL 42 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
788 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
789 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
790 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
791 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
792 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
793 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
794 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
795 05 LINE + 1.
796 10 COL 42 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
797 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
798 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
799 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
800 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
801 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
802 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
803 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
804 05 LINE + 1.
805 10 COL 42 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
806 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
807 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
808 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
809 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
810 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
811 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
812 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
813 05 LINE + 1.
814 10 COL 42 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
815 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
816 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
817 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
818 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
819 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
820 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
821 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
822 05 LINE + 1.
823 10 COL 42 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
824 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
825 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
826 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
827 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
828 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
829 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
830 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
831 05 LINE + 1.
832 10 COL 42 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
833 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 17

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 18

```

=====
834 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
835 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
836 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
837 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
838 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
839 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
840 05 LINE + 1.
841 10 COL 42 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
842 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
843 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
844 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
845 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
846 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
847 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
848 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
849 05 LINE + 1.
850 10 COL 42 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
851 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
852 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
853 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
854 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
855 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
856 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
857 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
858 *> #12
859 05 LINE 17.
860 10 COL 52 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
861 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
862 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
863 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
864 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
865 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
866 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
867 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
868 05 LINE + 1.
869 10 COL 52 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
870 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
871 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
872 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
873 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
874 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
875 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
876 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
877 05 LINE + 1.
878 10 COL 52 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
879 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
880 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
881 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
882 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 18

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

```

Line   Statement
=====
883 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
884 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
885 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
886 05 LINE + 1.
887 10 COL 52 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
888 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
889 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
890 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
891 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
892 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
893 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
894 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
895 05 LINE + 1.
896 10 COL 52 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
897 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
898 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
899 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
900 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
901 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
902 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
903 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
904 05 LINE + 1.
905 10 COL 52 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
906 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
907 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
908 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
909 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
910 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
911 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
912 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
913 05 LINE + 1.
914 10 COL 52 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
915 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
916 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
917 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
918 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
919 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
920 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
921 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
922 05 LINE + 1.
923 10 COL 52 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
924 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
925 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
926 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
927 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
928 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
929 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
930 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
931 PROCEDURE DIVISION.

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 19

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 20

```
=====
932 000-Main SECTION.
933 DISPLAY S-COLORTST-SCR
934 STOP RUN
935 .
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 20

```

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing                                2014/03/27
                                                                 C:/Users/tda010/Documents/Programs/Samples/colors.cbl
PROGRAM-ID      Identifier/Register/Function  Defn  Where Defined  References  Page: 21
=====
colors          000-Main                                932  PROCEDURE
colors          S-COLORTST-SCR                          6  SCREEN          933

```

4. DAY-FROM-DATE

DAY-FROM-DATE is a user-defined function that accepts a single numeric "USAGE DISPLAY" argument –æ either a 7-digit Julian date in the form *yyyyddd* or an 8-digit Gregorian date in the form *yyyymmdd*. This argument may be supplied either as a PIC 9(n) USAGE DISPLAY data item (n=7 or 8) or as a 7- or 8-digit numeric literal.

The subroutine will determine if the supplied date is a valid date in the year range 0000 thru 9999 and what day of the week that date fell on.

The value returned will be zero if the date argument was invalid or an integer in the range 1-7, representing Sunday thru Saturday.

In addition to general GNU COBOL concepts, this program provides a useful demonstration of the following:

- Coding a GNU COBOL user-defined function
- Using the "ANY LENGTH" data item attribute
- Using the "RETURNING" option in a subprogram
- Using the "DATE-OF-INTEGERS" intrinsic function
- Using the "C\$PARAMSIZE" built-in system subroutine

The program source and cross-reference listing, produced using the GNU COBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl

Line Statement

Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      FUNCTION-ID. DAY-FROM-DATE.
4      *>*****
5      *> This GNU COBOL user-defined function converts a Gregorian or **
6      *> Julian date into a numeric day of the week.                **
7      *>*****
8      *> Arguments:                                                **
9      *>                                                            **
10     *> Calendar-Date      A PIC 9 data item or numeric literal which **
11     *>                                                            **
12     *>                                                            **
13     *>                                                            **
14     *>                    7-digit value: Interpreted as a Julian date **
15     *>                                                            **
16     *>                    8-digit value: Interpreted as a Gregorian **
17     *>                    date in the form yyyymmdd                **
18     *>                                                            **
19     *> The result returned will be one of the following:          **
20     *>                                                            **
21     *> 0: The supplied date is invalid                            **
22     *> 1: The supplied date is a Sunday                          **
23     *> 2: The supplied date is a Monday                          **
24     *> .                                                            **
25     *> .                                                            **
26     *> .                                                            **
27     *> 7: The supplied date is a Saturday                        **
28     *>*****
29     ENVIRONMENT DIVISION.
30     CONFIGURATION SECTION.
31     REPOSITORY.
32     FUNCTION ALL INTRINSIC.
33     DATA DIVISION.
34     WORKING-STORAGE SECTION.
35     01 WS-Input-Date-DT.
36         05 WS-ID-YYYY-NUM                PIC 9(4).
37         05 WS-ID-MM-NUM                  PIC 9(2).
38         05 WS-ID-DD-NUM                  PIC 9(2).
39     01 WS-Y-NUM                          BINARY-LONG.
40     01 WS-M-NUM                          BINARY-LONG.
41     01 WS-Temp-NUM                       BINARY-LONG.
42     LINKAGE SECTION.
43     01 L-Input-Date-DT                   PIC 9 ANY LENGTH.
44     01 L-Output-Day-Num                  USAGE BINARY-LONG
45                                         SIGNED.
46     PROCEDURE DIVISION USING L-Input-Date-DT
47         RETURNING L-Output-Day-Num.
48     000-Main SECTION.
49     CALL "C$PARAMSIZE" USING 1
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl

Line Statement

Page: 2

```

=====
50      EVALUATE RETURN-CODE
51      WHEN 7
52          IF TEST-DAY-YYYYDDD(L-Input-Date-DT) > 0
53              MOVE 0 TO L-Output-Day-NUM
54              GOBACK
55          END-IF
56          MOVE DATE-OF-INTEGERS(INTEGERS-OF-DAY(L-Input-Date-DT))
57              TO WS-Input-Date-DT
58      WHEN 8
59          IF TEST-DATE-YYYYMMDD(L-Input-Date-DT) > 0
60              MOVE 0 TO L-Output-Day-NUM
61              GOBACK
62          END-IF
63          MOVE L-Input-Date-DT TO WS-Input-Date-DT
64      WHEN OTHER
65          MOVE 0 TO L-Output-Day-NUM
66          GOBACK
67      END-EVALUATE
68      *> IF january OR february
69      *>     y = year - 1
70      *>     m = month + 10
71      *> ELSE
72      *>     y = year
73      *>     m = month - 2
74      *> END-IF
75      *> For Gregorian calendar:
76      *>     result = (day + y + y/4 - y/100 + y/400 + (31*m)/12) mod 7
77      *> (All divisions are integer divisions, discarding any remainder)
78      IF WS-ID-MM-NUM = 1 OR 2
79          SUBTRACT 1 FROM WS-ID-YYYY-NUM GIVING WS-Y-NUM
80          ADD WS-ID-MM-NUM, 10 GIVING WS-M-NUM
81      ELSE
82          MOVE WS-ID-YYYY-NUM TO WS-Y-NUM
83          SUBTRACT 2 FROM WS-ID-MM-NUM GIVING WS-M-NUM
84      END-IF
85      COMPUTE L-Output-Day-NUM =
86          WS-ID-DD-NUM
87          + WS-Y-NUM
88          + INTEGER(WS-Y-NUM/4)
89          - INTEGER(WS-Y-NUM/100)
90          + INTEGER(WS-Y-NUM/400)
91          + INTEGER((31*WS-M-NUM)/12)
92      DIVIDE L-Output-Day-NUM BY 7
93          GIVING WS-Temp-NUM
94          REMAINDER L-Output-Day-NUM
95      ADD 1 TO L-Output-Day-NUM
96      GOBACK
97      .
98
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 3
DAY-FROM-DATE	000-Main	48	PROCEDURE		
DAY-FROM-DATE	L-Input-Date-DT	43	LINKAGE	46 59	52 63 56
DAY-FROM-DATE	L-Output-Day-NUM	44	LINKAGE	47 65* 94*	53* 85* 95* 60*
DAY-FROM-DATE	RETURN-CODE		PROCEDURE	50	
DAY-FROM-DATE	WS-ID-DD-NUM	38	WORKING-STORAGE	86	
DAY-FROM-DATE	WS-ID-MM-NUM	37	WORKING-STORAGE	78	80 83
DAY-FROM-DATE	WS-ID-YYYY-NUM	36	WORKING-STORAGE	79	82
DAY-FROM-DATE	WS-Input-Date-DT	35	WORKING-STORAGE	57*	63*
DAY-FROM-DATE	WS-M-NUM	40	WORKING-STORAGE	80*	83* 91
DAY-FROM-DATE	WS-Temp-NUM	41	WORKING-STORAGE	93*	
DAY-FROM-DATE	WS-Y-NUM	39	WORKING-STORAGE	79* 88	82* 89 87 90

=====
 GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

5. GCic

This is MUCH more than a mere demonstration program –æ it's also a very practical utility! The "GCic" (GNU COBOL Interactive Compiler) is a TUI (Textual User Interface) program that may be used as a full-screen interface to the "cobc" compiler. In addition, GCic can produce neat, concise and useful cross-reference listings of GNU COBOL programs, showing not only where user-defined names and built-in registers and intrinsic functions are referenced, but also where user-defined data items ARE MODIFIED by program code!

The program is well documented (IMHO) and you should find it fairly easy to follow. The GCic.cbl program was written to work with a native Windows or Windows/MinGW build of GNU COBOL as well as a Windows/Cygwin, UNIX or OS X build.

Source listings generated by GCic will show the original source code of your programs, with all indentation and comments preserved. Additionally, any COPYed code will be included in the listing immediately (in compressed form) following the COPY statement that triggered its inclusion into your program.

Cross-reference listings will show all user-defined data items and procedures as well as intrinsic function and special register references. In addition to showing the line numbers at which items were defined and referenced, those references that MODIFY the contents of the data item will have an asterisk appended to them.

In addition to general GNU COBOL concepts, this program provides a useful demonstration of the following:

- Creating a GNU COBOL compilation unit that consists of multiple programs
- Using CDF conditional compilation facilities
- Using the "SCREEN SECTION" and associated "ACCEPT" and "DISPLAY" statements
- Using "DECLARATIVES" to trap file I/O errors
- Using "FILE-STATUS"
- Using the "REPLACING" clause on a CDF "COPY" statement
- Using the following statements:
 - o "ACCEPT FROM COMMAND-LINE" statement
 - o "ACCEPT FROM DATE/TIME" statement
 - o "ACCEPT FROM ENVIRONMENT" statement
 - o "EXIT PERFORM" statement
 - o "EXIT SECTION" statement
 - o "INSPECT" statement
 - o "PERFORM FOREVER" statement
 - o "SEARCH ALL" statement
 - o "SET ENVIRONMENT" statement
 - o "SORT" statement
 - o "STRING" statement

- o "UNSTRING" statement
- Using the following built-in subroutines:
 - o "C\$JUSTIFY" built-in system subroutine
 - o "C\$SLEEP" built-in system subroutine
 - o "CBL_CHANGE_DIR" built-in system subroutine
 - o "CBL_CHECK_FILE_EXIST" built-in system subroutine
 - o "CBL_DELETE_FILE" built-in system subroutine
 - o "SYSTEM" built-in system subroutine
- Using the following intrinsic functions:
 - o "CONCATENATE" intrinsic function
 - o "LENGTH" intrinsic function
 - o "LOWER-CASE" intrinsic function
 - o "NUMVAL" intrinsic function
 - o "TRIM" intrinsic function
 - o "UPPER-CASE" intrinsic function
- Using the "COB-CRT-STATUS,Special Registers" special register
- Programmatically producing a report destined for either portrait or landscape printing

Here is a sample of the screen generated by this program:

```
GNU COBOL Compiler
GCic (2013/12/26 10:16) GNU COBOL 2.1 23NOV2013 Interactive Compilation
Filename: mathtest.cbl
Folder: E:\Programs\Samples
Set/Clr Switches Via F1-F9; Set Config Via F12; ENTER Key Compiles; ESC Quits
F1 Assume WITH DEBUGGING MODE F6 >"FUNCTION" Is Optional Current
F2 Procedure+Statement Trace F7 >Enable All Warnings Config:
F3 Make a Library (DLL) F8 Source Is Free-Format DEFAULT
F4 Execute If Compilation OK F9 >No COMP/BINARY Truncation
F5 Produce Full Listing
Extra "cobc" Switches, If Any ("-save-temps=xxx" Prevents Listings):
Program Execution Arguments, If Any:
GCic for Windows/MinGW Copyright (C) 2009-2013, Gary L. Cutler, GPL
```

The program source and cross-reference listing, produced using this program, begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      *> CONFIGURATION SETTINGS: Set these switches before compiling:
3      *>
4      *> LINEDRAW Set to:
5      *>   0   To use spaces (no lines)
6      *>   1   To use the line-drawing character set (PC codepage 437)
7      *>   2   To use conventional ASCII characters (+, -, |)
8      *>
9      *>           OSX USERS - To use the linedrawing character set,
10     *>           set your 'terminal' font to 'Lucida Console'
11     *>
12     *> OS       Set to one of the following:
13     *>           'CYGWIN'   For a Windows/Cygwin version
14     *>           'MINGW'    For a Windows/MinGW version
15     *>           'OSX'      For a Macintosh OSX version
16     *>           'UNIX'     For a Unix/Linux version
17     *>           'WINDOWS'  For a Native Windows version
18     *>
19     *> SELCHAR  Set to the desired single character to be used as the red
20     *>           'feature selected' character on the screen.
21     *>           SUGGESTIONS: '>', '* ', '= ', '+ '
22     *>
23     *> LPP      Set to maximum printable lines per page when the listing
24     *>           should be generated for LANDSCAPE orientation (can be over-
25     *>           ridden at execution time using the GCXREF_LINES environ-
26     *>           ment variable.
27     *>
28     *> LPPP     Set to maximum printable lines per page when the listing
29     *>           should be generated for PORTRAIT orientation (can be over-
30     *>           ridden at execution time using the GCXREF_LINES_PORT
31     *>           environment variable.
32     *>
33 GC0712 >>DEFINE CONSTANT LINEDRAW AS 1
34 GC0712 >>DEFINE CONSTANT OS AS 'MINGW'
35 GC0712 >>DEFINE CONSTANT SELCHAR AS '>'
36 GC1213 >>DEFINE CONSTANT LPP AS 60  *> LANDSCAPE (GCXREF_LINES)
37 GC1213 >>DEFINE CONSTANT LPPP AS 54  *> PORTRAIT (GCXREF_LINES_PORT)
38     *> -----
39     *> Now set these switches to establish initial (default) settings
40     *> for the various on-screen options. Set them to a value of
41     *> 0 if they are to be 'OFF' and 1 if they are to be 'ON'
42 GC1213*> (for F5, 1=ON (Landscape), 2=ON (Portrait))
43     *>
44 GC0712 >>DEFINE CONSTANT F1 AS 0  *> Assume WITH DEBUGGING MODE
45 GC0712 >>DEFINE CONSTANT F2 AS 0  *> Procedure+Statement Trace
46 GC0712 >>DEFINE CONSTANT F3 AS 0  *> Make A Library (DLL)
47 GC0712 >>DEFINE CONSTANT F4 AS 0  *> Execute If Compilation OK
48 GC1213 >>DEFINE CONSTANT F5 AS 0  *> Listings
49 GC0712 >>DEFINE CONSTANT F6 AS 1  *> "FUNCTION" Is Optional
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 2

```
=====
50 GC0712 >>DEFINE CONSTANT F7 AS 1 *> Enable All Warnings
51 GC0712 >>DEFINE CONSTANT F8 AS 0 *> Source Is Free-Format
52 GC0712 >>DEFINE CONSTANT F9 AS 1 *> No COMP/BINARY Truncation
53 GC0712 >>DEFINE CONSTANT F12 AS 4 *> Default config file (1-7):
54 *> 1 = BS2000
55 *> 2 = COBOL85
56 *> 3 = COBOL2002
57 *> 4 = DEFAULT
58 *> 5 = IBM
59 *> 6 = MF (i.e. Microfocus)
60 *> 7 = MVS
61 *> -----
62 *> END CONFIGURATION SETTINGS
```

```
=====
GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 3

```

=====
64      IDENTIFICATION DIVISION.
65      PROGRAM-ID. GCic.
66      *>*****
67      *> >NOTE< >NOTE< >NOTE< >NOTE< >NOTE< >NOTE< **
68      *> **
69      *> If this program is compiled with '-fdebugging-line', you **
70      *> will need to pipe SYSERR to a text file when executing GCic **
71      *> (by adding the text '> filename' to the end of the GCic **
72      *> command). You may also need to press the ENTER key when **
73      *> GCic is finished. **
74      *>*****
75      *> This program provides a Textual User Interface (TUI) to the **
76      *> process of compiling and (optionally) executing a GNU COBOL **
77      *> program. **
78      *> **
79      *> This programs execution syntax is as follows: **
80      *> **
81      *> GCic <program-path-and-filename> [ <switch>... ] **
82      *> **
83      *> Once executed, a display screen will be presented showing **
84      *> the compilation options that will be used. The user will **
85      *> have the opportunity to change options, specify new ones **
86      *> and specify any program execution arguments to be used if **
87      *> you select the 'Execute' option. When you press the Enter **
88      *> key the program will be compiled. **
89      *> **
90      *> The SCREEN SECTION contains an image of the screen. **
91      *> **
92      *> The '010-Parse-Args' section in the PROCEDURE DIVISION has **
93      *> documentation on switches and their function. **
94      *>*****
95      *> **
96      *> AUTHOR:          GARY L. CUTLER **
97      *>          Copyright (C) 2009-2014, Gary L. Cutler, GPL **
98      *> **
99      *> DATE-WRITTEN: June 14, 2009 **
100     *> **
101     *>*****
102     *> DATE CHANGE DESCRIPTION **
103     *> ===== **
104     *> GC0609 Don't display compiler messages file if compilation **
105     *> Is successful. Also don't display messages if the **
106     *> output file is busy (just put a message on the **
107     *> screen, leave the OC screen up & let the user fix **
108     *> the problem & resubmit. **
109     *> GC0709 When 'EXECUTE' is selected, a 'FILE BUSY' error will **
110     *> still cause the (old) executable to be launched. **
111     *> Also, the 'EXTRA SWITCHES' field is being ignored. **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 4

```

=====
112     *>      Changed the title bar to lowlighted reverse video & **
113     *>      the message area to highlighted reverse-video. **
114     *> GC0809 Add a SPACE in front of command-line args when **
115     *>      executing users program. Add a SPACE after the **
116     *>      -ftraceall switch when building cobc command. **
117     *> GC0909 Convert to work on Cygwin/Linux as well as MinGW **
118     *> GC0310 Virtualized the key codes for S-F1 thru S-F7 as they **
119     *>      differ depending upon whether PDCurses or NCurses is **
120     *>      being used. **
121     *> GC0410 Introduced the cross-reference and source listing **
122     *>      features. Also fixed a bug in EXTRA switch proces- **
123     *>      sing where garbage will result if more than the **
124     *>      EXTRA switch is specified. **
125     *> GC1010 Corrected several problems reported by Vince Coen: **
126     *>      1) Listing/Xref wouldn't work if '-I' additional **
127     *>      cobc switch specified. **
128     *>      2) Programs coded with lowercase reserved words did **
129     *>      not get parsed properly when generating listing **
130     *>      and/or xref reports. **
131     *>      3) Reliance on a TEMP environment variable caused **
132     *>      non-recoverable errors when generating listing **
133     *>      and/or xref reports in a session that lacks a **
134     *>      TEMP variable. **
135     *>      As a result of this change, GCic no longer runs a **
136     *>      second 'cobc' when generating listing and/or xref **
137     *>      reports. A '-save-temps' (without '=dir') specified **
138     *>      in the EXTRA options field will be ignored. A **
139     *>      '-save-temps=dir' specified in the EXTRA options **
140     *>      field will negate both the XREF and SOURCE opts, **
141     *>      if specified. **
142     *> GC0711 Tailored for 29APR2011 version of GNU COBOL 2.0 **
143     *> GC0712 Replaced all switches with configuration settings; **
144     *>      Tailored for 11FEB2012 version of GNU COBOL 2.0; **
145     *>      Reformatted screen layout to fit a 24x80 screen **
146     *>      rather than a 25x81 screen and to accommodate shell **
147     *>      environments having only F1-F12 (like 'terminal' in **
148     *>      OSX); Fully tested under OSX (required a few altera- **
149     *>      tions); Expanded both extra-options and runtime- **
150     *>      arguments areas to TWO lines (152 chars total) each; **
151     *>      Added support for MF/IBM/BS2000 listing-control **
152     *>      directives EJECT,SKIP1,SKIP2,SKIP3 (any of these in **
153     *>      copybooks will be ignored) **
154     *> GC0313 Expand the source code record from 80 chars to 256 **
155     *>      to facilitate looking for "LINKAGE SECTION" in a **
156     *>      free-format file. **
157     *> GC1113 Edited to support the change of "OpenCOBOL" to "GNU **
158     *>      COBOL" **
159     *> GC1213 Updated for 23NOV2013 version of GNU COBOL 2.1 **
160     *> GC0114 Introduce a "Press ENTER to Close" action after run- **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 5

```

=====
161      *>          ning the compiled program in the compiler window (F4)**
162      *>*****
163      ENVIRONMENT DIVISION.
164      CONFIGURATION SECTION.
165      REPOSITORY.
166          FUNCTION ALL INTRINSIC.
167      INPUT-OUTPUT SECTION.
168      FILE-CONTROL.
169 GC1010      SELECT F-Cobc-Output-FILE      ASSIGN TO WS-Listing-Filename-TXT
170                                         ORGANIZATION IS LINE SEQUENTIAL.
171
172          SELECT F-Source-Code-FILE      ASSIGN TO WS-File-Name-TXT
173                                         ORGANIZATION IS LINE SEQUENTIAL.
174                                         FILE STATUS IS WS-FSM-Status-CD.
=====

```

```

=====
GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 5

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 6

```
=====
176      DATA DIVISION.
177      FILE SECTION.
178      FD F-Cobc-Output-FILE.
179      01 F-Cobc-Output-REC                PIC X(256).
180
181      FD F-Source-Code-FILE.
182 GC0313 01 F-Source-Code-REC            PIC X(256).
183
184      WORKING-STORAGE SECTION.
185      COPY screenio.
186      78 COB-COLOR-BLACK VALUE 0.
187      78 COB-COLOR-BLUE VALUE 1.
188      78 COB-COLOR-GREEN VALUE 2.
189      78 COB-COLOR-CYAN VALUE 3.
190      78 COB-COLOR-RED VALUE 4.
191      78 COB-COLOR-MAGENTA VALUE 5.
192      78 COB-COLOR-YELLOW VALUE 6.
193      78 COB-COLOR-WHITE VALUE 7.
194      78 COB-SCR-OK VALUE 0.
195      78 COB-SCR-F1 VALUE 1001.
196      78 COB-SCR-F2 VALUE 1002.
197      78 COB-SCR-F3 VALUE 1003.
198      78 COB-SCR-F4 VALUE 1004.
199      78 COB-SCR-F5 VALUE 1005.
200      78 COB-SCR-F6 VALUE 1006.
201      78 COB-SCR-F7 VALUE 1007.
202      78 COB-SCR-F8 VALUE 1008.
203      78 COB-SCR-F9 VALUE 1009.
204      78 COB-SCR-F10 VALUE 1010.
205      78 COB-SCR-F11 VALUE 1011.
206      78 COB-SCR-F12 VALUE 1012.
207      78 COB-SCR-F13 VALUE 1013.
208      78 COB-SCR-F14 VALUE 1014.
209      78 COB-SCR-F15 VALUE 1015.
210      78 COB-SCR-F16 VALUE 1016.
211      78 COB-SCR-F17 VALUE 1017.
212      78 COB-SCR-F18 VALUE 1018.
213      78 COB-SCR-F19 VALUE 1019.
214      78 COB-SCR-F20 VALUE 1020.
215      78 COB-SCR-F21 VALUE 1021.
216      78 COB-SCR-F22 VALUE 1022.
217      78 COB-SCR-F23 VALUE 1023.
218      78 COB-SCR-F24 VALUE 1024.
219      78 COB-SCR-F25 VALUE 1025.
220      78 COB-SCR-F26 VALUE 1026.
221      78 COB-SCR-F27 VALUE 1027.
222      78 COB-SCR-F28 VALUE 1028.
223      78 COB-SCR-F29 VALUE 1029.
=====
```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 6

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 7

```

=====
78 COB-SCR-F30 VALUE 1030.
78 COB-SCR-F31 VALUE 1031.
78 COB-SCR-F32 VALUE 1032.
78 COB-SCR-F33 VALUE 1033.
78 COB-SCR-F34 VALUE 1034.
78 COB-SCR-F35 VALUE 1035.
78 COB-SCR-F36 VALUE 1036.
78 COB-SCR-F37 VALUE 1037.
78 COB-SCR-F38 VALUE 1038.
78 COB-SCR-F39 VALUE 1039.
78 COB-SCR-F40 VALUE 1040.
78 COB-SCR-F41 VALUE 1041.
78 COB-SCR-F42 VALUE 1042.
78 COB-SCR-F43 VALUE 1043.
78 COB-SCR-F44 VALUE 1044.
78 COB-SCR-F45 VALUE 1045.
78 COB-SCR-F46 VALUE 1046.
78 COB-SCR-F47 VALUE 1047.
78 COB-SCR-F48 VALUE 1048.
78 COB-SCR-F49 VALUE 1049.
78 COB-SCR-F50 VALUE 1050.
78 COB-SCR-F51 VALUE 1051.
78 COB-SCR-F52 VALUE 1052.
78 COB-SCR-F53 VALUE 1053.
78 COB-SCR-F54 VALUE 1054.
78 COB-SCR-F55 VALUE 1055.
78 COB-SCR-F56 VALUE 1056.
78 COB-SCR-F57 VALUE 1057.
78 COB-SCR-F58 VALUE 1058.
78 COB-SCR-F59 VALUE 1059.
78 COB-SCR-F60 VALUE 1060.
78 COB-SCR-F61 VALUE 1061.
78 COB-SCR-F62 VALUE 1062.
78 COB-SCR-F63 VALUE 1063.
78 COB-SCR-F64 VALUE 1064.
78 COB-SCR-PAGE_UP VALUE 2001.
78 COB-SCR-PAGE_DOWN VALUE 2002.
78 COB-SCR-KEY-UP VALUE 2003.
78 COB-SCR-KEY-DOWN VALUE 2004.
78 COB-SCR-ESC VALUE 2005.
78 COB-SCR-PRINT VALUE 2006.
78 COB-SCR-NO-FIELD VALUE 8000.
78 COB-SCR-TIME-OUT VALUE 8001.
78 COB-SCR-FATAL VALUE 9000.
78 COB-SCR-MAX-FIELD VALUE 9001.
186
187 GC0712 01 WS-Compilation-Switches-TXT.
188 GC0712 05 WS-CS-Args-TXT VALUE SPACES.
189 GC0712 10 WS-CS-Arg-H1-TXT PIC X(76).
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 7

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 8

```

=====
190 GC0712      10 WS-CS-Arg-H2-TXT                PIC X(76).
191 GC0712      05 WS-CS-FileNames-TXT.
192 GC0712      10 VALUE 'BS2000'                    PIC X(9).
193 GC0712      10 VALUE 'COBOL85'                 PIC X(9).
194 GC0712      10 VALUE 'COBOL2002'           PIC X(9).
195 GC0712      10 VALUE 'DEFAULT'           PIC X(9).
196 GC0712      10 VALUE 'IBM'                PIC X(9).
197 GC0712      10 VALUE 'MF'                PIC X(9).
198 GC0712      10 VALUE 'MVS'              PIC X(9).
199 GC0712      05 WS-CS-FileNames-Table-TXT REDEFINES WS-CS-FileNames-TXT.
200 GC0712      10 WS-CS-Filename-TXT          OCCURS 7 TIMES
201 GC0712      10 WS-CS-Filename-TXT          PIC X(9).
202 GC0712      >>IF F12 < 1
203 GC0712      05 WS-CS-Config-NUM      VALUE 4      PIC 9(1).
204 GC0712      >>ELIF F12 > 7
205 GC0712      05 WS-CS-Config-NUM      VALUE 4      PIC 9(1).
206 GC0712      >>ELSE
207 GC0712      05 WS-CS-Config-NUM      VALUE F12    PIC 9(1).
208 GC0712      >>END-IF
209 GC0712      05 WS-CS-Extra-TXT VALUE SPACES.
210 GC0712      10 WS-CS-Extra-H1-TXT        PIC X(76).
211 GC0712      10 WS-CS-Extra-H2-TXT        PIC X(76).
212 GC0712      05 WS-CS-Switch-Defaults-TXT.
213 GC0712      10 VALUE F1                  PIC 9(1). *> WS-CS-DEBUG-CHR
214 GC0712      10 VALUE F4                  PIC 9(1). *> WS-CS-EXECUTE-CHR
215 GC0712      10 VALUE F8                  PIC 9(1). *> WS-CS-FREE-CHR
216 GC0712      10 VALUE F3                  PIC 9(1). *> WS-CS-LIBRARY-CHR
217 GC0712      10 VALUE F5                  PIC 9(1). *> WS-CS-LISTING-CHR
218 GC0712      10 VALUE F6                  PIC 9(1). *> WS-CS-NOFUNC-CHR
219 GC0712      10 VALUE F9                  PIC 9(1). *> WS-CS-NOTRUNC-CHR
220 GC0712      10 VALUE F2                  PIC 9(1). *> WS-CS-TRACEALL-CHR
221 GC0712      10 VALUE F7                  PIC 9(1). *> WS-CS-WARNALL-CHR
222 GC0712      05 WS-CS-All-Switches-TXT REDEFINES
223 GC0712      WS-CS-Switch-Defaults-TXT.
224 GC0712      10 WS-CS-DEBUG-CHR          PIC X(1).
225 GC0712      10 WS-CS-EXECUTE-CHR       PIC X(1).
226 GC0712      10 WS-CS-FREE-CHR           PIC X(1).
227 GC0712      10 WS-CS-LIBRARY-CHR       PIC X(1).
228 GC0712      10 WS-CS-LISTING-CHR       PIC X(1).
229 GC0712      10 WS-CS-NOFUNC-CHR       PIC X(1).
230 GC0712      10 WS-CS-NOTRUNC-CHR       PIC X(1).
231 GC0712      10 WS-CS-TRACEALL-CHR      PIC X(1).
232 GC0712      10 WS-CS-WARNALL-CHR      PIC X(1).
233
234 GC0909 01 WS-Cmd-TXT                    PIC X(512).
235
236 GC0712 01 WS-Cmd-Args-TXT              PIC X(256).
237
238 GC0712 01 WS-Cmd-End-Quote-CHR        PIC X(1).
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 8

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 9

```

=====
239
240 GC0712 01  WS-Cmd-SUB                USAGE BINARY-LONG.
241
242         01  WS-Cobc-Cmd-TXT          PIC X(256) .
243
244         01  WS-Config-Fn-TXT         PIC X(12) .
245
246 GC1113 01  WS-Delete-Fn-TXT         PIC X(256) .
247
248         01  WS-File-Name-TXT.
249             05 WS-FN-CHR              OCCURS 256 TIMES
250                                     PIC X(1) .
251
252         01  WS-File-Status-Message-TXT.
253             05 VALUE 'Status Code: '  PIC X(13) .
254             05 WS-FSM-Status-CD       PIC 9(2) .
255             05 VALUE ', Meaning: '    PIC X(11) .
256             05 WS-FSM-Msg-TXT        PIC X(25) .
257
258 GC0909 01  WS-Horizontal-Line-TXT   PIC X(80) .
259 GC0909
260         01  WS-I-SUB                  USAGE BINARY-LONG.
261
262         01  WS-J-SUB                  USAGE BINARY-LONG.
263
264 GC1213 01  WS-Listing-CD VALUE F5    PIC 9(1) .
265
266 GC0712 01  WS-Listing-Filename-TXT   PIC X(256) .
267
268 GC1213 01  WS-Listing-TXT VALUE SPACES PIC X(27) .
269
270         01  WS-OC-Compile-DT          PIC XXXX/XX/XXBXX/XX.
271
272 GC0712 >>IF OS = 'CYGWIN'
273 GC0712 01  WS-OS-Dir-CHR              VALUE '/'          PIC X(1) .
274 GC0712 78  WS-OS-Exe-Ext-CONST       VALUE '.exe' .
275 GC0712 78  WS-OS-Lib-Ext-CONST       VALUE '.dll' .
276 GC0712 78  WS-OS-Lib-Type-CONST     VALUE 'DLL' .
277 GC0712 01  WS-OS-Type-CD             VALUE 2            PIC 9(1) .
278 GC0712 >>ELIF OS = 'MINGW'
279 GC0712 01  WS-OS-Dir-CHR              VALUE '\\'         PIC X(1) .
280 GC0712 78  WS-OS-Exe-Ext-CONST       VALUE '.exe' .
281 GC0712 78  WS-OS-Lib-Ext-CONST       VALUE '.dll' .
282 GC0712 78  WS-OS-Lib-Type-CONST     VALUE 'DLL' .
283 GC0712 01  WS-OS-Type-CD             VALUE 5            PIC 9(1) .
284 GC0712 >>ELIF OS = 'OSX'
285 GC0712 01  WS-OS-Dir-CHR              VALUE '/'          PIC X(1) .
286 GC0712 78  WS-OS-Exe-Ext-CONST       VALUE '' .
287 GC0712 78  WS-OS-Lib-Ext-CONST       VALUE '.dylib' .
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 9

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 10

```

=====
288 GC0712 78 WS-OS-Lib-Type-CONST VALUE 'DYLIB)'.
289 GC0712 01 WS-OS-Type-CD VALUE 4 PIC 9(1).
290 GC0712 >>ELIF OS = 'UNIX'
291 GC0712 01 WS-OS-Dir-CHR VALUE '/' PIC X(1).
292 GC0712 78 WS-OS-Exe-Ext-CONST VALUE ' '.
293 GC0712 78 WS-OS-Lib-Ext-CONST VALUE '.so'.
294 GC0712 78 WS-OS-Lib-Type-CONST VALUE 'SO)'.
295 GC0712 01 WS-OS-Type-CD VALUE 3 PIC 9(1).
296 GC0712 >>ELIF OS = 'WINDOWS'
297 GC0712 01 WS-OS-Dir-CHR VALUE '\' PIC X(1).
298 GC0712 78 WS-OS-Exe-Ext-CONST VALUE '.exe'.
299 GC0712 78 WS-OS-Lib-Ext-CONST VALUE '.dll'.
300 GC0712 78 WS-OS-Lib-Type-CONST VALUE 'DLL)'.
301 GC0712 01 WS-OS-Type-CD VALUE 1 PIC 9(1).
302 GC0712 >>END-IF
303 GC0909 88 WS-OS-Windows-BOOL VALUE 1, 5.
304 GC0909 88 WS-OS-Cygwin-BOOL VALUE 2.
305 GC0712 88 WS-OS-UNIX-BOOL VALUE 3, 4.
306 GC0712 88 WS-OS-OSX-BOOL VALUE 4.
307
308 01 WS-OS-Type-FILLER-TXT.
309 05 VALUE 'Windows' PIC X(14).
310 05 VALUE 'Windows/Cygwin' PIC X(14).
311 05 VALUE 'UNIX/Linux' PIC X(14).
312 05 VALUE 'OSX' PIC X(14).
313 05 VALUE 'Windows/MinGW' PIC X(14).
314 01 WS-OS-Types-TXT REDEFINES WS-OS-Type-FILLER-TXT.
315 05 WS-OS-Type-TXT OCCURS 5 TIMES
316 PIC X(14).
317
318 01 WS-Output-Msg-TXT PIC X(80).
319
320 01 WS-Path-Delimiter-CHR PIC X(1).
321
322 01 WS-Prog-Extension-TXT PIC X(256).
323
324 01 WS-Prog-Folder-TXT PIC X(256).
325
326 GC0712 01 WS-Prog-File-Name-TXT.
327 GC0712 05 WS-PFN-CHR OCCURS 256 TIMES
328 GC0712 PIC X(1).
329
330 GC0712 01 WS-Pgm-Nm-TXT PIC X(31).
331
332 01 WS-Runtime-Switches-TXT.
333 05 WS-RS-Compile-OK-CHR PIC X(1).
334 88 WS-RS-Compile-OK-BOOL VALUE 'Y'.
335 GC0909 88 WS-RS-Compile-OK-Warn-BOOL VALUE 'W'.
336 88 WS-RS-Compile-Failed-BOOL VALUE 'N'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 10

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 11

```

=====
337 GC0609      05 WS-RS-Complete-CHR          PIC X(1).
338 GC0609      88 WS-RS-Complete-BOOL          VALUE 'Y'.
339 GC0609      88 WS-RS-Not-Complete-BOOL        VALUE 'N'.
340 GC0712      05 WS-RS-Quote-CHR          PIC X(1).
341 GC0712      88 WS-RS-Double-Quote-Used-BOOL      VALUE 'Y' FALSE 'N'.
342 GC0809      05 WS-RS-IDENT-DIV-CHR          PIC X(1).
343 GC0809      88 WS-RS-1st-Prog-Complete-BOOL      VALUE 'Y'.
344 GC0809      88 WS-RS-More-To-1st-Prog-BOOL      VALUE 'N'.
345             05 WS-RS-No-Switch-Chgs-CHR      PIC X(1).
346             88 WS-RS-No-Switch-Changes-BOOL  VALUE 'Y'.
347             88 WS-RS-Switch-Changes-BOOL     VALUE 'N'.
348 GC0709      05 WS-RS-Output-File-Busy-CHR        PIC X(1).
349 GC0709      88 WS-RS-Output-File-Busy-BOOL   VALUE 'Y'.
350 GC0709      88 WS-RS-Output-File-Avail-BOOL   VALUE 'N'.
351 GC0809      05 WS-RS-Source-Record-Type-CHR    PIC X(1).
352 GC0809      88 WS-RS-Source-Rec-Linkage-BOOL  VALUE 'L'.
353 GC0809      88 WS-RS-Source-Rec-Ident-BOOL    VALUE 'I'.
354 GC0712      88 WS-RS-Source-Rec-Ignored-BOOL    VALUE ' '.
355             05 WS-RS-Switch-Error-CHR        PIC X(1).
356             88 WS-RS-Switch-Is-Bad-BOOL      VALUE 'Y'.
357             88 WS-RS-Switch-Is-Good-BOOL     VALUE 'N'.
358
359             01 WS-Tally-QTY                  USAGE BINARY-LONG.
=====

```

```

=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 11

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 12

```

=====
361     SCREEN SECTION.
362     *>
363     *> Here is the layout of the GCic screen.
364     *>
365     *> The sample screen below shows how the screen would look if the LINEDRAW
366     *> configuration setting is set to a value of 2
367     *>
368     *> The following sample screen layout shows how the screen looks with line-drawing
369     *> characters disabled.
370     *>
371     *>          1          2          3          4          5          6          7          8
372     *>1234567890123456789012345678901234567890123456789012345678901234567890
373     *>=====
374 01 *> GCic (2011/07/11 08:52) - GNU COBOL V2.1 23NOV2013 Interactive Compilation
375 02 *>+-----+
376 03 *>| Folder:   E:\GNU COBOL\Samples                                     |
377 04 *>| Filename: GCic.cbl                                             |
378 05 *>+-----+
379 06 *> Set/Clr Switches Via F1-F9; Set Config Via F12; ENTER Key Compiles; ESC Quits
380 07 *>+-----+
381 08 *>| F1  Assume WITH DEBUGGING MODE  F6  "FUNCTION" Is Optional      | Current  |
382 09 *>| F2  Procedure+Statement Trace   F7  Enable All Warnings        | Config:  |
383 10 *>| F3  Make A Library (DLL)        F8  Source Is Free-Format      | XXXXXXXX |
384 11 *>| F4  Execute If Compilation OK   F9  No COMP/BINARY Truncation  |          |
385 12 *>| F5  >Produce Listing (Landscape) |          |
386 13 *>+-----+
387 14 *> Extra "cobc" Switches, If Any ("-save-temps=xxx" Prevents Listings):
388 15 *>+-----+
389 16 *>| _____ |
390 17 *>| _____ |
391 18 *>+-----+
392 19 *> Program Execution Arguments, If Any:
393 20 *>+-----+
394 21 *>| _____ |
395 22 *>| _____ |
396 23 *>+-----+
397 24 *> GCic Copyright (C) 2009-2014, Gary L. Cutler, GPL
398     *>=====
399     *>1234567890123456789012345678901234567890123456789012345678901234567890
400     *>          1          2          3          4          5          6          7          8
401     *>
402     *> If this program is run on Windows, it must run with codepage 437 activated to
403     *> display the line-drawing characters.  With a native Windows build or a
404     *> Windows/MinGW build, one could use the command 'chcp 437' to set that codepage
405     *> for display within a Windows console window (that should be the default though).
406     *> With a Windows/Cygwin build, set the environment variable CYGWIN to a value of
407     *> 'codepage:oem' (this cannot be done from within the program though - you will
408     *> have to use the 'Computer/Advanced System Settings/Environment Variables' (Vista
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 12

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 13

```

=====
409      *> or Windows 7) function to define the variable.  XP Users: use 'My Computer/
410      *> Properties/Advanced/Environment Variables'.
411      *>
412      *> OSX users may use line drawing characters in this and any GNU COBOL program
413      *> simply by setting their 'terminal' application's font to "Lucida Console".
414      *>
415      >>IF LINEDRAW IS EQUAL TO 0
416          78 LD-UL-Corner          VALUE ' '.
417          78 LD-LL-Corner          VALUE ' '.
418          78 LD-UR-Corner          VALUE ' '.
419          78 LD-LR-Corner          VALUE ' '.
420          78 LD-Upper-T            VALUE ' '.
421          78 LD-Lower-T            VALUE ' '.
422          78 LD-Horiz-Line         VALUE ' '.
423          78 LD-Vert-Line          VALUE ' '.
424      >>ELIF LINEDRAW IS EQUAL TO 1
425          78 LD-UL-Corner          VALUE X'DA'.
426          78 LD-LL-Corner          VALUE X'CO'.
427          78 LD-UR-Corner          VALUE X'BF'.
428          78 LD-LR-Corner          VALUE X'D9'.
429          78 LD-Upper-T            VALUE X'C2'.
430          78 LD-Lower-T            VALUE X'C1'.
431          78 LD-Horiz-Line         VALUE X'C4'.
432          78 LD-Vert-Line          VALUE X'B3'.
433      >>ELSE
434          78 LD-UL-Corner          VALUE '+'.
435          78 LD-LL-Corner          VALUE '+'.
436          78 LD-UR-Corner          VALUE '+'.
437          78 LD-LR-Corner          VALUE '+'.
438          78 LD-Upper-T            VALUE '+'.
439          78 LD-Lower-T            VALUE '+'.
440          78 LD-Horiz-Line         VALUE '-'.
441          78 LD-Vert-Line          VALUE '|'.
442      >>END-IF
443
444      01 S-Blank-SCR LINE 1 COLUMN 1 BLANK SCREEN.
445
446      01 S-Switches-SCR BACKGROUND-COLOR COB-COLOR-BLACK
447                          FOREGROUND-COLOR COB-COLOR-WHITE AUTO.
448      *>
449      *> GENERAL SCREEN FRAMEWORK
450      *>
451          03 BACKGROUND-COLOR COB-COLOR-BLACK
452          FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
453 GC0712      05 LINE 02 COL 01          VALUE LD-UL-Corner.
454 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
455          05          COL 80          VALUE LD-UR-Corner.
456
457 GC0712      05 LINE 03 COL 01          VALUE LD-Vert-Line.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 13

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 14

```

=====
458          05          COL 80          VALUE LD-Vert-Line.
459
460 GC0712    05 LINE 04 COL 01          VALUE LD-Vert-Line.
461          05          COL 80          VALUE LD-Vert-Line.
462
463 GC0712    05 LINE 05 COL 01          VALUE LD-LL-Corner.
464 GC0712    05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
465          05          COL 80          VALUE LD-LR-Corner.
466
467 GC0712    05 LINE 07 COL 01          VALUE LD-UL-Corner.
468 GC0712    05          COL 02 PIC X(65) FROM WS-Horizontal-Line-TXT.
469 GC0712    05          COL 67          VALUE LD-Upper-T.
470 GC0712    05          COL 68 PIC X(12) FROM WS-Horizontal-Line-TXT.
471          05          COL 80          VALUE LD-UR-Corner.
472
473 GC0712    05 LINE 08 COL 01          VALUE LD-Vert-Line.
474 GC0712    05          COL 67          VALUE LD-Vert-Line.
475          05          COL 80          VALUE LD-Vert-Line.
476
477 GC0712    05 LINE 09 COL 01          VALUE LD-Vert-Line.
478 GC0712    05          COL 67          VALUE LD-Vert-Line.
479          05          COL 80          VALUE LD-Vert-Line.
480
481 GC0712    05 LINE 10 COL 01          VALUE LD-Vert-Line.
482 GC0712    05          COL 67          VALUE LD-Vert-Line.
483          05          COL 80          VALUE LD-Vert-Line.
484
485 GC0712    05 LINE 11 COL 01          VALUE LD-Vert-Line.
486 GC0712    05          COL 67          VALUE LD-Vert-Line.
487          05          COL 80          VALUE LD-Vert-Line.
488
489 GC0712    05 LINE 12 COL 01          VALUE LD-Vert-Line.
490 GC0712    05          COL 67          VALUE LD-Vert-Line.
491          05          COL 80          VALUE LD-Vert-Line.
492
493 GC0712    05 LINE 13 COL 01          VALUE LD-LL-Corner.
494 GC0712    05          COL 02 PIC X(65) FROM WS-Horizontal-Line-TXT.
495 GC0712    05          COL 67          VALUE LD-Lower-T.
496 GC0712    05          COL 68 PIC X(12) FROM WS-Horizontal-Line-TXT.
497          05          COL 80          VALUE LD-LR-Corner.
498
499 GC0712    05 LINE 15 COL 01          VALUE LD-UL-Corner.
500 GC0712    05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
501          05          COL 80          VALUE LD-UR-Corner.
502
503 GC0712    05 LINE 16 COL 01          VALUE LD-Vert-Line.
504          05          COL 80          VALUE LD-Vert-Line.
505
506 GC0712    05 LINE 17 COL 01          VALUE LD-Vert-Line.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 14

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 15

```

=====
507          05          COL 80          VALUE LD-Vert-Line.
508
509 GC0712    05 LINE 18 COL 01          VALUE LD-LL-Corner.
510 GC0712    05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
511          05          COL 80          VALUE LD-LR-Corner.
512
513 GC0712    05 LINE 20 COL 01          VALUE LD-UL-Corner.
514 GC0712    05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
515          05          COL 80          VALUE LD-UR-Corner.
516
517 GC0712    05 LINE 21 COL 01          VALUE LD-Vert-Line.
518          05          COL 80          VALUE LD-Vert-Line.
519
520 GC0712    05 LINE 22 COL 01          VALUE LD-Vert-Line.
521          05          COL 80          VALUE LD-Vert-Line.
522
523 GC0712    05 LINE 23 COL 01          VALUE LD-LL-Corner.
524 GC0712    05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
525          05          COL 80          VALUE LD-LR-Corner.
526          *>
527          *> TOP AND BOTTOM LINES
528          *>
529 GC0712    03 BACKGROUND-COLOR COB-COLOR-BLUE
530          FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
531 GC0410    05 LINE 01 COL 01 VALUE ' GCic ('.
532 GC0410    05          COL 08 PIC X(16) FROM WS-OC-Compile-DT.
533 GC1213    05          COL 24 VALUE ') GNU COBOL 2.1 23NOV2013 ' &
534 GC0410          'Interactive Compilation ' &
535 GC0712    03 BACKGROUND-COLOR COB-COLOR-RED BLINK
536 GC0712    FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
537 GC0712    05 LINE 24 COL 01 PIC X(80) FROM WS-Output-Msg-TXT.
538          *>
539          *> LABELS
540          *>
541          03 BACKGROUND-COLOR COB-COLOR-BLACK
542          FOREGROUND-COLOR COB-COLOR-CYAN HIGHLIGHT.
543 GC0712    05 LINE 06 COL 02 VALUE 'Set/Clr Switches Via F1-F9; ' &
544 GC0712          'Set Config Via F12; Enter Key ' &
545 GC0712          'Compiles; Esc Quits'.
546 GC0712    05 LINE 14 COL 02 VALUE 'Extra "cobc" Switches, If Any ' &
547 GC0712          '("-save-temps=xxx" Prevents ' &
548 GC0712          'Listings):'.
549 GC0712    05 LINE 19 COL 02 VALUE 'Program Execution Arguments, ' &
550 GC0712          'If Any:'.
551 GC0712    03 BACKGROUND-COLOR COB-COLOR-BLACK
552 GC0712    FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
553 GC0712    05 LINE 06 COL 23 VALUE 'F1'.
554 GC0712    05          COL 26 VALUE 'F9'.
555 GC0712    05          COL 45 VALUE 'F12'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 15

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 16

```

=====
556 GC0712      05          COL 50 VALUE 'ENTER'.
557 GC0712      05          COL 70 VALUE 'ESC'.
558             *>
559             *> TOP SECTION BACKGROUND
560             *>
561             03 BACKGROUND-COLOR COB-COLOR-BLACK
562             FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
563 GC0712      05 LINE 03 COL 62 VALUE 'Enter'.
564 GC0712      05 LINE 04 COL 62 VALUE 'Esc'.
565
566             03 BACKGROUND-COLOR COB-COLOR-BLACK
567             FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
568 GC0712      05 LINE 04 COL 03 VALUE 'Folder: '.
569 GC0712      05 LINE 03 COL 03 VALUE 'Filename: '.
570
571 GC0712      05 LINE 03 COL 67 VALUE ': Compile '.
572 GC0712      05 LINE 04 COL 65 VALUE ': Quit '.
573             *>
574             *> TOP SECTION PROGRAM INFO
575             *>
576             03 BACKGROUND-COLOR COB-COLOR-BLACK
577             FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
578 GC0712      05 LINE 03 COL 13 PIC X(66) FROM WS-Prog-File-Name-TXT.
579 GC0712      05 LINE 04 COL 13 PIC X(66) FROM WS-Prog-Folder-TXT.
580             *>
581             *> MIDDLE LEFT SECTION F-KEYS
582             *>
583             03 BACKGROUND-COLOR COB-COLOR-BLACK
584             FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
585 GC0712      05 LINE 08 COL 03 VALUE 'F1'.
586 GC0712      05 LINE 09 COL 03 VALUE 'F2'.
587 GC0712      05 LINE 10 COL 03 VALUE 'F3'.
588 GC0712      05 LINE 11 COL 03 VALUE 'F4'.
589 GC0712      05 LINE 12 COL 03 VALUE 'F5'.
590
591 GC0712      05 LINE 08 COL 35 VALUE 'F6'.
592 GC0712      05 LINE 09 COL 35 VALUE 'F7'.
593 GC0712      05 LINE 10 COL 35 VALUE 'F8'.
594 GC0712      05 LINE 11 COL 35 VALUE 'F9'.
595             *>
596             *> MIDDLE LEFT SECTION SWITCHES
597             *>
598             03 BACKGROUND-COLOR COB-COLOR-BLACK
599             FOREGROUND-COLOR COB-COLOR-RED HIGHLIGHT.
600 GC0712      05 LINE 08 COL 06 PIC X(1) FROM WS-CS-DEBUG-CHR.
601 GC0712      05 LINE 09 COL 06 PIC X(1) FROM WS-CS-TRACEALL-CHR.
602 GC0712      05 LINE 10 COL 06 PIC X(1) FROM WS-CS-LIBRARY-CHR.
603 GC0712      05 LINE 11 COL 06 PIC X(1) FROM WS-CS-EXECUTE-CHR.
604 GC0712      05 LINE 12 COL 06 PIC X(1) FROM WS-CS-LISTING-CHR.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 16

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 17

```

=====
605
606 GC0712      05 LINE 08 COL 38 PIC X(1) FROM WS-CS-NOFUNC-CHR.
607 GC0712      05 LINE 09 COL 38 PIC X(1) FROM WS-CS-WARNALL-CHR.
608 GC0712      05 LINE 10 COL 38 PIC X(1) FROM WS-CS-FREE-CHR.
609 GC0712      05 LINE 11 COL 38 PIC X(1) FROM WS-CS-NOTRUNC-CHR.
610             *>
611             *> MIDDLE LEFT SECTION BACKGROUND
612             *>
613             03 BACKGROUND-COLOR COB-COLOR-BLACK
614             FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
615 GC0712      05 LINE 08 COL 07 VALUE 'Assume WITH DEBUGGING MODE'.
616 GC0712      05 LINE 09 COL 07 VALUE 'Procedure+Statement Trace '.
617 GC0712      05 LINE 10 COL 07 VALUE 'Make a Library ('.
618 GC0712      05             COL 23 VALUE WS-OS-Lib-Type-CONST.
619 GC0712      05 LINE 11 COL 07 VALUE 'Execute If Compilation OK '.
620 GC1213      05 LINE 12 COL 07 FROM WS-Listing-TXT.
621
622 GC0712      05 LINE 08 COL 39 VALUE '"FUNCTION" Is Optional  '.
623 GC0712      05 LINE 09 COL 39 VALUE 'Enable All Warnings  '.
624 GC0712      05 LINE 10 COL 39 VALUE 'Source Is Free-Format  '.
625 GC0712      05 LINE 11 COL 39 VALUE 'No COMP/BINARY Truncation '.
626             *>
627             *> MIDDLE RIGHT SECTION Text
628             *>
629             03 BACKGROUND-COLOR COB-COLOR-BLACK
630             FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
631 GC0712      05 LINE 08 COL 69 VALUE 'Current'.
632 GC0712      05 LINE 09 COL 69 VALUE 'Config:'.
633             *>
634             *> MIDDLE RIGHT SECTION CONFIG FILE
635             *>
636             03 BACKGROUND-COLOR COB-COLOR-BLACK
637             FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
638 GC0712      05 LINE 10 COL 69 PIC X(10)
639 GC0712      FROM WS-CS-Filename-TXT (WS-CS-Config-NUM).
640             *>
641             *> FREE-FORM OPTIONS FIELDS
642             *>
643             03 BACKGROUND-COLOR COB-COLOR-BLACK
644             FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
645 GC0712      05 LINE 16 COL 03 PIC X(76) USING WS-CS-Extra-H1-TXT.
646 GC0712      05 LINE 17 COL 03 PIC X(76) USING WS-CS-Extra-H2-TXT.
647 GC0712      05 LINE 21 COL 03 PIC X(76) USING WS-CS-Arg-H1-TXT.
648 GC0712      05 LINE 22 COL 03 PIC X(76) USING WS-CS-Arg-H2-TXT.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 17

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 18

```

=====
650      PROCEDURE DIVISION.
651      *>*****
652      *> Legend to procedure names:                **
653      *>                                           **
654      *> 00x-xxx  All MAIN driver procedures      **
655      *> 0xx-xxx  All GLOBAL UTILITY procedures  **
656      *> 1xx-xxx  All INITIALIZATION procedures  **
657      *> 2xx-xxx  All CORE PROCESSING procedures **
658      *> 9xx-xxx  All TERMINATION procedures     **
659      *>*****
660      DECLARATIVES.
661      000-File-Error SECTION.
662      USE AFTER STANDARD ERROR PROCEDURE ON F-Source-Code-FILE.
663      COPY FileStat-Msgs
664      REPLACING STATUS BY WS-FSM-Status-CD
665      MSG      BY WS-FSM-Msg-TXT.

EVALUATE WS-FSM-Status-CD
WHEN 00 MOVE 'SUCCESS'           ' TO WS-FSM-Msg-TXT
WHEN 02 MOVE 'SUCCESS DUPLICATE' ' TO WS-FSM-Msg-TXT
WHEN 04 MOVE 'SUCCESS INCOMPLETE' ' TO WS-FSM-Msg-TXT
WHEN 05 MOVE 'SUCCESS OPTIONAL'   ' TO WS-FSM-Msg-TXT
WHEN 07 MOVE 'SUCCESS NO UNIT'    ' TO WS-FSM-Msg-TXT
WHEN 10 MOVE 'END OF FILE'        ' TO WS-FSM-Msg-TXT
WHEN 14 MOVE 'OUT OF KEY RANGE'   ' TO WS-FSM-Msg-TXT
WHEN 21 MOVE 'KEY INVALID'        ' TO WS-FSM-Msg-TXT
WHEN 22 MOVE 'KEY EXISTS'         ' TO WS-FSM-Msg-TXT
WHEN 23 MOVE 'KEY NOT EXISTS'     ' TO WS-FSM-Msg-TXT
WHEN 30 MOVE 'PERMANENT ERROR'    ' TO WS-FSM-Msg-TXT
WHEN 31 MOVE 'INCONSISTENT FILENAME' ' TO WS-FSM-Msg-TXT
WHEN 34 MOVE 'BOUNDARY VIOLATION' ' TO WS-FSM-Msg-TXT
WHEN 35 MOVE 'FILE NOT FOUND'     ' TO WS-FSM-Msg-TXT
WHEN 37 MOVE 'PERMISSION DENIED'  ' TO WS-FSM-Msg-TXT
WHEN 38 MOVE 'CLOSED WITH LOCK'   ' TO WS-FSM-Msg-TXT
WHEN 39 MOVE 'CONFLICT ATTRIBUTE' ' TO WS-FSM-Msg-TXT
WHEN 41 MOVE 'ALREADY OPEN'       ' TO WS-FSM-Msg-TXT
WHEN 42 MOVE 'NOT OPEN'           ' TO WS-FSM-Msg-TXT
WHEN 43 MOVE 'READ NOT DONE'      ' TO WS-FSM-Msg-TXT
WHEN 44 MOVE 'RECORD OVERFLOW'    ' TO WS-FSM-Msg-TXT
WHEN 46 MOVE 'READ ERROR'         ' TO WS-FSM-Msg-TXT
WHEN 47 MOVE 'INPUT DENIED'       ' TO WS-FSM-Msg-TXT
WHEN 48 MOVE 'OUTPUT DENIED'      ' TO WS-FSM-Msg-TXT
WHEN 49 MOVE 'I/O DENIED'         ' TO WS-FSM-Msg-TXT
WHEN 51 MOVE 'RECORD LOCKED'      ' TO WS-FSM-Msg-TXT
WHEN 52 MOVE 'END-OF-PAGE'        ' TO WS-FSM-Msg-TXT
WHEN 57 MOVE 'I/O LINAGE'         ' TO WS-FSM-Msg-TXT
WHEN 61 MOVE 'FILE SHARING FAILURE' ' TO WS-FSM-Msg-TXT
WHEN 91 MOVE 'FILE NOT AVAILABLE' ' TO WS-FSM-Msg-TXT
END-EVALUATE.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 18

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 19

```

=====
666         MOVE SPACES TO WS-Output-Msg-TXT
667         IF WS-FSM-Status-CD = 35
668             DISPLAY
669                 'File not found: ''
670                 TRIM(WS-File-Name-TXT,TRAILING)
671                 ','
672         ELSE
673             DISPLAY
674                 'Error accessing file: ''
675                 TRIM(WS-File-Name-TXT,TRAILING)
676                 ','
677         END-IF
678         GOBACK
679         .
680     END DECLARATIVES.
681
682     000-Main SECTION.
683         PERFORM 100-Initialization
684 GC0609     SET WS-RS-Not-Complete-BOOL TO TRUE
685 GC0609     PERFORM UNTIL WS-RS-Complete-BOOL
686 GC0609         PERFORM 200-Let-User-Set-Switches
687 GC0609         PERFORM 210-Run-Compiler
688 GC0410     IF (WS-RS-Compile-OK-BOOL OR WS-RS-Compile-OK-Warn-BOOL)
689 GC0712     AND (WS-CS-LISTING-CHR > SPACE)
690 GC0712         DISPLAY S-Blank-SCR
691 GC0410     PERFORM 220-Make-Listing
692 GC0410     END-IF
693 GC0709     IF (WS-CS-EXECUTE-CHR NOT = SPACES)
694 GC0709     AND (WS-RS-Output-File-Avail-BOOL)
695 GC0609         PERFORM 230-Run-Program
696 GC0609     END-IF
697 GC0712     PERFORM 250-Autoload-Listing
698 GC0609     END-PERFORM
699         PERFORM 900-Terminate
700     * -- Control will NOT return
701     .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 19

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 20

```

=====
703      *>*****
704      *> Perform all program-wide initialization operations      **
705      *>*****
706      100-Initialization SECTION.
707      *>*****
708      *> Make sure full screen-handling is in effect          **
709      *>*****
710      SET ENVIRONMENT 'COB_SCREEN_EXCEPTIONS' TO 'Y'
711      SET ENVIRONMENT 'COB_SCREEN_ESC' TO 'Y'
712      *>*****
713      *> Get GCic Compilation Date/Time                        **
714      *>*****
715      MOVE WHEN-COMPILED (1:12) TO WS-OC-Compile-DT
716      INSPECT WS-OC-Compile-DT
717      REPLACING ALL '/' BY ':'
718      AFTER INITIAL SPACE
719      *>*****
720      *> Convert WS-CS-All-Switches-TXT to Needed Alphanumeric Values**
721      *>*****
722      INSPECT WS-CS-All-Switches-TXT
723      REPLACING ALL '0' BY SPACE
724      ALL '1' BY SELCHAR
725 GC1213 ALL '2' BY SELCHAR
726      *>*****
727      *> Process filename (the only command-line argument)    **
728      *>*****
729 GC0712 ACCEPT WS-Cmd-Args-TXT FROM COMMAND-LINE
730 GC0712 MOVE 1 TO WS-Cmd-SUB
731 GC0712 IF WS-Cmd-Args-TXT(WS-Cmd-SUB:1) = ''' OR '''
732 GC0712 MOVE WS-Cmd-Args-TXT(WS-Cmd-SUB:1)
733 GC0712 TO WS-Cmd-End-Quote-CHR
734 GC0712 ADD 1 TO WS-Cmd-SUB
735 GC0712 UNSTRING WS-Cmd-Args-TXT
736 GC0712 DELIMITED BY WS-Cmd-End-Quote-CHR
737 GC0712 INTO WS-File-Name-TXT
738 GC0712 WITH POINTER WS-Cmd-SUB
739 GC0712 ELSE
740 GC0712 UNSTRING WS-Cmd-Args-TXT
741 GC0712 DELIMITED BY ALL SPACES
742 GC0712 INTO WS-File-Name-TXT
743 GC0712 WITH POINTER WS-Cmd-SUB
744 GC0712 END-IF
745      IF WS-File-Name-TXT = SPACES
746 GC0712 DISPLAY 'No program filename was specified'
747      PERFORM 900-Terminate
748      * ----- Control will NOT return
749      END-IF
750      *>*****
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 20

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 21

```

=====
751     *> Determine if 'Make A Library' feature should be forced 'ON' **
752     *>*****
753         PERFORM 240-Find-LINKAGE-SECTION
754     *>*****
755     *> Split 'WS-File-Name-TXT' into 'WS-Prog-Folder-TXT' and **
756     *> 'WS-Prog-File-Name-TXT' **
757     *>*****
758 GC0909     IF WS-OS-Cygwin-BOOL AND WS-File-Name-TXT (2:1) = ':'
759 GC0712         MOVE '\ ' TO WS-OS-Dir-CHR
760 GC0909     END-IF
761 GC0712     MOVE LENGTH(WS-File-Name-TXT) TO WS-I-SUB
762 GC0712     PERFORM UNTIL WS-I-SUB = 0
763 GC0712         OR WS-FN-CHR (WS-I-SUB) = WS-OS-Dir-CHR
764             SUBTRACT 1 FROM WS-I-SUB
765     END-PERFORM
766     IF WS-I-SUB = 0
767         MOVE SPACES TO WS-Prog-Folder-TXT
768         MOVE WS-File-Name-TXT TO WS-Prog-File-Name-TXT
769     ELSE
770         MOVE '*' TO WS-FN-CHR (WS-I-SUB)
771         UNSTRING WS-File-Name-TXT DELIMITED BY '*'
772             INTO WS-Prog-Folder-TXT
773                 WS-Prog-File-Name-TXT
774 GC0712     MOVE WS-OS-Dir-CHR TO WS-FN-CHR (WS-I-SUB)
775     END-IF
776     IF WS-Prog-Folder-TXT = SPACES
777         ACCEPT WS-Prog-Folder-TXT FROM ENVIRONMENT 'CD'
778 GC0909     ELSE
779 GC0909         CALL 'CBL_CHANGE_DIR'
780 GC0909         USING TRIM(WS-Prog-Folder-TXT,TRAILING)
781     END-IF
782 GC0909     IF WS-OS-Cygwin-BOOL AND WS-File-Name-TXT (2:1) = ':'
783 GC0712         MOVE '/' TO WS-OS-Dir-CHR
784 GC0909     END-IF
785     *>*****
786     *> Split 'WS-Prog-File-Name-TXT' into 'WS-Pgm-Nm-TXT' & **
787     *> 'WS-Prog-Extension-TXT' **
788     *>*****
789 GC0712     MOVE LENGTH(WS-Prog-File-Name-TXT) TO WS-I-SUB
790 GC0712     PERFORM UNTIL WS-I-SUB = 0
791 GC0712         OR WS-PFN-CHR (WS-I-SUB) = '.'
792 GC0712         SUBTRACT 1 FROM WS-I-SUB
793 GC0712     END-PERFORM
794 GC0712     IF WS-I-SUB = 0
795 GC0712         MOVE WS-Prog-File-Name-TXT TO WS-Pgm-Nm-TXT
796 GC0712         MOVE SPACES TO WS-Prog-Extension-TXT
797 GC0712     ELSE
798 GC0712         MOVE '*' TO WS-PFN-CHR (WS-I-SUB)
799 GC0712         UNSTRING WS-Prog-File-Name-TXT DELIMITED BY '*'
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 21

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 22

```
=====
800 GC0712          INTO WS-Pgm-Nm-TXT
801 GC0712          WS-Prog-Extension-TXT
802 GC0712          MOVE '.' TO WS-PFN-CHR (WS-I-SUB)
803 GC0712          END-IF
804                *>*****
805                *> Build initial Line 24 Message                **
806                *>*****
807 GC0909          MOVE ALL LD-Horiz-Line TO WS-Horizontal-Line-TXT.
808 GC0410          MOVE CONCATENATE(' GCic for '
809 GC0410          TRIM(WS-OS-Type-TXT(WS-OS-Type-CD),Trailing)
810 GC1213          ' Copyright (C) 2009-2014, Gary L. '
811 GC0410          'Cutler, GPL')
812 GC0410          TO WS-Output-Msg-TXT.
813 GC0909          .
=====
```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 22

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 23

```

=====
815      *>*****
816      *> Show the user the current switch settings and allow them to **
817      *> be changed. **
818      *>*****
819      200-Let-User-Set-Switches SECTION.
820          SET WS-RS-Switch-Changes-BOOL TO TRUE
821          PERFORM UNTIL WS-RS-No-Switch-Changes-BOOL
822 GC1213      EVALUATE WS-Listing-CD
823 GC1213          WHEN 0
824 GC1213              MOVE 'Listing Off'          TO WS-Listing-TXT
825 GC1213              MOVE SPACE                TO WS-CS-LISTING-CHR
826 GC1213          WHEN 1
827 GC1213              MOVE 'Listing On (Landscape)' TO WS-Listing-TXT
828 GC1213              MOVE SELCHAR              TO WS-CS-LISTING-CHR
829 GC1213          WHEN 2
830 GC1213              MOVE 'Listing On (Portrait)' TO WS-Listing-TXT
831 GC1213              MOVE SELCHAR              TO WS-CS-LISTING-CHR
832 GC1213          END-EVALUATE
833          ACCEPT S-Switches-SCR
834          IF COB-CRT-STATUS > 0
835              EVALUATE COB-CRT-STATUS
836                  WHEN COB-SCR-F1
837                      IF WS-CS-DEBUG-CHR = SPACE
838 GC0712                          MOVE SELCHAR TO WS-CS-DEBUG-CHR
839                      ELSE
840                          MOVE ' ' TO WS-CS-DEBUG-CHR
841                      END-IF
842 GC0712                  WHEN COB-SCR-F2
843 GC0712                      IF WS-CS-TRACEALL-CHR = SPACE
844 GC0712                          MOVE SELCHAR TO WS-CS-TRACEALL-CHR
845 GC0712                      ELSE
846 GC0712                          MOVE ' ' TO WS-CS-TRACEALL-CHR
847 GC0712                      END-IF
848                  WHEN COB-SCR-F3
849 GC0712                      IF WS-CS-LIBRARY-CHR = SPACE
850 GC0712                          MOVE SELCHAR TO WS-CS-LIBRARY-CHR
851                      ELSE
852 GC0712                          MOVE ' ' TO WS-CS-LIBRARY-CHR
853                      END-IF
854                  WHEN COB-SCR-F4
855 GC0712                      IF WS-CS-EXECUTE-CHR = SPACE
856 GC0712                          MOVE SELCHAR TO WS-CS-EXECUTE-CHR
857                      ELSE
858                          MOVE ' ' TO WS-CS-EXECUTE-CHR
859                      END-IF
860 GC0712                  WHEN COB-SCR-F5
861 GC1213                      ADD 1 TO WS-Listing-CD
862 GC1213                      IF WS-Listing-CD > 2
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 23

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 24

```

=====
863 GC1213                MOVE 0 TO WS-Listing-CD
864 GC1213                END-IF
865 GC0712                WHEN COB-SCR-F6
866 GC0712                IF WS-CS-NOFUNC-CHR = SPACE
867 GC0712                MOVE SELCHAR TO WS-CS-NOFUNC-CHR
868 GC0712                ELSE
869 GC0712                MOVE ' ' TO WS-CS-NOFUNC-CHR
870 GC0712                END-IF
871 GC0712                WHEN COB-SCR-F7
872 GC0712                IF WS-CS-WARNALL-CHR = SPACE
873 GC0712                MOVE SELCHAR TO WS-CS-WARNALL-CHR
874 GC0712                ELSE
875 GC0712                MOVE ' ' TO WS-CS-WARNALL-CHR
876 GC0712                END-IF
877 GC0712                WHEN COB-SCR-F8
878 GC0712                IF WS-CS-FREE-CHR = SPACE
879 GC0712                MOVE SELCHAR TO WS-CS-FREE-CHR
880 GC0712                ELSE
881 GC0712                MOVE ' ' TO WS-CS-FREE-CHR
882 GC0712                END-IF
883 GC0712                WHEN COB-SCR-F9
884 GC0712                IF WS-CS-NOTRUNC-CHR = SPACE
885 GC0712                MOVE SELCHAR TO WS-CS-NOTRUNC-CHR
886 GC0712                ELSE
887 GC0712                MOVE ' ' TO WS-CS-NOTRUNC-CHR
888 GC0712                END-IF
889                        WHEN COB-SCR-ESC
890                        PERFORM 900-Terminate
891 * ----- Control will NOT return
892 GC0712                WHEN COB-SCR-F12
893 GC0712                ADD 1 TO WS-CS-Config-NUM
894 GC0712                IF WS-CS-Config-NUM > 7
895 GC0712                MOVE 1 TO WS-CS-Config-NUM
896 GC0712                END-IF
897                        WHEN OTHER
898                        MOVE 'An unsupported key was pressed'
899                        TO WS-Output-Msg-TXT
900                        END-EVALUATE
901                        ELSE
902                        SET WS-RS-No-Switch-Changes-BOOL TO TRUE
903                        END-IF
904                END-PERFORM
905                .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 24

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 25

```

=====
907      *>*****
908      *> Run the compiler using the switch settings we've prepared. **
909      *>*****
910      210-Run-Compiler SECTION.
911          MOVE SPACES TO WS-Cmd-TXT
912              WS-Cobc-Cmd-TXT
913              WS-Output-Msg-TXT
914      DISPLAY S-Switches-SCR
915      MOVE 1 TO WS-I-SUB
916 GC0712  MOVE LOWER-CASE(WS-CS-Filename-TXT (WS-CS-Config-NUM))
917 GC0712  TO WS-Config-Fn-TXT
918      *>*****
919      *> Build the 'cobc' command **
920      *>*****
921 GC0909  MOVE SPACES TO WS-Cobc-Cmd-TXT
922 GC0909  STRING 'cobc -v -std='
923 GC0909  TRIM(WS-Config-Fn-TXT,TRAILING)
924 GC0909  ' '
925 GC0909  INTO WS-Cobc-Cmd-TXT
926 GC0909  WITH POINTER WS-I-SUB
927      IF WS-CS-LIBRARY-CHR NOT = ' '
928          STRING '-m '
929              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
930              WITH POINTER WS-I-SUB
931      ELSE
932          STRING '-x '
933              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
934              WITH POINTER WS-I-SUB
935      END-IF
936      IF WS-CS-DEBUG-CHR NOT = ' '
937          STRING '-fdebugging-line '
938              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
939              WITH POINTER WS-I-SUB
940      END-IF
941      IF WS-CS-NOTRUNC-CHR NOT = ' '
942          STRING '-fnotrunc '
943              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
944              WITH POINTER WS-I-SUB
945      END-IF
946      IF WS-CS-TRACEALL-CHR NOT = ' '
947 GC0809  STRING '-ftraceall '
948              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
949              WITH POINTER WS-I-SUB
950      END-IF
951 GC0712  IF WS-CS-NOFUNC-CHR NOT = ' '
952 GC0712  STRING '-fintrinsic=all '
953 GC0712  DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
954 GC0712  WITH POINTER WS-I-SUB
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 25

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 26

```

=====
955 GC0712      END-IF
956 GC0712      IF WS-CS-WARNALL-CHR NOT = ' '
957 GC0712          STRING '-Wall '
958 GC0712              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
959 GC0712              WITH POINTER WS-I-SUB
960 GC0712      END-IF
961 GC0712      IF WS-CS-FREE-CHR NOT = ' '
962 GC0712          STRING '-free '
963 GC0712              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
964 GC0712              WITH POINTER WS-I-SUB
965 GC0712      ELSE
966 GC0712          STRING '-fixed '
967 GC0712              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
968 GC0712              WITH POINTER WS-I-SUB
969 GC0712      END-IF
970
971 GC0712      MOVE 0 TO WS-Tally-QTY
972 GC0712      INSPECT WS-CS-Extra-TXT
973 GC0712          TALLYING WS-Tally-QTY FOR ALL '-save-temps'
974 GC0712      IF WS-CS-LISTING-CHR > SPACE
975 GC0712      AND WS-Tally-QTY > 0
976 GC0712          MOVE SPACE TO WS-CS-LISTING-CHR *> Can't generate listing if -save-temps u
          sed
977 GC0712      END-IF
978 GC0712      IF WS-CS-LISTING-CHR > SPACE
979 GC1010          STRING '-save-temps '
980 GC1010              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
981 GC1010              WITH POINTER WS-I-SUB
982 GC1010      END-IF
983
984 GC0709      IF WS-CS-Extra-TXT > SPACES
985 GC0709          STRING ' '
986 GC0709              TRIM(WS-CS-Extra-TXT,TRAILING)
987 GC0709              ' '
988 GC0709              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
989 GC0709              WITH POINTER WS-I-SUB
990 GC0709      END-IF
991 GC0909      STRING TRIM(WS-Prog-File-Name-TXT,TRAILING)
992 GC0909          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
993 GC0909          WITH POINTER WS-I-SUB
994          *>*****
995          *> Prepare the compilation listing file **
996          *>*****
997 GC1113      MOVE CONCATENATE(TRIM(WS-Pgm-Nm-TXT,Trailing),'.gclst')
998 GC0712          TO WS-Listing-Filename-TXT
999 GC0712      CALL 'CBL_DELETE_FILE' USING WS-Listing-Filename-TXT
1000          *>*****
1001          *> Now execute the 'cobc' command **
1002          *>*****
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 26

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 27

```

=====
1003 GC0410    MOVE ' Compiling...' TO WS-Output-Msg-TXT
1004 GC0410    DISPLAY S-Switches-SCR
1005 GC0609    SET WS-RS-Output-File-Avail-BOOL TO TRUE
1006          MOVE SPACES TO WS-Cmd-TXT
1007          STRING TRIM(WS-Cobc-Cmd-TXT,TRAILING)
1008 GC0712          ' >' WS-Listing-Filename-TXT
1009 GC0712          ' 2>&1'
1010          DELIMITED SIZE
1011          INTO WS-Cmd-TXT
1012 DEBUG D    DISPLAY WS-Cmd-TXT UPON SYSERR
1013          CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1014 GC0712    OPEN EXTEND F-Cobc-Output-FILE
1015 GC0712    WRITE F-Cobc-Output-REC FROM SPACES
1016 GC0712    IF RETURN-CODE = 0
1017 GC0712          SET WS-RS-Compile-OK-BOOL TO TRUE
1018 GC0712          MOVE ' Compilation Was Successful' TO WS-Output-Msg-TXT
1019 GC0712          MOVE CONCATENATE('GNU COBOL',WS-Output-Msg-TXT)
1020 GC0712          TO F-Cobc-Output-REC
1021 GC0712          WRITE F-Cobc-Output-REC
1022 GC0712          SET WS-RS-Complete-BOOL TO TRUE
1023 GC0712    ELSE
1024 GC0712          SET WS-RS-Compile-Failed-BOOL TO TRUE
1025 GC0712          MOVE CONCATENATE(' Compilation Failed - See ',
1026 GC0712          TRIM(WS-Listing-Filename-TXT,Trailing))
1027 GC0712          TO WS-Output-Msg-TXT
1028 GC0712          MOVE 'GNU COBOL Compilation HAS FAILED - See Above'
1029 GC0712          TO F-Cobc-Output-REC
1030 GC0712          WRITE F-Cobc-Output-REC
1031 GC0712    END-IF
1032 GC0712    CLOSE F-Cobc-Output-FILE
1033 GC0712    DISPLAY S-Switches-SCR
1034 GC0712    CALL 'C$SLEEP' USING 2
1035 GC0712    MOVE SPACES TO WS-Output-Msg-TXT
1036          IF WS-RS-Compile-Failed-BOOL
1037 GC0712          PERFORM 250-Autoload-Listing
1038          PERFORM 900-Terminate
1039          *> ----- Control will not return
1040          END-IF
1041          .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 27

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 28

```

=====
1043      *>*****
1044      *> Generate a source + xref listing using 'LISTING' subroutine **
1045      *>*****
1046 GC0410 220-Make-Listing SECTION.
1047 GC0410     MOVE ' Generating listing...' TO WS-Output-Msg-TXT
1048 GC0410     DISPLAY S-Switches-SCR
1049 GC0410     MOVE 0 TO RETURN-CODE
1050      *>*****
1051      *> Create the listing **
1052      *>*****
1053 GC0410     MOVE SPACES TO WS-Output-Msg-TXT
1054 GC0410     CALL 'LISTING' USING WS-Listing-Filename-TXT
1055 GC0712                WS-File-Name-TXT
1056 GC0712                WS-OS-Type-CD
1057 GC1213                LPP
1058 GC1213                LPPP
1059 GC1213                WS-Listing-CD
1060 GC0410     ON EXCEPTION
1061 GC0410         MOVE ' LISTING module is not available'
1062 GC0410         TO WS-Output-Msg-TXT
1063 GC0410         MOVE 1 TO RETURN-CODE
1064 GC0410     END-CALL
1065 GC0410     IF RETURN-CODE = 0
1066 GC0712         MOVE ' Source+Xref listing generated '
1067 GC0712         TO WS-Output-Msg-TXT
1068 GC0410     END-IF
1069 GC0712     DISPLAY S-Switches-SCR
1070 GC0712     CALL 'C$SLEEP' USING 2
1071 GC0712     PERFORM 250-Autoload-Listing
1072 GC0410     .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 28

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 29

```

=====
1074      *>*****
1075      *> Run the compiled program                               **
1076      *>*****
1077      230-Run-Program SECTION.
1078 GC0114      MOVE ' Preparing to run program ... press ENTER to close '
1079 GC0114      TO WS-Output-Msg-TXT
1080 GC0114      DISPLAY S-Switches-SCR
1081 GC0114      CALL 'C$SLEEP' USING 3
1082 GC0909      MOVE SPACES TO WS-Cmd-TXT
1083 GC0909      MOVE 1 TO WS-I-SUB
1084      *>*****
1085      *> If necessary, start with 'cobcrun' command             **
1086      *>*****
1087 GC0712      IF WS-CS-LIBRARY-CHR NOT = ' '
1088              STRING 'cobcrun ' DELIMITED SIZE
1089              INTO WS-Cmd-TXT
1090              WITH POINTER WS-I-SUB
1091      END-IF
1092      *>*****
1093      *> Add any necessary path prefix                           **
1094      *>*****
1095 GC0712      SET WS-RS-Double-Quote-Used-BOOL TO FALSE
1096      IF WS-Prog-Folder-TXT NOT = SPACES
1097 GC0909      IF WS-OS-Cygwin-BOOL AND WS-Prog-Folder-TXT (2:1) = ':'
1098 GC0909      STRING '/cygdrive/'
1099 GC0909      INTO WS-Cmd-TXT
1100 GC0909      WITH POINTER WS-I-SUB
1101 GC0909      STRING LOWER-CASE(WS-Prog-Folder-TXT (1:1))
1102 GC0909      INTO WS-Cmd-TXT
1103 GC0909      WITH POINTER WS-I-SUB
1104 GC0909      PERFORM
1105 GC0909      VARYING WS-J-SUB FROM 3 BY 1
1106 GC0909      UNTIL WS-J-SUB > LENGTH(TRIM(WS-Prog-Folder-TXT))
1107 GC0909      IF WS-Prog-Folder-TXT (WS-J-SUB:1) = '\'
1108 GC0909      STRING '/'
1109 GC0909      INTO WS-Cmd-TXT
1110 GC0909      WITH POINTER WS-I-SUB
1111 GC0909      ELSE
1112 GC0909      STRING WS-Prog-Folder-TXT (WS-J-SUB:1)
1113 GC0909      INTO WS-Cmd-TXT
1114 GC0909      WITH POINTER WS-I-SUB
1115 GC0909      END-IF
1116 GC0909      END-PERFORM
1117 GC0909      ELSE
1118 GC0410      STRING ''' TRIM(WS-Prog-Folder-TXT,TRAILING)
1119 GC0909      INTO WS-Cmd-TXT
1120 GC0909      WITH POINTER WS-I-SUB
1121 GC0712      SET WS-RS-Double-Quote-Used-BOOL TO TRUE
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 29

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 30

```

=====
1122 GC0909      END-IF
1123 GC0712      STRING WS-OS-Dir-CHR
1124 GC0909      INTO WS-Cmd-TXT
1125 GC0909      WITH POINTER WS-I-SUB
1126 GC0909      ELSE
1127 GC0909      IF WS-OS-Cygwin-BOOL OR WS-OS-UNIX-BOOL
1128 GC0909      STRING './'
1129 GC0909      INTO WS-Cmd-TXT
1130 GC0909      WITH POINTER WS-I-SUB
1131 GC0909      END-IF
1132      END-IF
1133      *>*****
1134      *> Insert program filename **
1135      *>*****
1136 GC0909      STRING TRIM(WS-Pgm-Nm-TXT,TRAILING)
1137 GC0909      INTO WS-Cmd-TXT
1138 GC0909      WITH POINTER WS-I-SUB
1139      *>*****
1140      *> Insert proper extension **
1141      *>*****
1142 GC0712      IF WS-CS-LIBRARY-CHR = ' '
1143 GC0712      IF WS-OS-Exe-Ext-CONST > ' '
1144 GC0712      STRING WS-OS-Exe-Ext-CONST DELIMITED SPACE
1145 GC0712      INTO WS-Cmd-TXT
1146 GC0712      WITH POINTER WS-I-SUB
1147 GC0712      END-IF
1148 GC0712      ELSE
1149 GC0712      IF WS-OS-Lib-Ext-CONST > ' '
1150 GC0712      STRING WS-OS-Lib-Ext-CONST DELIMITED SPACE
1151 GC0712      INTO WS-Cmd-TXT
1152 GC0712      WITH POINTER WS-I-SUB
1153 GC0712      END-IF
1154 GC0712      END-IF
1155 GC0712      IF WS-RS-Double-Quote-Used-BOOL
1156 GC0712      STRING ''' DELIMITED SIZE
1157 GC0712      INTO WS-Cmd-TXT
1158 GC0712      WITH POINTER WS-I-SUB
1159 GC0712      END-IF
1160      IF WS-CS-Args-TXT NOT = SPACES
1161 GC0809      STRING ' ' TRIM(WS-CS-Args-TXT,TRAILING)
1162      INTO WS-Cmd-TXT
1163      WITH POINTER WS-I-SUB
1164      END-IF
1165      *>*****
1166      *> Run the program **
1167      *>*****
1168 GC0114      CALL X'E4'
1169      CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1170 GC0712      MOVE SPACES TO WS-Output-Msg-TXT
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 30

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 31

```
=====
1171 GC0114      ACCEPT WS-Output-Msg-TXT(1:1) AT 0101
1172              PERFORM 900-Terminate
1173      * -- Control will NOT return
1174              .
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 31

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 32

```

=====
1176      *>*****
1177      *> Determine if the program being compiled is a MAIN program **
1178      *>*****
1179      240-Find-LINKAGE-SECTION SECTION.
1180      OPEN INPUT F-Source-Code-FILE
1181 GC0712 MOVE ' ' TO WS-CS-LIBRARY-CHR
1182      SET WS-RS-More-To-1st-Prog-BOOL TO TRUE
1183      PERFORM UNTIL WS-RS-1st-Prog-Complete-BOOL
1184          READ F-Source-Code-FILE AT END
1185          CLOSE F-Source-Code-FILE
1186          EXIT SECTION
1187      END-READ
1188 GC0712 CALL 'CHECKSRC'
1189 GC0712     USING BY CONTENT F-Source-Code-REC
1190 GC0712     BY REFERENCE WS-RS-Source-Record-Type-CHR
1191      IF WS-RS-Source-Rec-Ident-BOOL
1192          SET WS-RS-1st-Prog-Complete-BOOL TO TRUE
1193      END-IF
1194      END-PERFORM
1195 GC0712 SET WS-RS-Source-Rec-Ignored-BOOL TO TRUE
1196      PERFORM UNTIL WS-RS-Source-Rec-Linkage-BOOL
1197          OR WS-RS-Source-Rec-Ident-BOOL
1198          READ F-Source-Code-FILE AT END
1199          CLOSE F-Source-Code-FILE
1200          EXIT SECTION
1201      END-READ
1202 GC0712 CALL 'CHECKSRC'
1203 GC0712     USING BY CONTENT F-Source-Code-REC
1204 GC0712     BY REFERENCE WS-RS-Source-Record-Type-CHR
1205      END-PERFORM
1206      CLOSE F-Source-Code-FILE
1207      IF WS-RS-Source-Rec-Linkage-BOOL
1208 GC0712 MOVE SELCHAR TO WS-CS-LIBRARY-CHR
1209      END-IF
1210      .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 32

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 33

```

=====
1212 GC0712*>*****
1213 GC0712*> Attempt to open the listing file as a command. This will - **
1214 GC1113*> if the user has associated filetype/extension 'gclst' with **
1215 GC0712*> an application - invoke the appropriate application to **
1216 GC0712*> allow the user to view the listing. **
1217 GC0712*>*****
1218 GC0712 250-Autoload-Listing SECTION.
1219 GC0712 EVALUATE TRUE
1220 GC0712 WHEN WS-OS-Windows-BOOL OR WS-OS-Cygwin-BOOL
1221 GC0712 MOVE SPACES TO WS-Cmd-TXT
1222 GC0712 STRING
1223 GC0712 'cmd /c '
1224 GC0712 TRIM(WS-Listing-Filename-TXT,TRAILING)
1225 GC0712 DELIMITED SIZE INTO WS-Cmd-TXT
1226 GC0712 CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1227 GC0712 WHEN WS-OS-OSX-BOOL
1228 GC0712 MOVE SPACES TO WS-Cmd-TXT
1229 GC0712 STRING
1230 GC0712 'open -t '
1231 GC0712 TRIM(WS-Listing-Filename-TXT,TRAILING)
1232 GC0712 DELIMITED SIZE INTO WS-Cmd-TXT
1233 GC0712 CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1234 GC0712 END-EVALUATE
1235 GC0712*> *****
1236 GC0712*> ** Since we had to do our own '-save-temps' when we **
1237 GC0712*> ** compiled (in order to generate the cross-reference **
1238 GC0712*> ** listing) we now need to clean up after ourselves. **
1239 GC0712*> *****
1240 GC1112 DISPLAY S-Blank-SCR
1241 GC0712 IF WS-OS-Windows-BOOL
1242 GC0712 MOVE CONCATENATE('del ',TRIM(WS-Pgm-Nm-TXT,TRAILING))
1243 GC0712 TO WS-Cmd-TXT
1244 GC0712 ELSE
1245 GC0712 MOVE CONCATENATE('rm ',TRIM(WS-Pgm-Nm-TXT,TRAILING))
1246 GC0712 TO WS-Cmd-TXT
1247 GC0712 END-IF
1248 GC0712 CALL 'SYSTEM'
1249 GC0712 USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c')
1250 GC0712 CALL 'SYSTEM'
1251 GC0712 USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c.h')
1252 GC0712 CALL 'SYSTEM'
1253 GC0712 USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c.l*.h')
1254 GC0712 CALL 'SYSTEM'
1255 GC0712 USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.i')
1256 GC0712 CALL 'SYSTEM'
1257 GC0712 USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.o')
1258
1259 GC0712 .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 33

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 34

```
=====
1261      *>*****
1262      *> Display a message and halt the program          **
1263      *>*****
1264      900-Terminate SECTION.
1265 GC0909      IF WS-Output-Msg-TXT > SPACES
1266 GC0909          DISPLAY S-Switches-SCR
1267 GC0909          CALL 'C$SLEEP' USING 2
1268 GC0909      END-IF
1269          DISPLAY S-Blank-SCR
1270          STOP RUN
1271          .
1272
1273      END PROGRAM GCic.
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 34

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 35

```

=====
1275 IDENTIFICATION DIVISION.
1276 PROGRAM-ID. CHECKSRC.
1277 *>*****
1278 *> This subprogram will scan a line of source code it is given **
1279 *> looking for 'LINKAGE SECTION' or 'IDENTIFICATION DIVISION'. **
1280 *> **
1281 *> ****NOTE**** ****NOTE**** ****NOTE**** ****NOTE*** **
1282 *> **
1283 *> These two strings must be found IN THEIR ENTIRETY within **
1284 *> the 1st 80 columns of program source records, and cannot **
1285 *> follow either a '*>' sequence OR a '*' in col 7. **
1286 *>*****
1287 *> DATE CHANGE DESCRIPTION **
1288 *> ===== **
1289 *> GC0809 Initial coding. **
1290 *>*****
1291 ENVIRONMENT DIVISION.
1292 CONFIGURATION SECTION.
1293 REPOSITORY.
1294 FUNCTION ALL INTRINSIC.
1295 DATA DIVISION.
1296 WORKING-STORAGE SECTION.
1297 01 WS-Compressed-Src-TXT.
1298 05 WS-CS-CHR OCCURS 80 TIMES
1299 PIC X(1).
1300
1301 01 WS-Runtime-Switches-TXT.
1302 05 WS-RS-Found-SPACE-CHR PIC X(1).
1303 88 WS-RS-Skipping-SPACE-BOOL VALUE 'Y'.
1304 88 WS-RS-Not-Skipping-SPACE-BOOL VALUE 'N'.
1305
1306 01 WS-I-SUB USAGE BINARY-CHAR.
1307
1308 01 WS-J-SUB USAGE BINARY-CHAR.
1309 LINKAGE SECTION.
1310 01 L-Argument-1-TXT.
1311 02 L-A1-CHR OCCURS 80 TIMES
1312 PIC X(1).
1313
1314 01 L-Argument-2-CHR PIC X(1).
1315 88 L-A2-LINKAGE-SECTION-BOOL VALUE 'L'.
1316 88 L-A2-IDENT-DIVISION-BOOL VALUE 'I'.
1317 88 L-A2-Nothing-Special-BOOL VALUE ' '.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 35

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 36

```

=====
1319 GC0712 PROCEDURE DIVISION USING BY VALUE      L-Argument-1-TXT
1320 GC0712                                     BY REFERENCE L-Argument-2-CHR.
1321      000-Main SECTION.
1322          SET L-A2-Nothing-Special-BOOL TO TRUE
1323          IF L-A1-CHR (7) = '*'
1324              GOBACK
1325          END-IF
1326      .
1327      *>
1328      *> Compress multiple consecutive spaces
1329      *>
1330          SET WS-RS-Not-Skipping-SPACE-BOOL TO TRUE
1331          MOVE 0 TO WS-J-SUB
1332          MOVE SPACES TO WS-Compressed-Src-TXT
1333          PERFORM VARYING WS-I-SUB FROM 1 BY 1
1334              UNTIL WS-I-SUB > 80
1335              IF L-A1-CHR (WS-I-SUB) = SPACE
1336                  IF WS-RS-Not-Skipping-SPACE-BOOL
1337                      ADD 1 TO WS-J-SUB
1338                      MOVE UPPER-CASE(L-A1-CHR (WS-I-SUB))
1339                      TO WS-CS-CHR (WS-J-SUB)
1340                      SET WS-RS-Skipping-SPACE-BOOL TO TRUE
1341                  END-IF
1342              ELSE
1343                  SET WS-RS-Not-Skipping-SPACE-BOOL TO TRUE
1344                  ADD 1 TO WS-J-SUB
1345                  MOVE L-A1-CHR (WS-I-SUB) TO WS-CS-CHR (WS-J-SUB)
1346              END-IF
1347          END-PERFORM
1348      *>
1349      *> Scan the compressed source line
1350      *>
1351          PERFORM VARYING WS-I-SUB FROM 1 BY 1
1352              UNTIL WS-I-SUB > 66
1353          EVALUATE TRUE
1354              WHEN WS-CS-CHR (WS-I-SUB) = '*'
1355                  IF WS-Compressed-Src-TXT (WS-I-SUB : 2) = '*>'
1356                      GOBACK
1357                  END-IF
1358              WHEN (WS-CS-CHR (WS-I-SUB) = 'L') AND (WS-I-SUB < 66)
1359                  IF WS-Compressed-Src-TXT (WS-I-SUB : 15)
1360                      = 'LINKAGE SECTION'
1361                      SET L-A2-LINKAGE-SECTION-BOOL TO TRUE
1362                      GOBACK
1363                  END-IF
1364              WHEN (WS-CS-CHR (WS-I-SUB) = 'I') AND (WS-I-SUB < 58)
1365                  IF WS-Compressed-Src-TXT (WS-I-SUB : 23)
1366                      = 'IDENTIFICATION DIVISION'
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 36

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 37

```

=====
1367             SET L-A2-IDENT-DIVISION-BOOL TO TRUE
1368             GOBACK
1369             END-IF
1370             END-EVALUATE
1371             END-PERFORM
1372             *>
1373             *> If we get to here, we never found anything!
1374             *>
1375 +             GOBACK
1376             .
1377             END PROGRAM CHECKSRC.
1378
1379             IDENTIFICATION DIVISION.
1380             PROGRAM-ID. LISTING.
1381             *>*****
1382             *> This subprogram generates a cross-reference listing of an **
1383             *> GNU COBOL program. **
1384             *>*****
1385             *> **
1386             *> AUTHOR:          GARY L. CUTLER **
1387             *>                Copyright (C) 2010, Gary L. Cutler, GPL **
1388             *> **
1389             *> DATE-WRITTEN: April 1, 2010 **
1390             *> **
1391             *>*****
1392             *> DATE CHANGE DESCRIPTION **
1393             *> ===== **
1394             *> GC0410 Initial coding **
1395             *> GC0711 Updates to accommodate the 12MAR2010 version of OC **
1396             *> GC0710 Handle duplicate data names (i.e. 'CORRESPONDING' or **
1397             *> qualified items) better; ignore 'END PROGRAM' recs **
1398             *> so program name doesn't appear in listing. **
1399             *> GC0313 Fix problem where the first procedure name defined **
1400             *> in the PROCEDURE DIVISION lacks a "Defined" line **
1401             *> number. **
1402             *> GC1213 Updated for 23NOV2013 version of GNU COBOL 2.1; Stop **
1403             *> showing functions as if they were identifiers in the **
1404             *> xref listing; Flag all CALL argument references with **
1405             *> a "C" rather than "*" because they aren't necessari- **
1406             *> ly altered; Fixed assorted formatting bugs; DOWN- **
1407             *> WARD COMPATIBLE WITH GNU COBOL 2.0 SYNTAX **
1408             *> GC0314 Fix problem where 1st char of 1st token on a line is **
1409             *> lost if >>SOURCE MODE IS FREE is in effect and the **
1410             *> 1st character is non-blank. **
1411             *>*****
1412             ENVIRONMENT DIVISION.
1413             CONFIGURATION SECTION.
1414             REPOSITORY.
1415             FUNCTION ALL INTRINSIC.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 37

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 38

```

=====
1416      INPUT-OUTPUT SECTION.
1417      FILE-CONTROL.
1418          SELECT F-Expanded-Src-FILE ASSIGN TO WS-Expanded-Src-Fn-TXT
1419          ORGANIZATION IS LINE SEQUENTIAL.
1420 GC0712      SELECT F-Listing-FILE      ASSIGN TO L-Listing-Fn-TXT
1421          ORGANIZATION IS LINE SEQUENTIAL.
1422          SELECT F-Original-Src-FILE ASSIGN TO L-Src-Fn-TXT
1423          ORGANIZATION IS LINE SEQUENTIAL.
1424          SELECT F-Sort-Work-FILE      ASSIGN TO DISK.
1425      DATA DIVISION.
1426      FILE SECTION.
1427      FD  F-Expanded-Src-FILE.
1428      01  F-Expanded-Src-REC.
1429          05  F-ES-1-CHR                      PIC X.
1430          05  F-ES-2-256-TXT-256             PIC X(256).
1431 GC0712 01  F-Expanded-Src2-REC.
1432 GC0712      05  F-ES-1-7-TXT                      PIC X(7).
1433 GC0712      05  F-ES-8-256-TXT                   PIC X(249).
1434
1435 GC0712 FD  F-Listing-FILE.
1436 GC1213 01  F-Listing-96-REC                     PIC X(96).
1437 GC1213 01  F-Listing-135-REC                    PIC X(135).
1438          01  F-Listing-REC                       PIC X(135).
1439
1440      FD  F-Original-Src-FILE.
1441      01  F-Original-Src-REC.
1442 GC0410      05  F-OS-1-128-TXT.
1443 GC0410          10  FILLER                      PIC X(6).
1444 GC0410          10  F-OS-7-CHR                   PIC X(1).
1445 GC0712          10  F-OS-8-72-TXT                PIC X(65).
1446 GC0712          10  FILLER                      PIC X(56).
1447          05  F-OS-129-256-TXT                   PIC X(128).
1448
1449      SD  F-Sort-Work-FILE.
1450      01  F-Sort-Work-REC.
1451          05  F-SW-Prog-ID-TXT                    PIC X(15).
1452          05  F-SW-Token-Uc-TXT                   PIC X(32).
1453          05  F-SW-Token-TXT                      PIC X(32).
1454          05  F-SW-Section-TXT                    PIC X(15).
1455          05  F-SW-Def-Line-NUM                   PIC 9(6).
1456          05  F-SW-Reference-TXT.
1457              10  F-SW-Ref-Line-NUM              PIC 9(6).
1458              10  F-SW-Ref-Flag-CHR              PIC X(1).
1459
1460      WORKING-STORAGE SECTION.
1461 GC1213 01  WS-Copyright-TXT                      PIC X(86).
1462
1463          01  WS-Curr-CHR                          PIC X(1).
1464          88  WS-Curr-Char-Is-Punct-BOOL          VALUE '=' , '( , )' ,
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 38

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 39

```

=====
1465                                     '*','/', '&',
1466                                     ';','>', '<',
1467                                     '>',':'.
1468      88 WS-Curr-Char-Is-Quote-BOOL   VALUE '"', ''''.
1469      88 WS-Curr-Char-Is-X-BOOL      VALUE 'x', 'X'.
1470      88 WS-Curr-Char-Is-Z-BOOL      VALUE 'z', 'Z'.
1471
1472      01 WS-Curr-Division-TXT         PIC X(1).
1473 GC1010      88 WS-CD-In-IDENT-DIV-BOOL VALUE 'i', 'I', '?.
1474 GC1010      88 WS-CD-In-ENV-DIV-BOOL VALUE 'e', 'E'.
1475 GC1010      88 WS-CD-In-DATA-DIV-BOOL VALUE 'd', 'D'.
1476 GC1010      88 WS-CD-In-PROC-DIV-BOOL VALUE 'p', 'P'.
1477
1478      01 WS-Curr-Line-NUM             PIC 9(6).
1479
1480      01 WS-Curr-Prog-ID-TXT.
1481          05 FILLER                   PIC X(12).
1482          05 WS-CPI-13-15-TXT         PIC X(3).
1483 GC0712      05 WS-CPI-16-CHR        PIC X(1).
1484
1485      01 WS-Curr-Section-TXT.
1486          05 WS-CS-1-CHR              PIC X(1).
1487          05 WS-CS-2-14-TXT.
1488              10 FILLER               PIC X(10).
1489              10 WS-CS-11-14-TXT     PIC X(3).
1490          05 WS-CS-15-CHR             PIC X(1).
1491
1492      01 WS-Curr-Verb-TXT             PIC X(12).
1493
1494      01 WS-Delim-TXT                 PIC X(2).
1495
1496      01 WS-Dummy-TXT                 PIC X(1).
1497
1498      01 WS-Expanded-Src-Fn-TXT       PIC X(256).
1499
1500      01 WS-Filename-TXT              PIC X(256).
1501
1502 GC1213      01 WS-Flags-TXT.
1503 GC1213      05 WS-Suppress-FF-CHR    PIC X(1).
1504
1505 GC1213      01 WS-Formatted-DT       PIC 9999/99/99.
1506
1507      01 WS-Group-Indicators-TXT.
1508          05 WS-GI-Prog-ID-TXT        PIC X(15).
1509          05 WS-GI-Token-TXT          PIC X(32).
1510
1511      01 WS-Held-Reference-TXT        PIC X(100).
1512
1513      01 WS-I-SUB                      USAGE BINARY-LONG.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 39

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 40

```

=====
1514
1515      01 WS-J-SUB                      USAGE BINARY-LONG.
1516
1517      01 WS-Lines-Left-NUM             USAGE BINARY-LONG.
1518
1519      01 WS-Lines-Per-Page-NUM         USAGE BINARY-LONG.
1520
1521      01 WS-Lines-Per-Page-Env-TXT     PIC X(256).
1522
1523 GC1010 01 WS-Main-Module-Name-TXT   PIC X(256).
1524
1525      01 WS-Next-CHR                    PIC X(1).
1526      88 WS-Next-Char-Is-Quote-BOOL   VALUE '''', ''''.
1527
1528      01 WS-OS-Type-FILLER-TXT.
1529          05 VALUE 'Windows'           PIC X(14).
1530          05 VALUE 'Windows/Cygwin'    PIC X(14).
1531          05 VALUE 'UNIX/Linux'       PIC X(14).
1532          05 VALUE 'OSX'               PIC X(14).
1533          05 VALUE 'Windows/MinGW'     PIC X(14).
1534      01 WS-OS-Types-TXT REDEFINES WS-OS-Type-FILLER-TXT.
1535          05 WS-OS-Type-TXT            PIC X(14)
1536                                     OCCURS 5 TIMES .
1537
1538 GC0712 01 WS-Page-NUM                 USAGE BINARY-LONG.
1539
1540 GC0712 01 WS-Page-No-TXT.
1541 GC0712      05 WS-PN-Literal-TXT     PIC X(6).
1542 GC0712      05 WS-PN-Page-NUM       PIC Z(3)9.
1543
1544 GC1213 01 WS-Program-Path-TXT        PIC X(135).
1545
1546      01 WS-Reserved-Words-TXT.
1547          05 VALUE '                ' PIC X(33).
1548 GC1213      05 VALUE 'FABS          ' PIC X(33).
1549          05 VALUE 'VACCEPT         ' PIC X(33).
1550          05 VALUE 'ACCESS          ' PIC X(33).
1551 GC1213      05 VALUE 'FACOS        ' PIC X(33).
1552          05 VALUE 'ACTIVE-CLASS    ' PIC X(33). UNIMPLEMENTED
1553          05 VALUE 'VADD            ' PIC X(33).
1554          05 VALUE 'ADDRESS         ' PIC X(33).
1555          05 VALUE 'ADVANCING       ' PIC X(33).
1556          05 VALUE 'KAFTER         ' PIC X(33).
1557          05 VALUE 'ALIGNED         ' PIC X(33). UNIMPLEMENTED
1558          05 VALUE 'ALL             ' PIC X(33).
1559          05 VALUE 'VALLOCATE       ' PIC X(33).
1560          05 VALUE 'ALPHABET        ' PIC X(33).
1561          05 VALUE 'ALPHABETIC     ' PIC X(33).
1562          05 VALUE 'ALPHABETIC-LOWER' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 40

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 41

```

=====
1563      05 VALUE ' ALPHABETIC-UPPER           ' PIC X(33).
1564      05 VALUE ' ALPHANUMERIC             ' PIC X(33).
1565      05 VALUE ' ALPHANUMERIC-EDITED      ' PIC X(33).
1566      05 VALUE ' ALSO                      ' PIC X(33).
1567      05 VALUE ' VALTER                    ' PIC X(33).
1568      05 VALUE ' ALTERNATE                 ' PIC X(33).
1569      05 VALUE ' AND                       ' PIC X(33).
1570 GC1213 05 VALUE ' FANNUITY                 ' PIC X(33).
1571      05 VALUE ' ANY                       ' PIC X(33).
1572      05 VALUE ' ANYCASE                   ' PIC X(33).      UNIMPLEMENTED
1573      05 VALUE ' ARE                       ' PIC X(33).
1574      05 VALUE ' AREA                      ' PIC X(33).
1575      05 VALUE ' AREAS                     ' PIC X(33).
1576      05 VALUE ' ARGUMENT-NUMBER          ' PIC X(33).
1577      05 VALUE ' ARGUMENT-VALUE           ' PIC X(33).
1578      05 VALUE ' ARITHMETIC                ' PIC X(33).      UNIMPLEMENTED
1579      05 VALUE ' AS                       ' PIC X(33).
1580      05 VALUE ' ASCENDING                 ' PIC X(33).
1581      05 VALUE ' ASCII                     ' PIC X(33).
1582 GC1213 05 VALUE ' FASIN                   ' PIC X(33).
1583      05 VALUE ' ASSIGN                     ' PIC X(33).
1584      05 VALUE ' AT                         ' PIC X(33).
1585 GC1213 05 VALUE ' FATAN                   ' PIC X(33).
1586 GC0711 05 VALUE ' ATTRIBUTE               ' PIC X(33).
1587      05 VALUE ' AUTHOR                    ' PIC X(33).      OBSOLETE
1588      05 VALUE ' AUTO                      ' PIC X(33).
1589      05 VALUE ' AUTO-SKIP                  ' PIC X(33).
1590      05 VALUE ' AUTOMATIC                  ' PIC X(33).
1591      05 VALUE ' AUTOTERMINATE             ' PIC X(33).
1592      05 VALUE ' AWAY-FROM-ZERO            ' PIC X(33).
1593      05 VALUE ' B-AND                      ' PIC X(33).      UNIMPLEMENTED
1594      05 VALUE ' B-NOT                     ' PIC X(33).      UNIMPLEMENTED
1595      05 VALUE ' B-OR                      ' PIC X(33).      UNIMPLEMENTED
1596      05 VALUE ' B-XOR                     ' PIC X(33).      UNIMPLEMENTED
1597      05 VALUE ' BACKGROUND-COLOR          ' PIC X(33).
1598      05 VALUE ' BACKGROUND-COLOUR         ' PIC X(33).
1599      05 VALUE ' BASED                     ' PIC X(33).
1600      05 VALUE ' BEEP                       ' PIC X(33).
1601      05 VALUE ' BEFORE                     ' PIC X(33).
1602      05 VALUE ' BELL                       ' PIC X(33).
1603      05 VALUE ' BINARY                     ' PIC X(33).
1604      05 VALUE ' BINARY-C-LONG              ' PIC X(33).
1605      05 VALUE ' BINARY-CHAR                ' PIC X(33).
1606      05 VALUE ' BINARY-DOUBLE              ' PIC X(33).
1607      05 VALUE ' BINARY-INT                 ' PIC X(33).
1608      05 VALUE ' BINARY-LONG                ' PIC X(33).
1609      05 VALUE ' BINARY-LONG-LONG           ' PIC X(33).
1610      05 VALUE ' BINARY-SHORT               ' PIC X(33).
1611      05 VALUE ' BIT                       ' PIC X(33).      UNIMPLEMENTED
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 41

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 42

```

=====
1612          05 VALUE ' BLANK                ' PIC X(33).
1613          05 VALUE ' BLINK                ' PIC X(33).
1614          05 VALUE ' BLOCK                ' PIC X(33).
1615          05 VALUE ' BOOLEAN             ' PIC X(33).      UNIMPLEMENTED
1616 GC1213    05 VALUE ' FBOOLEAN-OF-INTEGER ' PIC X(33).      UNIMPLEMENTED
1617          05 VALUE ' BOTTOM               ' PIC X(33).
1618          05 VALUE ' YBY                 ' PIC X(33).
1619 GC1213    05 VALUE ' FBYTE-LENGTH        ' PIC X(33).
1620          05 VALUE ' MC01                 ' PIC X(33).
1621          05 VALUE ' MC02                 ' PIC X(33).
1622          05 VALUE ' MC03                 ' PIC X(33).
1623          05 VALUE ' MC04                 ' PIC X(33).
1624          05 VALUE ' MC05                 ' PIC X(33).
1625          05 VALUE ' MC06                 ' PIC X(33).
1626          05 VALUE ' MC07                 ' PIC X(33).
1627          05 VALUE ' MC08                 ' PIC X(33).
1628          05 VALUE ' MC09                 ' PIC X(33).
1629          05 VALUE ' MC10                 ' PIC X(33).
1630          05 VALUE ' MC11                 ' PIC X(33).
1631          05 VALUE ' MC12                 ' PIC X(33).
1632          05 VALUE ' VCALL                ' PIC X(33).
1633          05 VALUE ' MCALL-CONVENTION     ' PIC X(33).
1634          05 VALUE ' VCANCEL              ' PIC X(33).
1635          05 VALUE ' CAPACITY             ' PIC X(33).      UNIMPLEMENTED
1636          05 VALUE ' CD                   ' PIC X(33).      OBSOLETE
1637          05 VALUE ' CENTER              ' PIC X(33).      UNIMPLEMENTED
1638          05 VALUE ' CF                   ' PIC X(33).
1639          05 VALUE ' CH                   ' PIC X(33).
1640          05 VALUE ' CHAIN                ' PIC X(33).      UNIMPLEMENTED
1641          05 VALUE ' CHAINING             ' PIC X(33).
1642 GC1213    05 VALUE ' FCHAR               ' PIC X(33).
1643 GC1213    05 VALUE ' FCHAR-NATIONAL      ' PIC X(33).      UNIMPLEMENTED
1644          05 VALUE ' CHARACTER           ' PIC X(33).
1645          05 VALUE ' CHARACTERS          ' PIC X(33).
1646          05 VALUE ' CLASS                ' PIC X(33).
1647          05 VALUE ' CLASS-ID            ' PIC X(33).      UNIMPLEMENTED
1648 GC0711    05 VALUE ' CLASSIFICATION      ' PIC X(33).
1649          05 VALUE ' VCLOSE              ' PIC X(33).
1650 GC1213    05 VALUE ' FCOB-CRT-STATUS    ' PIC X(33).
1651          05 VALUE ' CODE                 ' PIC X(33).
1652          05 VALUE ' CODE-SET             ' PIC X(33).
1653          05 VALUE ' COL                  ' PIC X(33).
1654          05 VALUE ' COLLATING           ' PIC X(33).
1655          05 VALUE ' COLS                 ' PIC X(33).
1656          05 VALUE ' COLUMN              ' PIC X(33).
1657          05 VALUE ' COLUMNS             ' PIC X(33).
1658 GC1213    05 VALUE ' FCOMBINED-DATETIME ' PIC X(33).
1659          05 VALUE ' COMMA               ' PIC X(33).
1660          05 VALUE ' COMMAND-LINE        ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 42

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 43

```

=====
1661          05 VALUE 'VCOMMIT                ' PIC X(33).
1662          05 VALUE ' COMMON                ' PIC X(33).
1663          05 VALUE ' COMMUNICATION          ' PIC X(33).      OBSOLETE
1664          05 VALUE ' COMP                  ' PIC X(33).
1665          05 VALUE ' COMP-1                ' PIC X(33).
1666          05 VALUE ' COMP-2                ' PIC X(33).
1667          05 VALUE ' COMP-3                ' PIC X(33).
1668          05 VALUE ' COMP-4                ' PIC X(33).
1669          05 VALUE ' COMP-5                ' PIC X(33).
1670          05 VALUE ' COMP-6                ' PIC X(33).
1671          05 VALUE ' COMP-X                ' PIC X(33).
1672          05 VALUE ' COMPUTATIONAL          ' PIC X(33).
1673          05 VALUE ' COMPUTATIONAL-1       ' PIC X(33).
1674          05 VALUE ' COMPUTATIONAL-2       ' PIC X(33).
1675          05 VALUE ' COMPUTATIONAL-3       ' PIC X(33).
1676          05 VALUE ' COMPUTATIONAL-4       ' PIC X(33).
1677          05 VALUE ' COMPUTATIONAL-5       ' PIC X(33).
1678          05 VALUE ' COMPUTATIONAL-X       ' PIC X(33).
1679          05 VALUE 'VCOMPUTE                ' PIC X(33).
1680 GC1213    05 VALUE 'FCONCATENATE          ' PIC X(33).
1681 GC0712    05 VALUE ' CONDITION              ' PIC X(33).
1682          05 VALUE 'KCONFIGURATION         ' PIC X(33).
1683          05 VALUE 'MCONSOLE                ' PIC X(33).
1684          05 VALUE ' CONSTANT               ' PIC X(33).
1685          05 VALUE ' CONTAINS              ' PIC X(33).
1686 GC0712    05 VALUE 'ACONTENT              ' PIC X(33).
1687          05 VALUE 'VCONTINUE              ' PIC X(33).
1688          05 VALUE ' CONTROL                ' PIC X(33).
1689          05 VALUE ' CONTROLS               ' PIC X(33).
1690 GC0711    05 VALUE ' CONVERSION            ' PIC X(33).
1691          05 VALUE 'KCONVERTING             ' PIC X(33).
1692          05 VALUE ' COPY                   ' PIC X(33).
1693          05 VALUE ' CORR                   ' PIC X(33).
1694          05 VALUE ' CORRESPONDING          ' PIC X(33).
1695 GC1213    05 VALUE 'FCOS                   ' PIC X(33).
1696          05 VALUE 'KCOUNT                 ' PIC X(33).
1697          05 VALUE ' CRT                    ' PIC X(33).
1698          05 VALUE ' CRT-UNDER              ' PIC X(33).
1699          05 VALUE 'MCSP                    ' PIC X(33).
1700          05 VALUE ' CURRENCY               ' PIC X(33).
1701 GC1213    05 VALUE 'FCURRENCY-SYMBOL        ' PIC X(33).
1702 GC1213    05 VALUE 'FCURRENT-DATE          ' PIC X(33).
1703          05 VALUE ' CURSOR                 ' PIC X(33).
1704          05 VALUE ' CYCLE                  ' PIC X(33).
1705          05 VALUE 'KDATA                   ' PIC X(33).
1706          05 VALUE ' DATA-POINTER           ' PIC X(33).      UNIMPLEMENTED
1707          05 VALUE ' DATE                   ' PIC X(33).
1708          05 VALUE ' DATE-COMPILED          ' PIC X(33).      OBSOLETE
1709          05 VALUE ' DATE-MODIFIED          ' PIC X(33).      OBSOLETE
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 43

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 44

```

=====
1710 GC1213      05 VALUE 'FDATE-OF-INTEGERS' PIC X(33).
1711 GC1213      05 VALUE 'FDATE-TO-YYYYMMDD' PIC X(33).
1712             05 VALUE 'DATE-WRITTEN' PIC X(33). OBSOLETE
1713             05 VALUE 'DAY' PIC X(33).
1714 GC1213      05 VALUE 'FDAY-OF-INTEGERS' PIC X(33).
1715             05 VALUE 'DAY-OF-WEEK' PIC X(33).
1716 GC1213      05 VALUE 'IDAY-TO-YYYYDDD' PIC X(33).
1717             05 VALUE 'DE' PIC X(33).
1718 GC0712      05 VALUE 'IDEBUG-CONTENTS' PIC X(33).
1719 GC0712      05 VALUE 'IDEBUG-ITEM' PIC X(33).
1720 GC0712      05 VALUE 'IDEBUG-LINE' PIC X(33).
1721 GC0712      05 VALUE 'IDEBUG-NAME' PIC X(33).
1722 GC0712      05 VALUE 'IDEBUG-SUB-1' PIC X(33).
1723 GC0712      05 VALUE 'IDEBUG-SUB-2' PIC X(33).
1724 GC0712      05 VALUE 'IDEBUG-SUB-3' PIC X(33).
1725             05 VALUE 'DEBUGGING' PIC X(33).
1726             05 VALUE 'DECIMAL-POINT' PIC X(33).
1727             05 VALUE 'DECLARATIVES' PIC X(33).
1728             05 VALUE 'DEFAULT' PIC X(33).
1729             05 VALUE 'VDELETE' PIC X(33).
1730             05 VALUE 'DELIMITED' PIC X(33).
1731             05 VALUE 'KDELIMITER' PIC X(33).
1732             05 VALUE 'DEPENDING' PIC X(33).
1733             05 VALUE 'DESCENDING' PIC X(33).
1734             05 VALUE 'DESTINATION' PIC X(33). UNIMPLEMENTED
1735             05 VALUE 'DETAIL' PIC X(33).
1736 GC0711      05 VALUE 'DISC' PIC X(33).
1737             05 VALUE 'DISK' PIC X(33).
1738             05 VALUE 'VDISPLAY' PIC X(33).
1739 GC1213      05 VALUE 'FDISPLAY-OF' PIC X(33). UNIMPLEMENTED
1740             05 VALUE 'VDIVIDE' PIC X(33).
1741             05 VALUE 'KDIVISION' PIC X(33).
1742             05 VALUE 'KDOWN' PIC X(33).
1743             05 VALUE 'DUPLICATES' PIC X(33).
1744             05 VALUE 'DYNAMIC' PIC X(33).
1745 GC1213      05 VALUE 'FE' PIC X(33).
1746             05 VALUE 'EBCDIC' PIC X(33).
1747 GC0712      05 VALUE 'EC' PIC X(33).
1748             05 VALUE 'EGI' PIC X(33). OBSOLETE
1749             05 VALUE 'VELSE' PIC X(33).
1750             05 VALUE 'EMI' PIC X(33). OBSOLETE
1751             05 VALUE 'EMPTY-CHECK' PIC X(33).
1752             05 VALUE 'VENABLE' PIC X(33). OBSOLETE
1753 GC0710      05 VALUE 'KEND' PIC X(33).
1754             05 VALUE 'END-ACCEPT' PIC X(33).
1755             05 VALUE 'END-ADD' PIC X(33).
1756             05 VALUE 'END-CALL' PIC X(33).
1757             05 VALUE 'END-CHAIN' PIC X(33). UNIMPLEMENTED
1758             05 VALUE 'END-COMPUTE' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 44

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 45

```

=====
1759      05 VALUE ' END-DELETE                ' PIC X(33).
1760      05 VALUE ' END-DISPLAY              ' PIC X(33).
1761      05 VALUE ' END-DIVIDE               ' PIC X(33).
1762      05 VALUE ' END-EVALUATE            ' PIC X(33).
1763      05 VALUE ' END-IF                  ' PIC X(33).
1764      05 VALUE ' END-MULTIPLY            ' PIC X(33).
1765      05 VALUE ' END-OF-PAGE              ' PIC X(33).
1766      05 VALUE ' END-PERFORM             ' PIC X(33).
1767      05 VALUE ' END-READ                ' PIC X(33).
1768      05 VALUE ' END-RECEIVE             ' PIC X(33).      OBSOLETE
1769      05 VALUE ' END-RETURN              ' PIC X(33).
1770      05 VALUE ' END-REWRITE             ' PIC X(33).
1771      05 VALUE ' END-SEARCH              ' PIC X(33).
1772      05 VALUE ' END-START               ' PIC X(33).
1773      05 VALUE ' END-STRING              ' PIC X(33).
1774      05 VALUE ' END-SUBTRACT            ' PIC X(33).
1775      05 VALUE ' END-UNSTRING            ' PIC X(33).
1776      05 VALUE ' END-WRITE               ' PIC X(33).
1777      05 VALUE ' VENTRY                   ' PIC X(33).
1778      05 VALUE ' ENTRY-CONVENTION        ' PIC X(33).      UNIMPLEMENTED
1779      05 VALUE ' KENVIRONMENT            ' PIC X(33).
1780      05 VALUE ' ENVIRONMENT-NAME        ' PIC X(33).
1781      05 VALUE ' ENVIRONMENT-VALUE       ' PIC X(33).
1782      05 VALUE ' EO                      ' PIC X(33).      UNIMPLEMENTED
1783      05 VALUE ' EOL                     ' PIC X(33).
1784      05 VALUE ' EOP                     ' PIC X(33).
1785      05 VALUE ' EOS                     ' PIC X(33).
1786      05 VALUE ' EQUAL                   ' PIC X(33).
1787      05 VALUE ' KEQUALS                 ' PIC X(33).
1788      05 VALUE ' ERASE                   ' PIC X(33).
1789      05 VALUE ' ERROR                   ' PIC X(33).
1790      05 VALUE ' ESCAPE                  ' PIC X(33).
1791      05 VALUE ' ESI                     ' PIC X(33).      OBSOLETE
1792      05 VALUE ' VEVALUATE               ' PIC X(33).
1793      05 VALUE ' EXCEPTION               ' PIC X(33).
1794 GC1213 05 VALUE ' FEXCEPTION-FILE        ' PIC X(33).
1795 GC1213 05 VALUE ' FEXCEPTION-FILE-N    ' PIC X(33).      UNIMPLEMENTED
1796 GC1213 05 VALUE ' FEXCEPTION-LOCATION    ' PIC X(33).
1797 GC1213 05 VALUE ' FEXCEPTION-LOCATION-N ' PIC X(33).      UNIMPLEMENTED
1798      05 VALUE ' EXCEPTION-OBJECT        ' PIC X(33).      UNIMPLEMENTED
1799 GC1213 05 VALUE ' FEXCEPTION-STATEMENT ' PIC X(33).
1800 GC1213 05 VALUE ' FEXCEPTION-STATUS    ' PIC X(33).
1801      05 VALUE ' EXCLUSIVE                ' PIC X(33).
1802      05 VALUE ' VEXIT                   ' PIC X(33).
1803 GC1213 05 VALUE ' FEXP                  ' PIC X(33).
1804 GC1213 05 VALUE ' FEXP10               ' PIC X(33).
1805      05 VALUE ' EXPANDS                 ' PIC X(33).      UNIMPLEMENTED
1806      05 VALUE ' EXTEND                  ' PIC X(33).
1807      05 VALUE ' EXTERNAL                ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 45

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 46

```

=====
1808 GC1213      05 VALUE 'FFACTORIAL          ' PIC X(33).
1809              05 VALUE ' FACTORY          ' PIC X(33).      UNIMPLEMENTED
1810              05 VALUE ' FALSE          ' PIC X(33).
1811              05 VALUE 'KFD          ' PIC X(33).
1812              05 VALUE 'KFILE          ' PIC X(33).
1813              05 VALUE ' FILE-CONTROL    ' PIC X(33).
1814              05 VALUE ' FILE-ID        ' PIC X(33).
1815 GC1113      05 VALUE ' FILLER          ' PIC X(33).
1816              05 VALUE ' FINAL          ' PIC X(33).
1817              05 VALUE ' FIRST          ' PIC X(33).
1818 GC0712      05 VALUE ' FLOAT-BINARY-128      ' PIC X(33).      UNIMPLEMENTED
1819 GC0712      05 VALUE ' FLOAT-BINARY-32  ' PIC X(33).      UNIMPLEMENTED
1820 GC0712      05 VALUE ' FLOAT-BINARY-64  ' PIC X(33).      UNIMPLEMENTED
1821              05 VALUE ' FLOAT-DECIMAL-16 ' PIC X(33).
1822              05 VALUE ' FLOAT-DECIMAL-34 ' PIC X(33).
1823              05 VALUE ' FLOAT-EXTENDED  ' PIC X(33).      UNIMPLEMENTED
1824 GC0712      05 VALUE ' FLOAT-INFINITY    ' PIC X(33).      UNIMPLEMENTED
1825              05 VALUE ' FLOAT-LONG     ' PIC X(33).
1826 GC0712      05 VALUE ' FLOAT-NOT-A-NUMBER ' PIC X(33).      UNIMPLEMENTED
1827              05 VALUE ' FLOAT-SHORT   ' PIC X(33).
1828              05 VALUE ' FOOTING       ' PIC X(33).
1829              05 VALUE ' FOR           ' PIC X(33).
1830              05 VALUE ' FOREGROUND-COLOR ' PIC X(33).
1831              05 VALUE ' FOREGROUND-COLOUR ' PIC X(33).
1832 GC0711      05 VALUE ' FOREVER          ' PIC X(33).
1833              05 VALUE ' FORMAT        ' PIC X(33).      UNIMPLEMENTED
1834 GC1213      05 VALUE ' FFORMATTED-CURRENT-DATE ' PIC X(33).      UNIMPLEMENTED
1835 GC1213      05 VALUE ' FFORMATTED-DATE   ' PIC X(33).      UNIMPLEMENTED
1836 GC1213      05 VALUE ' FFORMATTED-DATETIME ' PIC X(33).      UNIMPLEMENTED
1837 GC1213      05 VALUE ' FFORMATTED-TIME   ' PIC X(33).      UNIMPLEMENTED
1838              05 VALUE ' MFORMFEED     ' PIC X(33).
1839 GC1213      05 VALUE ' FFRACTION-PART     ' PIC X(33).
1840              05 VALUE ' VFREE         ' PIC X(33).
1841              05 VALUE ' FROM         ' PIC X(33).
1842              05 VALUE ' FULL         ' PIC X(33).
1843              05 VALUE ' FUNCTION     ' PIC X(33).
1844 GC0712      05 VALUE ' KFUNCTION-ID        ' PIC X(33).
1845              05 VALUE ' FUNCTION-POINTER ' PIC X(33).      UNIMPLEMENTED
1846              05 VALUE ' VGENERATE     ' PIC X(33).
1847              05 VALUE ' GET          ' PIC X(33).      UNIMPLEMENTED
1848              05 VALUE ' KGIVING      ' PIC X(33).
1849              05 VALUE ' GLOBAL       ' PIC X(33).
1850              05 VALUE ' VGO         ' PIC X(33).
1851              05 VALUE ' VGOBACK     ' PIC X(33).
1852              05 VALUE ' GREATER      ' PIC X(33).
1853              05 VALUE ' GROUP        ' PIC X(33).
1854              05 VALUE ' GROUP-USAGE   ' PIC X(33).      UNIMPLEMENTED
1855              05 VALUE ' HEADING     ' PIC X(33).
1856              05 VALUE ' HIGH-VALUE  ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 46

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 47

```

=====
1857          05 VALUE ' HIGH-VALUES          ' PIC X(33).
1858 GC1213   05 VALUE 'FHIGHEST-ALGEBRAIC    ' PIC X(33).
1859          05 VALUE ' HIGHLIGHT            ' PIC X(33).
1860          05 VALUE ' I-O                  ' PIC X(33).
1861          05 VALUE ' I-O-CONTROL          ' PIC X(33).
1862          05 VALUE 'KID                   ' PIC X(33).
1863          05 VALUE 'KIDENTIFICATION        ' PIC X(33).
1864          05 VALUE 'VIF                    ' PIC X(33).
1865          05 VALUE ' IGNORE                ' PIC X(33).
1866          05 VALUE ' IGNORING              ' PIC X(33).
1867          05 VALUE ' IMPLEMENTS            ' PIC X(33).      UNIMPLEMENTED
1868          05 VALUE ' IN                    ' PIC X(33).
1869          05 VALUE ' INDEX                 ' PIC X(33).
1870          05 VALUE 'KINDEXED               ' PIC X(33).
1871          05 VALUE ' INDICATE               ' PIC X(33).
1872          05 VALUE ' INDIRECT              ' PIC X(33).      UNIMPLEMENTED
1873          05 VALUE ' INHERITS              ' PIC X(33).      UNIMPLEMENTED
1874          05 VALUE ' INITIAL               ' PIC X(33).
1875          05 VALUE 'VINITIALISE            ' PIC X(33).
1876          05 VALUE ' INITIALISED          ' PIC X(33).
1877          05 VALUE 'VINITIALIZE            ' PIC X(33).
1878          05 VALUE ' INITIALIZED            ' PIC X(33).
1879          05 VALUE 'VINITIATE              ' PIC X(33).
1880          05 VALUE ' INPUT                  ' PIC X(33).
1881          05 VALUE 'KINPUT-OUTPUT          ' PIC X(33).
1882          05 VALUE 'VINSPECT                ' PIC X(33).
1883          05 VALUE ' INSTALLATION           ' PIC X(33).      OBSOLETE
1884 GC1213   05 VALUE 'FINTEGER               ' PIC X(33).
1885 GC1213   05 VALUE 'FINTEGER-OF-BOOLEAN    ' PIC X(33).      UNIMPLEMENTED
1886 GC1213   05 VALUE 'FINTEGER-OF-DATE       ' PIC X(33).
1887 GC1213   05 VALUE 'FINTEGER-OF-DAY        ' PIC X(33).
1888 GC1213   05 VALUE 'FINTEGER-OF-FORMATTED-DATE ' PIC X(33).      UNIMPLEMENTED
1889 GC1213   05 VALUE 'FINTEGER-PART         ' PIC X(33).
1890          05 VALUE ' INTERFACE              ' PIC X(33).      UNIMPLEMENTED
1891          05 VALUE ' INTERFACE-ID           ' PIC X(33).      UNIMPLEMENTED
1892          05 VALUE ' INTERMEDIATE           ' PIC X(33).      UNIMPLEMENTED
1893          05 VALUE 'KINTO                  ' PIC X(33).
1894          05 VALUE ' INTRINSIC              ' PIC X(33).
1895          05 VALUE ' INVALID                ' PIC X(33).
1896          05 VALUE ' INVOKE                 ' PIC X(33).      UNIMPLEMENTED
1897          05 VALUE ' IS                     ' PIC X(33).
1898          05 VALUE ' JUST                   ' PIC X(33).
1899          05 VALUE ' JUSTIFIED              ' PIC X(33).
1900          05 VALUE ' KEPT                   ' PIC X(33).
1901          05 VALUE ' KEY                    ' PIC X(33).
1902          05 VALUE ' KEYBOARD                ' PIC X(33).
1903          05 VALUE ' LABEL                  ' PIC X(33).
1904          05 VALUE ' LAST                   ' PIC X(33).
1905          05 VALUE ' LC_ALL                  ' PIC X(33).      UNIMPLEMENTED
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 47

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 48

```

=====
1906          05 VALUE ' LC_COLLATE                ' PIC X(33).      UNIMPLEMENTED
1907          05 VALUE ' LC_CTYPE                  ' PIC X(33).      UNIMPLEMENTED
1908          05 VALUE ' LC_MESSAGES                ' PIC X(33).      UNIMPLEMENTED
1909          05 VALUE ' LC_MONETARY                ' PIC X(33).      UNIMPLEMENTED
1910          05 VALUE ' LC_NUMERIC                 ' PIC X(33).      UNIMPLEMENTED
1911          05 VALUE ' LC_TIME                     ' PIC X(33).      UNIMPLEMENTED
1912          05 VALUE ' LEADING                     ' PIC X(33).
1913          05 VALUE ' LEFT                         ' PIC X(33).
1914          05 VALUE ' LEFT-JUSTIFY                ' PIC X(33).      UNIMPLEMENTED
1915          05 VALUE ' LEFTLINE                    ' PIC X(33).
1916 GC1213    05 VALUE ' FLENGTH                     ' PIC X(33).
1917 GC1213    05 VALUE ' FLENGTH-AN                 ' PIC X(33).
1918          05 VALUE ' LENGTH-CHECK                ' PIC X(33).
1919          05 VALUE ' LESS                         ' PIC X(33).
1920          05 VALUE ' LIMIT                        ' PIC X(33).
1921          05 VALUE ' LIMITS                       ' PIC X(33).
1922          05 VALUE ' LINAGE                       ' PIC X(33).
1923          05 VALUE ' ILINAGE-COUNTER              ' PIC X(33).
1924          05 VALUE ' LINE                         ' PIC X(33).
1925 GC1213    05 VALUE ' ILINE-COUNTER                ' PIC X(33).
1926          05 VALUE ' LINES                        ' PIC X(33).
1927          05 VALUE ' KLINKAGE                     ' PIC X(33).
1928          05 VALUE ' KLOCAL-STORAGE                ' PIC X(33).
1929          05 VALUE ' LOCALE                       ' PIC X(33).
1930 GC1213    05 VALUE ' FLOCALE-COMPARE              ' PIC X(33).
1931 GC1213    05 VALUE ' FLOCALE-DATE                ' PIC X(33).
1932 GC1213    05 VALUE ' FLOCALE-TIME                ' PIC X(33).
1933 GC1213    05 VALUE ' FLOCALE-TIME-FROM-SECONDS  ' PIC X(33).
1934          05 VALUE ' LOCK                         ' PIC X(33).
1935 GC1213    05 VALUE ' FLOG                         ' PIC X(33).
1936 GC1213    05 VALUE ' FLOG10                      ' PIC X(33).
1937          05 VALUE ' LOW-VALUE                    ' PIC X(33).
1938          05 VALUE ' LOW-VALUES                   ' PIC X(33).
1939          05 VALUE ' LOWER                        ' PIC X(33).
1940 GC1213    05 VALUE ' FLOWER-CASE                  ' PIC X(33).
1941 GC1213    05 VALUE ' FLOWEST-ALGEBRAIC           ' PIC X(33).
1942          05 VALUE ' LOWLIGHT                     ' PIC X(33).
1943          05 VALUE ' MANUAL                       ' PIC X(33).
1944 GC1213    05 VALUE ' FMAX                         ' PIC X(33).
1945 GC1213    05 VALUE ' FMEAN                       ' PIC X(33).
1946 GC1213    05 VALUE ' FMEDIAN                     ' PIC X(33).
1947          05 VALUE ' MEMORY                       ' PIC X(33).
1948          05 VALUE ' VMERGE                       ' PIC X(33).
1949          05 VALUE ' MESSAGE                      ' PIC X(33).      OBSOLETE
1950          05 VALUE ' METHOD                        ' PIC X(33).      UNIMPLEMENTED
1951          05 VALUE ' METHOD-ID                     ' PIC X(33).      UNIMPLEMENTED
1952 GC1213    05 VALUE ' FMIDRANGE                    ' PIC X(33).
1953 GC1213    05 VALUE ' FMIN                       ' PIC X(33).
1954          05 VALUE ' MINUS                        ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 48

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 49

```

=====
1955 GC1213      05 VALUE 'FMODE                ' PIC X(33).
1956              05 VALUE ' MODE                ' PIC X(33).
1957 GC1213      05 VALUE 'FMODULE-CALLER-ID        ' PIC X(33).
1958 GC1213      05 VALUE 'FMODULE-DATE          ' PIC X(33).
1959 GC1213      05 VALUE 'FMODULE-FORMATTED-DATE    ' PIC X(33).
1960 GC1213      05 VALUE 'FMODULE-ID            ' PIC X(33).
1961 GC1213      05 VALUE 'FMODULE-PATH            ' PIC X(33).
1962 GC1213      05 VALUE 'FMODULE-SOURCE          ' PIC X(33).
1963 GC1213      05 VALUE 'FMODULE-TIME          ' PIC X(33).
1964 GC1213      05 VALUE 'FMONETARY-DECIMAL-POINT    ' PIC X(33).
1965 GC1213      05 VALUE 'FMONETARY-THOUSANDS-SEPARATOR  ' PIC X(33).
1966              05 VALUE 'VMOVE                ' PIC X(33).
1967              05 VALUE ' MULTIPLE            ' PIC X(33).
1968              05 VALUE 'VMULTIPLY           ' PIC X(33).
1969 GC0711      05 VALUE ' NAME                ' PIC X(33).
1970              05 VALUE ' NATIONAL            ' PIC X(33).
1971              05 VALUE ' NATIONAL-EDITED      ' PIC X(33).
1972 GC1213      05 VALUE 'FNATIONAL-OF            ' PIC X(33).      UNIMPLEMENTED
1973              05 VALUE ' NATIVE              ' PIC X(33).
1974              05 VALUE ' NEAREST-AWAY-FROM-ZERO    ' PIC X(33).
1975              05 VALUE ' NEAREST-EVEN          ' PIC X(33).
1976              05 VALUE ' NEAREST-TOWARD-ZERO      ' PIC X(33).
1977              05 VALUE ' NEGATIVE             ' PIC X(33).
1978              05 VALUE ' NESTED              ' PIC X(33).      UNIMPLEMENTED
1979              05 VALUE 'VNEXT                ' PIC X(33).
1980              05 VALUE ' NO                  ' PIC X(33).
1981              05 VALUE ' NO-ECHO             ' PIC X(33).
1982              05 VALUE ' NONE                ' PIC X(33).      UNIMPLEMENTED
1983              05 VALUE ' NORMAL              ' PIC X(33).
1984              05 VALUE ' NOT                 ' PIC X(33).
1985              05 VALUE ' NULL                ' PIC X(33).
1986              05 VALUE ' NULLS              ' PIC X(33).
1987              05 VALUE ' NUMBER             ' PIC X(33).
1988              05 VALUE ' INUMBER-OF-CALL-PARAMETERS  ' PIC X(33).
1989              05 VALUE ' NUMBERS             ' PIC X(33).
1990              05 VALUE ' NUMERIC            ' PIC X(33).
1991 GC1213      05 VALUE 'FNUMERIC-DECIMAL-POINT    ' PIC X(33).
1992              05 VALUE ' NUMERIC-EDITED        ' PIC X(33).
1993 GC1213      05 VALUE 'FNUMERIC-THOUSANDS-SEPARATOR  ' PIC X(33).
1994 GC1213      05 VALUE 'FNUMVAL              ' PIC X(33).
1995 GC1213      05 VALUE 'FNUMVAL-C            ' PIC X(33).
1996 GC1213      05 VALUE 'FNUMVAL-F            ' PIC X(33).
1997              05 VALUE ' OBJECT              ' PIC X(33).      UNIMPLEMENTED
1998              05 VALUE ' OBJECT-COMPUTER      ' PIC X(33).
1999              05 VALUE ' OBJECT-REFERENCE      ' PIC X(33).      UNIMPLEMENTED
2000              05 VALUE ' OCCURS              ' PIC X(33).
2001              05 VALUE ' OF                  ' PIC X(33).
2002              05 VALUE ' OFF                 ' PIC X(33).
2003              05 VALUE ' OMITTED            ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 49

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 50

```

=====
2004          05 VALUE ' ON                ' PIC X(33).
2005          05 VALUE ' ONLY              ' PIC X(33).
2006          05 VALUE ' VOPEN            ' PIC X(33).
2007          05 VALUE ' OPTIONAL         ' PIC X(33).
2008          05 VALUE ' OPTIONS          ' PIC X(33).      UNIMPLEMENTED
2009          05 VALUE ' OR               ' PIC X(33).
2010 GC1213   05 VALUE ' FORD              ' PIC X(33).
2011 GC1213   05 VALUE ' FORD-MAX         ' PIC X(33).
2012 GC1213   05 VALUE ' FORD-MIN        ' PIC X(33).
2013          05 VALUE ' ORDER            ' PIC X(33).
2014          05 VALUE ' ORGANISATION     ' PIC X(33).
2015          05 VALUE ' ORGANIZATION    ' PIC X(33).
2016          05 VALUE ' OTHER            ' PIC X(33).
2017          05 VALUE ' OUTPUT           ' PIC X(33).
2018          05 VALUE ' OVERFLOW         ' PIC X(33).
2019          05 VALUE ' OVERLINE        ' PIC X(33).
2020          05 VALUE ' OVERRIDE        ' PIC X(33).
2021          05 VALUE ' PACKED-DECIMAL   ' PIC X(33).
2022          05 VALUE ' PADDING          ' PIC X(33).
2023          05 VALUE ' PAGE             ' PIC X(33).
2024 GC1213   05 VALUE ' IPAGE-COUNTER    ' PIC X(33).
2025          05 VALUE ' PARAGRAPH        ' PIC X(33).
2026          05 VALUE ' VPERFORM         ' PIC X(33).
2027          05 VALUE ' PF               ' PIC X(33).
2028          05 VALUE ' PH               ' PIC X(33).
2029 GC1213   05 VALUE ' FPI              ' PIC X(33).
2030          05 VALUE ' KPIC              ' PIC X(33).
2031          05 VALUE ' KPICTURE         ' PIC X(33).
2032          05 VALUE ' PLUS              ' PIC X(33).
2033          05 VALUE ' KPOINTER         ' PIC X(33).
2034          05 VALUE ' POSITION           ' PIC X(33).
2035          05 VALUE ' POSITIVE          ' PIC X(33).
2036          05 VALUE ' PREFIXED         ' PIC X(33).      UNIMPLEMENTED
2037          05 VALUE ' PRESENT          ' PIC X(33).
2038 GC1213   05 VALUE ' FPRESENT-VALUE   ' PIC X(33).
2039          05 VALUE ' PREVIOUS          ' PIC X(33).
2040          05 VALUE ' MPRINTER          ' PIC X(33).
2041          05 VALUE ' PRINTING          ' PIC X(33).
2042          05 VALUE ' KPROCEDURE        ' PIC X(33).
2043          05 VALUE ' PROCEDURE-POINTER ' PIC X(33).
2044          05 VALUE ' PROCEDURES        ' PIC X(33).
2045          05 VALUE ' PROCEED           ' PIC X(33).
2046          05 VALUE ' PROGRAM          ' PIC X(33).
2047          05 VALUE ' KPROGRAM-ID       ' PIC X(33).
2048          05 VALUE ' PROGRAM-POINTER   ' PIC X(33).
2049          05 VALUE ' PROHIBITED        ' PIC X(33).
2050          05 VALUE ' PROMPT            ' PIC X(33).
2051          05 VALUE ' PROPERTY          ' PIC X(33).      UNIMPLEMENTED
2052          05 VALUE ' PROTOTYPE         ' PIC X(33).      UNIMPLEMENTED
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 50

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 51

```

=====
2053          05 VALUE 'PURGE'                ' PIC X(33).      OBSOLETE
2054          05 VALUE 'QUEUE'                ' PIC X(33).      OBSOLETE
2055          05 VALUE 'QUOTE'                ' PIC X(33).
2056          05 VALUE 'QUOTES'              ' PIC X(33).
2057          05 VALUE 'RAISE'                ' PIC X(33).      UNIMPLEMENTED
2058          05 VALUE 'RAISING'              ' PIC X(33).      UNIMPLEMENTED
2059 GC1213    05 VALUE 'FRANDOM'              ' PIC X(33).
2060 GC1213    05 VALUE 'FRANGE'              ' PIC X(33).
2061 GC1213    05 VALUE 'KRD'                 ' PIC X(33).
2062          05 VALUE 'VREAD'                ' PIC X(33).
2063          05 VALUE 'VREADY'               ' PIC X(33).
2064          05 VALUE 'VRECEIVE'             ' PIC X(33).      OBSOLETE
2065          05 VALUE 'RECORD'               ' PIC X(33).
2066          05 VALUE 'RECORDING'            ' PIC X(33).
2067          05 VALUE 'RECORDS'              ' PIC X(33).
2068          05 VALUE 'RECURSIVE'            ' PIC X(33).
2069          05 VALUE 'KREDEFINES'           ' PIC X(33).
2070          05 VALUE 'REEL'                 ' PIC X(33).
2071 GC0712    05 VALUE 'AREFERENCE'           ' PIC X(33).
2072          05 VALUE 'REFERENCES'            ' PIC X(33).
2073          05 VALUE 'RELATION'              ' PIC X(33).      UNIMPLEMENTED
2074          05 VALUE 'RELATIVE'              ' PIC X(33).
2075          05 VALUE 'VRELEASE'              ' PIC X(33).
2076 GC1213    05 VALUE 'FREM'                 ' PIC X(33).
2077          05 VALUE 'REMAINDER'             ' PIC X(33).
2078          05 VALUE 'REMARKS'               ' PIC X(33).      OBSOLETE
2079          05 VALUE 'REMOVAL'              ' PIC X(33).
2080          05 VALUE 'KRENAMES'              ' PIC X(33).
2081          05 VALUE 'REPLACE'               ' PIC X(33).
2082          05 VALUE 'KREPLACING'            ' PIC X(33).
2083          05 VALUE 'KREPORT'               ' PIC X(33).
2084          05 VALUE 'REPORTING'             ' PIC X(33).
2085          05 VALUE 'REPORTS'               ' PIC X(33).
2086          05 VALUE 'REPOSITORY'            ' PIC X(33).
2087          05 VALUE 'REQUIRED'              ' PIC X(33).
2088          05 VALUE 'RESERVE'              ' PIC X(33).
2089          05 VALUE 'VRESET'                ' PIC X(33).
2090          05 VALUE 'RESUME'                 ' PIC X(33).      UNIMPLEMENTED
2091          05 VALUE 'RETRY'                  ' PIC X(33).      UNIMPLEMENTED
2092          05 VALUE 'VRETURN'               ' PIC X(33).
2093          05 VALUE 'IRETURN-CODE'           ' PIC X(33).
2094          05 VALUE 'KRETURNING'            ' PIC X(33).
2095 GC1213    05 VALUE 'FREVERSE'             ' PIC X(33).
2096          05 VALUE 'REVERSE-VIDEO'         ' PIC X(33).
2097          05 VALUE 'REVERSED'              ' PIC X(33).
2098          05 VALUE 'REWIND'                ' PIC X(33).
2099          05 VALUE 'VREWRITE'              ' PIC X(33).
2100          05 VALUE 'RF'                    ' PIC X(33).
2101          05 VALUE 'RH'                    ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 51

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 52

```

=====
2102          05 VALUE ' RIGHT                ' PIC X(33).
2103          05 VALUE ' RIGHT-JUSTIFY        ' PIC X(33).      UNIMPLEMENTED
2104          05 VALUE ' VROLLBACK            ' PIC X(33).
2105          05 VALUE ' ROUNDED              ' PIC X(33).
2106          05 VALUE ' ROUNDING             ' PIC X(33).      UNIMPLEMENTED
2107          05 VALUE ' RUN                   ' PIC X(33).
2108          05 VALUE ' SAME                  ' PIC X(33).
2109          05 VALUE ' KSCREEN               ' PIC X(33).
2110          05 VALUE ' SCROLL               ' PIC X(33).
2111          05 VALUE ' KSD                  ' PIC X(33).
2112          05 VALUE ' VSEARCH              ' PIC X(33).
2113          05 VALUE ' SECONDS              ' PIC X(33).      UNIMPLEMENTED
2114 GC1213    05 VALUE ' FSECONDS-FROM-FORMATTED-TIME ' PIC X(33).
2115 GC1213    05 VALUE ' FSECONDS-PAST-MIDNIGHT ' PIC X(33).
2116          05 VALUE ' KSECTION             ' PIC X(33).
2117          05 VALUE ' SECURE               ' PIC X(33).
2118          05 VALUE ' SECURITY              ' PIC X(33).      OBSOLETE
2119          05 VALUE ' SEGMENT              ' PIC X(33).      OBSOLETE
2120          05 VALUE ' SEGMENT-LIMIT         ' PIC X(33).
2121          05 VALUE ' SELECT               ' PIC X(33).
2122          05 VALUE ' SELF                 ' PIC X(33).      UNIMPLEMENTED
2123          05 VALUE ' VSEND                ' PIC X(33).      OBSOLETE
2124          05 VALUE ' SENTENCE             ' PIC X(33).
2125          05 VALUE ' SEPARATE            ' PIC X(33).
2126          05 VALUE ' SEQUENCE            ' PIC X(33).
2127          05 VALUE ' SEQUENTIAL          ' PIC X(33).
2128          05 VALUE ' VSET                ' PIC X(33).
2129          05 VALUE ' SHARING              ' PIC X(33).
2130 GC1213    05 VALUE ' FSIGN              ' PIC X(33).
2131          05 VALUE ' SIGNED               ' PIC X(33).
2132          05 VALUE ' SIGNED-INT          ' PIC X(33).
2133          05 VALUE ' SIGNED-LONG        ' PIC X(33).
2134          05 VALUE ' SIGNED-SHORT       ' PIC X(33).
2135 GC1213    05 VALUE ' FSIN              ' PIC X(33).
2136          05 VALUE ' SIZE                ' PIC X(33).
2137          05 VALUE ' VSORT              ' PIC X(33).
2138          05 VALUE ' SORT-MERGE          ' PIC X(33).
2139          05 VALUE ' ISORT-RETURN        ' PIC X(33).
2140          05 VALUE ' SOURCE              ' PIC X(33).
2141          05 VALUE ' SOURCE-COMPUTER     ' PIC X(33).
2142          05 VALUE ' SOURCES             ' PIC X(33).      UNIMPLEMENTED
2143          05 VALUE ' SPACE              ' PIC X(33).
2144          05 VALUE ' SPACE-FILL         ' PIC X(33).      UNIMPLEMENTED
2145          05 VALUE ' SPACES             ' PIC X(33).
2146          05 VALUE ' SPECIAL-NAMES      ' PIC X(33).
2147 GC1213    05 VALUE ' FSQRT            ' PIC X(33).
2148          05 VALUE ' STANDARD           ' PIC X(33).
2149          05 VALUE ' STANDARD-1         ' PIC X(33).
2150          05 VALUE ' STANDARD-2         ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 52

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 53

```

=====
2151          05 VALUE ' STANDARD-BINARY          ' PIC X(33).      UNIMPLEMENTED
2152 GC1213    05 VALUE 'FSTANDARD-COMPARE        ' PIC X(33).      UNIMPLEMENTED
2153          05 VALUE ' STANDARD-DECIMAL        ' PIC X(33).      UNIMPLEMENTED
2154 GC1213    05 VALUE 'FSTANDARD-DEVIATION      ' PIC X(33).
2155          05 VALUE 'VSTART                    ' PIC X(33).
2156          05 VALUE ' STATEMENT                ' PIC X(33).      UNIMPLEMENTED
2157          05 VALUE ' STATIC                   ' PIC X(33).
2158          05 VALUE ' STATUS                   ' PIC X(33).
2159          05 VALUE ' STDCALL                  ' PIC X(33).
2160          05 VALUE 'MSTDERR                   ' PIC X(33).
2161          05 VALUE 'MSTDIN                    ' PIC X(33).
2162          05 VALUE 'MSTDOUT                   ' PIC X(33).
2163          05 VALUE ' STEP                     ' PIC X(33).
2164          05 VALUE 'VSTOP                     ' PIC X(33).
2165 GC1213    05 VALUE 'FSTORED-CHAR-LENGTH      ' PIC X(33).
2166          05 VALUE 'VSTRING                   ' PIC X(33).
2167          05 VALUE ' STRONG                    ' PIC X(33).      UNIMPLEMENTED
2168          05 VALUE ' SUB-QUEUE-1              ' PIC X(33).      OBSOLETE
2169          05 VALUE ' SUB-QUEUE-2              ' PIC X(33).      OBSOLETE
2170          05 VALUE ' SUB-QUEUE-3              ' PIC X(33).      OBSOLETE
2171 GC1213    05 VALUE 'FSUBSTITUTE               ' PIC X(33).
2172 GC1213    05 VALUE 'FSUBSTITUTE-CASE         ' PIC X(33).
2173          05 VALUE 'VSUBTRACT                 ' PIC X(33).
2174 GC1213    05 VALUE 'FSUM                     ' PIC X(33).
2175          05 VALUE ' SUPER                     ' PIC X(33).      UNIMPLEMENTED
2176          05 VALUE 'VSUPPRESS                 ' PIC X(33).
2177          05 VALUE 'MSW0                      ' PIC X(33).
2178          05 VALUE 'MSW1                      ' PIC X(33).
2179          05 VALUE 'MSW10                     ' PIC X(33).
2180          05 VALUE 'MSW11                     ' PIC X(33).
2181          05 VALUE 'MSW12                     ' PIC X(33).
2182          05 VALUE 'MSW13                     ' PIC X(33).
2183          05 VALUE 'MSW14                     ' PIC X(33).
2184          05 VALUE 'MSW15                     ' PIC X(33).
2185          05 VALUE 'MSW2                      ' PIC X(33).
2186          05 VALUE 'MSW3                      ' PIC X(33).
2187          05 VALUE 'MSW4                      ' PIC X(33).
2188          05 VALUE 'MSW5                      ' PIC X(33).
2189          05 VALUE 'MSW6                      ' PIC X(33).
2190          05 VALUE 'MSW7                      ' PIC X(33).
2191          05 VALUE 'MSW8                      ' PIC X(33).
2192          05 VALUE 'MSW9                      ' PIC X(33).
2193          05 VALUE 'MSWITCH-0                 ' PIC X(33).
2194          05 VALUE 'MSWITCH-1                 ' PIC X(33).
2195          05 VALUE 'MSWITCH-10                ' PIC X(33).
2196          05 VALUE 'MSWITCH-11                ' PIC X(33).
2197          05 VALUE 'MSWITCH-12                ' PIC X(33).
2198          05 VALUE 'MSWITCH-13                ' PIC X(33).
2199          05 VALUE 'MSWITCH-14                ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 53

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 54

```

=====
2200          05 VALUE 'MSWITCH-15          ' PIC X(33).
2201          05 VALUE 'MSWITCH-2          ' PIC X(33).
2202          05 VALUE 'MSWITCH-3          ' PIC X(33).
2203          05 VALUE 'MSWITCH-4          ' PIC X(33).
2204          05 VALUE 'MSWITCH-5          ' PIC X(33).
2205          05 VALUE 'MSWITCH-6          ' PIC X(33).
2206          05 VALUE 'MSWITCH-7          ' PIC X(33).
2207          05 VALUE 'MSWITCH-8          ' PIC X(33).
2208          05 VALUE 'MSWITCH-9          ' PIC X(33).
2209          05 VALUE ' SYMBOL              ' PIC X(33).      UNIMPLEMENTED
2210          05 VALUE ' SYMBOLIC            ' PIC X(33).
2211          05 VALUE ' SYNC                ' PIC X(33).
2212          05 VALUE ' SYNCHRONISED        ' PIC X(33).
2213          05 VALUE ' SYNCHRONIZED        ' PIC X(33).
2214          05 VALUE 'MSYSERR             ' PIC X(33).
2215          05 VALUE 'MSYSIN              ' PIC X(33).
2216          05 VALUE 'MSYSIPT             ' PIC X(33).
2217          05 VALUE 'MSYSLIST            ' PIC X(33).
2218          05 VALUE 'MSYSLST             ' PIC X(33).
2219          05 VALUE 'MSYSOUT             ' PIC X(33).
2220          05 VALUE ' SYSTEM-DEFAULT      ' PIC X(33).
2221          05 VALUE ' TABLE              ' PIC X(33).      UNIMPLEMENTED
2222          05 VALUE 'KTALLYING            ' PIC X(33).
2223 GC1213    05 VALUE 'FTAN                ' PIC X(33).
2224          05 VALUE ' TAPE                ' PIC X(33).
2225          05 VALUE ' TERMINAL            ' PIC X(33).      OBSOLETE
2226          05 VALUE 'VTERMINATE          ' PIC X(33).
2227          05 VALUE ' TEST                ' PIC X(33).
2228 GC1213    05 VALUE 'FTEST-DATE-YYYYMMDD ' PIC X(33).
2229 GC1213    05 VALUE 'FTEST-DAY-YYYYDDD   ' PIC X(33).
2230 GC1213    05 VALUE 'FTEST-FORMATTED-DATETIME ' PIC X(33).      UNIMPLEMENTED
2231 GC1213    05 VALUE 'FTEST-NUMVAL        ' PIC X(33).
2232 GC1213    05 VALUE 'FTEST-NUMVAL-C     ' PIC X(33).
2233 GC1213    05 VALUE 'FTEST-NUMVAL-F     ' PIC X(33).
2234          05 VALUE ' TEXT                ' PIC X(33).      OBSOLETE
2235          05 VALUE ' THAN                ' PIC X(33).
2236          05 VALUE ' THEN                ' PIC X(33).
2237          05 VALUE ' THROUGH             ' PIC X(33).
2238          05 VALUE ' THRU                ' PIC X(33).
2239          05 VALUE ' TIME                ' PIC X(33).
2240 GC0711    05 VALUE ' TIME-OUT            ' PIC X(33).
2241 GC0711    05 VALUE ' TIMEOUT            ' PIC X(33).
2242          05 VALUE ' TIMES                ' PIC X(33).
2243          05 VALUE 'KTO                  ' PIC X(33).
2244          05 VALUE ' TOP                  ' PIC X(33).
2245          05 VALUE ' TOWARD-GREATER       ' PIC X(33).
2246          05 VALUE ' TOWARD-LESSER       ' PIC X(33).
2247          05 VALUE ' TRAILING            ' PIC X(33).
2248          05 VALUE ' TRAILING-SIGN       ' PIC X(33).      UNIMPLEMENTED
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 54

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 55

```

=====
2249          05 VALUE 'VTRANSFORM          ' PIC X(33).
2250 GC1213    05 VALUE 'FTRIM              ' PIC X(33).
2251          05 VALUE ' TRUE              ' PIC X(33).
2252          05 VALUE ' TRUNCATION        ' PIC X(33).
2253          05 VALUE ' TYPE              ' PIC X(33).
2254          05 VALUE ' TYPEDEF          ' PIC X(33).      UNIMPLEMENTED
2255          05 VALUE ' UCS-4            ' PIC X(33).      UNIMPLEMENTED
2256          05 VALUE ' UNDERLINE        ' PIC X(33).
2257          05 VALUE ' UNIT              ' PIC X(33).
2258          05 VALUE ' UNIVERSAL        ' PIC X(33).      UNIMPLEMENTED
2259          05 VALUE ' VUNLOCK          ' PIC X(33).
2260          05 VALUE ' UNSIGNED          ' PIC X(33).
2261          05 VALUE ' UNSIGNED-INT     ' PIC X(33).
2262          05 VALUE ' UNSIGNED-LONG    ' PIC X(33).
2263          05 VALUE ' UNSIGNED-SHORT   ' PIC X(33).
2264          05 VALUE ' VUNSTRING        ' PIC X(33).
2265          05 VALUE ' UNTIL            ' PIC X(33).
2266          05 VALUE ' KUP              ' PIC X(33).
2267          05 VALUE ' UPDATE           ' PIC X(33).
2268          05 VALUE ' UPON             ' PIC X(33).
2269          05 VALUE ' UPPER            ' PIC X(33).
2270 GC1213    05 VALUE ' FUPPER-CASE      ' PIC X(33).
2271          05 VALUE ' USAGE            ' PIC X(33).
2272          05 VALUE ' VUSE             ' PIC X(33).
2273 GC0711    05 VALUE ' USER           ' PIC X(33).
2274          05 VALUE ' USER-DEFAULT    ' PIC X(33).
2275          05 VALUE ' KUSING           ' PIC X(33).
2276          05 VALUE ' UTF-16          ' PIC X(33).      UNIMPLEMENTED
2277          05 VALUE ' UTF-8           ' PIC X(33).      UNIMPLEMENTED
2278          05 VALUE ' VAL-STATUS      ' PIC X(33).      UNIMPLEMENTED
2279          05 VALUE ' VALID           ' PIC X(33).      UNIMPLEMENTED
2280          05 VALUE ' VALIDATE        ' PIC X(33).      UNIMPLEMENTED
2281          05 VALUE ' VALIDATE-STATUS ' PIC X(33).      UNIMPLEMENTED
2282 GC0712    05 VALUE ' AVALUE          ' PIC X(33).
2283          05 VALUE ' VALUES         ' PIC X(33).
2284 GC1213    05 VALUE ' FVARIANCE      ' PIC X(33).
2285          05 VALUE ' KVARYING        ' PIC X(33).
2286          05 VALUE ' VDISABLE        ' PIC X(33).      UNIMPLEMENTED
2287          05 VALUE ' WAIT            ' PIC X(33).
2288          05 VALUE ' VWHEN          ' PIC X(33).
2289 GC1213    05 VALUE ' FWHEN-COMPILED  ' PIC X(33).
2290          05 VALUE ' WITH            ' PIC X(33).
2291          05 VALUE ' WORDS           ' PIC X(33).
2292          05 VALUE ' KWORKING-STORAGE ' PIC X(33).
2293          05 VALUE ' VWRITE          ' PIC X(33).
2294 GC1213    05 VALUE ' FYEAR-TO-YYYY   ' PIC X(33).
2295          05 VALUE ' YYYYDDD         ' PIC X(33).
2296          05 VALUE ' YYYYMMDD       ' PIC X(33).
2297          05 VALUE ' ZERO            ' PIC X(33).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 55

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 56

```

=====
2298          05 VALUE ' ZERO-FILL                ' PIC X(33).      UNIMPLEMENTED
2299          05 VALUE ' ZEROES                  ' PIC X(33).
2300          05 VALUE ' ZEROS                    ' PIC X(33).
2301          01 WS-Reserved-Word-Table-TXT REDEFINES WS-Reserved-Words-TXT.
2302 GC1113     05 WS-Reserved-Word-TXT           OCCURS 754 TIMES
2303                                     ASCENDING KEY
2304                                     WS-RW-Word-TXT
2305                                     INDEXED WS-RW-IDX.
2306          10 WS-RW-Type-CD                     PIC X(1).
2307          10 WS-RW-Word-TXT                   PIC X(32).
2308
2309          01 WS-Runtime-Switches.
2310 GC0710     05 WS-RS-Duplicate-CHR             PIC X(1).
2311          05 WS-RS-In-Which-Pgm-CHR           PIC X(1).
2312          88 WS-RS-In-Main-Module-BOOL        VALUE 'M'.
2313          88 WS-RS-In-Copybook-BOOL          VALUE 'C'.
2314          05 WS-RS-Last-Token-Ended-Sent-CHR PIC X(1).
2315          05 WS-RS-Processing-PICTURE-CHR    PIC X(1).
2316          05 WS-RS-Token-Ended-Sentence-CHR  PIC X(1).
2317 GC0710     05 WS-RS-Verb-Has-Been-Found-CHR PIC X(1).
2318
2319          01 WS-Saved-Section-TXT             PIC X(15).
2320
2321 GC1213     01 WS-Src-Dashes-TXT.
2322 GC0712     05 VALUE '======'                 PIC X(7).
2323 GC0712     05 VALUE ALL '='                 PIC X(128).
2324
2325          01 WS-Src-Detail-Line-TXT.
2326          05 WS-SDL-Line-NUM                   PIC ZZZZZ9.
2327          05 FILLER                            PIC X(1).
2328          05 WS-SDL-Statement-TXT             PIC X(256).
2329
2330 GC1213     01 WS-Src-Hold-TXT                 PIC X(256).
2331
2332          01 WS-Src-Line-NUM                   PIC 9(6).
2333
2334 GC1213     01 WS-Src-Lines-NUM               USAGE BINARY-LONG.
2335
2336          01 WS-Src-SUB                       USAGE BINARY-LONG.
2337
2338          01 WS-Tally-QTY                     USAGE BINARY-LONG.
2339
2340          01 WS-Temp-10-Chars-TXT             PIC X(10).
2341
2342          01 WS-Temp-32-Chars-1-TXT           PIC X(32).
2343
2344 GC0711     01 WS-Temp-32-Chars-2-TXT         PIC X(32).
2345
2346 GC0711     01 WS-Temp-32-Chars-3-TXT         PIC X(32).
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 56

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 57

```

=====
2347
2348 GC0712 01 WS-Temp-65-Chars-TXT          PIC X(65).
2349
2350          01 WS-Temp-256-Chars-TXT      PIC X(256).
2351
2352          01 WS-Today-DT                 PIC 9(8).
2353
2354          01 WS-Token-Curr-TXT           PIC X(32).
2355
2356          01 WS-Token-Curr-Uc-TXT        PIC X(32).
2357
2358          01 WS-Token-Prev-TXT           PIC X(32).
2359
2360          01 WS-Token-Search-TXT         PIC X(32).
2361
2362          01 WS-Token-Type-CD             PIC X(1).
2363 GC0712          88 WS-TT-Token-Is-Argtype-BOOL      VALUE 'A'.
2364          88 WS-TT-Token-Is-EOF-BOOL        VALUE HIGH-VALUES.
2365 GC1213          88 WS-TT-Token-Is-Function-BOOL     VALUE 'F'.
2366          88 WS-TT-Token-Is-Identifier-BOOL    VALUE 'I'.
2367 GC0712          88 WS-TT-Token-Is-Keyword-BOOL     VALUE 'K', 'V', 'A'.
2368          88 WS-TT-Token-Is-Lit-Alpha-BOOL    VALUE 'L'.
2369          88 WS-TT-Token-Is-Lit-Number-BOOL   VALUE 'N'.
2370          88 WS-TT-Token-Is-Verb-BOOL        VALUE 'V'.
2371 GC1213          88 WS-TT-Token-Is-Reserved-Wd-BOOL  VALUE ' ', 'F'.
2372
2373          01 WS-Usernames-QTY              USAGE BINARY-LONG.
2374
2375          01 WS-Version-TXT                PIC X(23).
2376
2377          01 WS-Xref-Detail-Line-TXT.
2378          05 WS-XDL-Prog-ID-TXT            PIC X(15).
2379          05 FILLER                        PIC X(1).
2380          05 WS-XDL-Token-TXT              PIC X(32).
2381          05 FILLER                        PIC X(1).
2382          05 WS-XDL-Def-Line-NUM          PIC ZZZZ9.
2383          05 FILLER                        PIC X(1).
2384          05 WS-XDL-Section-TXT           PIC X(15).
2385          05 FILLER                        PIC X(1).
2386          05 WS-XDL-Reference-TXT         OCCURS 8 TIMES.
2387          10 WS-XDL-Ref-Line-NUM         PIC ZZZZ9.
2388          10 WS-XDL-Ref-Flag-CHR         PIC X(1).
2389          10 FILLER                      PIC X(1).
2390
2391 GC1213 01 WS-Xref-Lines-Per-Rec-NUM     PIC 9(1).
2392
2393          LINKAGE SECTION.
2394 GC0712 01 L-Listing-Fn-TXT              PIC X(256).
2395
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 57

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 58

```
=====
2396      01 L-Src-Fn-TXT                PIC X(256).
2397
2398 GC0712 01 L-OS-Type-CD              PIC 9(1).
2399
2400 GC1213 01 L-LPP-NUM                  USAGE BINARY-LONG.
2401
2402 GC1213 01 L-LPP-Port-NUM             USAGE BINARY-LONG.
2403
2404 GC1213 01 L-Listing-CD              PIC 9(1).
=====
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 58

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 59

```

=====
2406 GC0712 PROCEDURE DIVISION USING L-Listing-Fn-TXT
2407 GC0712                               L-Src-Fn-TXT
2408 GC0712                               L-OS-Type-CD
2409 GC1213                               L-LPP-NUM
2410 GC1213                               L-LPP-Port-NUM
2411 GC1213                               L-Listing-CD.
2412      000-Main SECTION.
2413      PERFORM 100-Initialization
2414 GC0712      OPEN OUTPUT F-Listing-FILE
2415 GC0712      PERFORM 500-Produce-Source-Listing
2416 GC0712      SORT F-Sort-Work-FILE
2417 GC0712          ASCENDING KEY      F-SW-Prog-ID-TXT
2418 GC0712          F-SW-Token-Uc-TXT
2419 GC0712          F-SW-Ref-Line-NUM
2420 GC0712          INPUT PROCEDURE 300-Tokenize-Source
2421 GC0712          OUTPUT PROCEDURE 400-Produce-Xref-Listing
2422 GC0712      CLOSE F-Listing-FILE
2423      GOBACK
2424      .
=====

```

```

=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 59

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 60

```

=====
2426      *>*****
2427      *> Perform all program-wide initialization operations      **
2428      *>*****
2429      100-Initialization SECTION.
2430 GC1213      MOVE 0 TO WS-Page-NUM
2431 GC1213      MOVE 'N' TO WS-Suppress-FF-CHR
2432 GC1213      MOVE SPACES TO WS-Copyright-TXT
2433 GC1213      STRING 'GCic for '                DELIMITED SIZE
2434 GC1213                WS-OS-Type-TXT(L-OS-Type-CD) DELIMITED SPACE
2435 GC1213                ' Copyright (C) 2009-2014, Gary L. Cutler, GPL'
2436 GC1213                DELIMITED SIZE
2437 GC1213      INTO WS-Copyright-TXT
2438 GC1213      MOVE 'GNU COBOL 2.1 23NOV2013' TO WS-Version-TXT
2439      MOVE TRIM(L-Src-Fn-TXT,Leading) TO L-Src-Fn-TXT
2440 GC1010      PERFORM VARYING WS-I-SUB FROM LENGTH(L-Src-Fn-TXT) BY -1 *> Locate last direct
        ory delimiter character so that the filename can be extracted
2441 GC1010                UNTIL L-Src-Fn-TXT(WS-I-SUB:1) = '/' OR '\',
2442 GC1010                OR WS-I-SUB = 0
2443 GC1010      END-PERFORM
2444 GC1010      IF WS-I-SUB = 0
2445 GC1010                MOVE UPPER-CASE(L-Src-Fn-TXT) TO WS-Main-Module-Name-TXT *> No directory d
        elimiter, whole thing is filename
2446 GC1010      ELSE
2447 GC1010                ADD 1 TO WS-I-SUB
2448 GC1010                MOVE UPPER-CASE(L-Src-Fn-TXT(WS-I-SUB:))
2449 GC1010                TO WS-Main-Module-Name-TXT *> Extract filename
2450 GC1010      END-IF
2451 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
2452 GC1213                MOVE 8 TO WS-Xref-Lines-Per-Rec-NUM
2453 GC1213                ACCEPT WS-Lines-Per-Page-Env-TXT
2454 GC1213                FROM ENVIRONMENT 'GCXREF_LINES'
2455 GC1213      ELSE *> PORTRAIT
2456 GC1213                MOVE 3 TO WS-Xref-Lines-Per-Rec-NUM
2457 GC1213                ACCEPT WS-Lines-Per-Page-Env-TXT
2458 GC1213                FROM ENVIRONMENT 'GCXREF_LINES_PORT'
2459 GC1213      END-IF
2460      INSPECT L-Src-Fn-TXT REPLACING ALL '\ ' BY '/'
2461      MOVE L-Src-Fn-TXT TO WS-Program-Path-TXT
2462      CALL 'C$JUSTIFY' USING WS-Program-Path-TXT, 'Right'
2463      MOVE LENGTH(TRIM(L-Src-Fn-TXT,Trailing)) TO WS-I-SUB
2464      MOVE 0 TO WS-J-SUB
2465      PERFORM UNTIL L-Src-Fn-TXT(WS-I-SUB:1) = '/'
2466                OR WS-I-SUB = 0
2467                SUBTRACT 1 FROM WS-I-SUB
2468                ADD 1 TO WS-J-SUB
2469      END-PERFORM
2470      UNSTRING L-Src-Fn-TXT((WS-I-SUB + 1):WS-J-SUB)
2471      DELIMITED BY ' .'
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 60

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 61

```

=====
2472          INTO WS-Filename-TXT
2473          WS-Dummy-TXT
2474 GC1010    STRING
2475 GC1010          TRIM(WS-Filename-TXT,Trailing)
2476 GC1010          '.i'
2477 GC1010          DELIMITED SIZE
2478 GC1010          INTO WS-Expanded-Src-Fn-TXT
2479 GC1010    CALL 'CBL_CHECK_FILE_EXIST' USING WS-Expanded-Src-Fn-TXT
2480 GC1010          WS-Temp-256-Chars-TXT
2481 GC1010    IF RETURN-CODE NOT = 0
2482 GC1010          GOBACK
2483 GC1010    END-IF
2484          IF WS-Lines-Per-Page-Env-TXT NOT = SPACES
2485              MOVE NUMVAL(WS-Lines-Per-Page-Env-TXT)
2486                  TO WS-Lines-Per-Page-NUM
2487          ELSE
2488 GC1213      IF L-LISTING-CD = 1 *> LANDSCAPE
2489 GC1213          MOVE L-LPP-NUM TO WS-Lines-Per-Page-NUM
2490 GC1213      ELSE *> PORTRAIT
2491 GC1213          MOVE L-LPP-Port-NUM TO WS-Lines-Per-Page-NUM
2492 GC1213      END-IF
2493          END-IF
2494 GC1213    SUBTRACT 3 FROM WS-Lines-Per-Page-NUM *> FOR PAGE FOOTER
2495          ACCEPT WS-Today-DT FROM DATE YYYYMMDD
2496 GC1213    MOVE WS-Today-DT TO WS-Formatted-DT
2497          MOVE '?????????????...' TO WS-Curr-Prog-ID-TXT
2498          MOVE SPACES              TO WS-Curr-Verb-TXT
2499          WS-Held-Reference-TXT
2500          .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 61

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 62

```

=====
2502      300-Tokenize-Source SECTION.
2503      OPEN INPUT F-Expanded-Src-FILE
2504      MOVE SPACES TO F-Expanded-Src-REC
2505      MOVE 256 TO WS-Src-SUB
2506      MOVE 0 TO WS-Usernames-QTY
2507          WS-Curr-Line-NUM
2508      MOVE '?' TO WS-Curr-Division-TXT
2509 GC0710  MOVE 'N' TO WS-RS-Verb-Has-Been-Found-CHR
2510      PERFORM FOREVER
2511          PERFORM 310-Get-Token
2512          IF WS-TT-Token-Is-EOF-BOOL
2513              EXIT PERFORM
2514          END-IF
2515          MOVE UPPER-CASE(WS-Token-Curr-TXT)
2516              TO WS-Token-Curr-Uc-TXT
2517 GC1010  IF WS-TT-Token-Is-Keyword-BOOL
2518 GC1010  OR WS-TT-Token-Is-Reserved-Wd-BOOL
2519 GC1010  MOVE WS-Token-Curr-Uc-TXT TO WS-Token-Curr-TXT
2520 GC1010  END-IF
2521      IF WS-TT-Token-Is-Verb-BOOL
2522          MOVE WS-Token-Curr-Uc-TXT TO WS-Curr-Verb-TXT
2523              WS-Token-Prev-TXT
2524          IF WS-Held-Reference-TXT NOT = SPACES
2525              MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
2526              MOVE SPACES TO WS-Held-Reference-TXT
2527              RELEASE F-Sort-Work-REC
2528          END-IF
2529      END-IF
2530      EVALUATE TRUE
2531      WHEN WS-CD-In-IDENT-DIV-BOOL
2532          PERFORM 320-IDENTIFICATION-DIVISION
2533      WHEN WS-CD-In-ENV-DIV-BOOL
2534          PERFORM 330-ENVIRONMENT-DIVISION
2535      WHEN WS-CD-In-DATA-DIV-BOOL
2536          PERFORM 340-DATA-DIVISION
2537      WHEN WS-CD-In-PROC-DIV-BOOL
2538          PERFORM 350-PROCEDURE-DIVISION
2539      END-EVALUATE
2540      IF WS-TT-Token-Is-Keyword-BOOL
2541          MOVE WS-Token-Curr-Uc-TXT TO WS-Token-Prev-TXT
2542      END-IF
2543      IF WS-RS-Token-Ended-Sentence-CHR = 'Y'
2544      AND WS-Curr-Division-TXT NOT = 'I'
2545          MOVE SPACES TO WS-Token-Prev-TXT
2546              WS-Curr-Verb-TXT
2547      END-IF
2548
2549      END-PERFORM
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 62

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 63

```
=====
2550      CLOSE F-Expanded-Src-FILE
2551      .
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 63

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 64

```

=====
2553      310-Get-Token SECTION.
2554      *>-- Position to 1st non-blank character
2555          MOVE WS-RS-Token-Ended-Sentence-CHR
2556              TO WS-RS-Last-Token-Ended-Sent-CHR
2557          MOVE 'N' TO WS-RS-Token-Ended-Sentence-CHR
2558          PERFORM UNTIL F-Expanded-Src-REC(WS-Src-SUB : 1) NOT = SPACE
2559              IF WS-Src-SUB > 255
2560                  READ F-Expanded-Src-FILE AT END
2561                      IF WS-Held-Reference-TXT NOT = SPACES
2562                          MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
2563                          MOVE SPACES          TO WS-Held-Reference-TXT
2564                          RELEASE F-Sort-Work-REC
2565                      END-IF
2566                      SET WS-TT-Token-Is-EOF-BOOL TO TRUE
2567                      MOVE 0 TO WS-Curr-Line-NUM
2568                      EXIT SECTION
2569          END-READ
2570 GC0712      IF F-ES-1-7-TXT NOT = '#DEFLIT'
2571 GC0712          IF F-ES-1-CHR = '#'
2572 GC0712              PERFORM 311-Control-Record
2573 GC0712          ELSE
2574 GC0712              PERFORM 312-Expanded-Src-Record
2575 GC0712          END-IF
2576 GC0712      END-IF
2577          ELSE
2578              ADD 1 TO WS-Src-SUB
2579          END-IF
2580      END-PERFORM
2581      *>-- Extract token string
2582          MOVE F-Expanded-Src-REC(WS-Src-SUB : 1)
2583              TO WS-Curr-CHR
2584          MOVE F-Expanded-Src-REC(WS-Src-SUB + 1: 1)
2585              TO WS-Next-CHR
2586          IF WS-Curr-CHR = '.'
2587              ADD 1 TO WS-Src-SUB
2588              MOVE WS-Curr-CHR TO WS-Token-Curr-TXT
2589              MOVE SPACE TO WS-Token-Type-CD
2590              MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2591          EXIT SECTION
2592      END-IF
2593          IF WS-Curr-Char-Is-Punct-BOOL
2594              AND WS-Curr-CHR = '='
2595              AND WS-Curr-Division-TXT = 'P'
2596              ADD 1 TO WS-Src-SUB
2597              MOVE 'EQUALS' TO WS-Token-Curr-TXT
2598              MOVE 'K'      TO WS-Token-Type-CD
2599          EXIT SECTION
2600      END-IF
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 64

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 65

```

=====
2601         IF WS-Curr-Char-Is-Punct-BOOL *> So subscripts don't get flagged w/ '*'
2602         AND WS-Curr-CHR = '('
2603         AND WS-Curr-Division-TXT = 'P'
2604         MOVE SPACES TO WS-Token-Prev-TXT
2605         END-IF
2606         IF WS-Curr-Char-Is-Punct-BOOL
2607         ADD 1 TO WS-Src-SUB
2608         MOVE WS-Curr-CHR TO WS-Token-Curr-TXT
2609         MOVE SPACE TO WS-Token-Type-CD
2610         EXIT SECTION
2611         END-IF
2612         IF WS-Curr-Char-Is-Quote-BOOL
2613         ADD 1 TO WS-Src-SUB
2614         UNSTRING F-Expanded-Src-REC
2615             DELIMITED BY WS-Curr-CHR
2616             INTO WS-Token-Curr-TXT
2617             WITH POINTER WS-Src-SUB
2618         IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2619             MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2620             ADD 1 TO WS-Src-SUB
2621         END-IF
2622         SET WS-TT-Token-Is-Lit-Alpha-BOOL TO TRUE
2623         EXIT SECTION
2624         END-IF
2625         IF WS-Curr-Char-Is-X-BOOL AND WS-Next-Char-Is-Quote-BOOL
2626         ADD 2 TO WS-Src-SUB
2627         UNSTRING F-Expanded-Src-REC
2628             DELIMITED BY WS-Next-CHR
2629             INTO WS-Token-Curr-TXT
2630             WITH POINTER WS-Src-SUB
2631         IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2632             MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2633             ADD 1 TO WS-Src-SUB
2634         END-IF
2635         SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2636         EXIT SECTION
2637         END-IF
2638         IF WS-Curr-Char-Is-Z-BOOL AND WS-Next-Char-Is-Quote-BOOL
2639         ADD 2 TO WS-Src-SUB
2640         UNSTRING F-Expanded-Src-REC
2641             DELIMITED BY WS-Next-CHR
2642             INTO WS-Token-Curr-TXT
2643             WITH POINTER WS-Src-SUB
2644         IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2645             MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2646             ADD 1 TO WS-Src-SUB
2647         END-IF
2648         SET WS-TT-Token-Is-Lit-Alpha-BOOL TO TRUE
2649         EXIT SECTION
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 65

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 66

```

=====
2650          END-IF
2651          IF WS-RS-Processing-PICTURE-CHR = 'Y'
2652              UNSTRING F-Expanded-Src-REC
2653                  DELIMITED BY ' . ' OR ' '
2654                  INTO WS-Token-Curr-TXT
2655                  DELIMITER IN WS-Delim-TXT
2656                  WITH POINTER WS-Src-SUB
2657          IF WS-Delim-TXT = ' . '
2658              MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2659              ADD 1 TO WS-Src-SUB
2660          END-IF
2661          IF UPPER-CASE(WS-Token-Curr-TXT) = 'IS'
2662              MOVE SPACE TO WS-Token-Type-CD
2663              EXIT SECTION
2664          ELSE
2665              MOVE 'N' TO WS-RS-Processing-PICTURE-CHR
2666              MOVE SPACE TO WS-Token-Type-CD
2667              EXIT SECTION
2668          END-IF
2669          END-IF
2670          UNSTRING F-Expanded-Src-REC
2671              DELIMITED BY ' . ' OR ' ' OR '=' OR '(' OR ')' OR '*'
2672                  OR '/' OR '&' OR ';' OR ',' OR '<'
2673                  OR '>' OR ':'
2674              INTO WS-Token-Curr-TXT
2675              DELIMITER IN WS-Delim-TXT
2676              WITH POINTER WS-Src-SUB
2677          IF WS-Delim-TXT = ' . '
2678              MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2679          END-IF
2680          IF WS-Delim-TXT NOT = ' . ' AND ' '
2681              SUBTRACT 1 FROM WS-Src-SUB
2682          END-IF
2683          *>-- Classify Token
2684          MOVE UPPER-CASE(WS-Token-Curr-TXT) TO WS-Token-Search-TXT
2685          IF WS-Token-Search-TXT = 'EQUAL' OR 'EQUALS'
2686              MOVE 'EQUALS' TO WS-Token-Curr-TXT
2687              MOVE 'K' TO WS-Token-Type-CD
2688              EXIT SECTION
2689          END-IF
2690          SEARCH ALL WS-Reserved-Word-TXT
2691              WHEN WS-RW-Word-TXT (WS-RW-IDX) = WS-Token-Search-TXT
2692                  MOVE WS-RW-Type-CD (WS-RW-IDX) TO WS-Token-Type-CD
2693 GC0710          IF WS-TT-Token-Is-Verb-BOOL
2694 GC0710              MOVE 'Y' TO WS-RS-Verb-Has-Been-Found-CHR
2695 GC0710          END-IF
2696              EXIT SECTION
2697          END-SEARCH
2698          *>-- Not a reserved word, must be a user name
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 66

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 67

```
=====
2699          SET WS-TT-Token-Is-Identifier-BOOL TO TRUE
2700          PERFORM 313-Check-For-Numeric-Token
2701          IF WS-TT-Token-Is-Lit-Number-BOOL
2702              IF (WS-RS-Last-Token-Ended-Sent-CHR = 'Y')
2703                  AND (WS-Curr-Division-TXT = 'D')
2704                      MOVE 'LEVEL #' TO WS-Token-Curr-TXT
2705                      MOVE 'K' TO WS-Token-Type-CD
2706                      EXIT SECTION
2707              ELSE
2708                  EXIT SECTION
2709          END-IF
2710      END-IF
2711      .
=====
```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 67

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 68

```

=====
2713      311-Control-Record SECTION.
2714      UNSTRING F-ES-2-256-TXT-256
2715          DELIMITED BY '''
2716      INTO WS-Temp-10-Chars-TXT
2717          WS-Temp-256-Chars-TXT
2718          WS-Dummy-TXT
2719      INSPECT WS-Temp-10-Chars-TXT REPLACING ALL ''' BY SPACE
2720 GC0712 IF WS-Temp-10-Chars-TXT(1:4) = 'line'
2721 GC0712     MOVE SPACES TO WS-Temp-10-Chars-TXT(1:4)
2722 GC0712 END-IF
2723     COMPUTE WS-I-SUB = NUMVAL(WS-Temp-10-Chars-TXT) - 1
2724 GC1010 IF UPPER-CASE(TRIM(WS-Temp-256-Chars-TXT,Trailing)) =
2725 GC1010     TRIM(WS-Main-Module-Name-TXT)
2726     MOVE WS-I-SUB TO WS-Curr-Line-NUM
2727     SET WS-RS-In-Main-Module-BOOL TO TRUE
2728     IF WS-Saved-Section-TXT NOT = SPACES
2729         MOVE WS-Saved-Section-TXT TO WS-Curr-Section-TXT
2730     END-IF
2731 ELSE
2732     SET WS-RS-In-Copybook-BOOL TO TRUE
2733     IF WS-Saved-Section-TXT = SPACES
2734         MOVE WS-Curr-Section-TXT TO WS-Saved-Section-TXT
2735     END-IF
2736     MOVE LENGTH(TRIM(WS-Temp-256-Chars-TXT,Trailing))
2737         TO WS-I-SUB
2738     MOVE 0 TO WS-J-SUB
2739     PERFORM UNTIL WS-Temp-256-Chars-TXT(WS-I-SUB:1) = '/'
2740         OR WS-I-SUB = 0
2741         SUBTRACT 1 FROM WS-I-SUB
2742         ADD 1 TO WS-J-SUB
2743     END-PERFORM
2744     UNSTRING WS-Temp-256-Chars-TXT((WS-I-SUB + 1):WS-J-SUB)
2745         DELIMITED BY ','
2746     INTO WS-Filename-TXT
2747         WS-Dummy-TXT
2748     MOVE '[' TO WS-CS-1-CHR
2749     MOVE WS-Filename-TXT TO WS-CS-2-14-TXT
2750     IF WS-CS-11-14-TXT NOT = SPACES
2751         MOVE '...' TO WS-CS-11-14-TXT
2752     END-IF
2753     MOVE ']' TO WS-CS-15-CHR
2754     END-IF
2755     MOVE SPACES TO F-Expanded-Src-REC *> Force another READ
2756     MOVE 256 TO WS-Src-SUB
2757     .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 68

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 69

```
=====
2759          312-Expanded-Src-Record SECTION.
2760 GC0314      IF F-Expanded-Src-REC(1:1) = SPACE
2761 GC0314          MOVE 2 TO WS-Src-SUB
2762 GC0314      ELSE
2763 GC0314          MOVE 1 TO WS-Src-SUB
2764 GC0314      END-IF
2765          IF WS-RS-In-Main-Module-BOOL
2766              ADD 1 To WS-Curr-Line-NUM
2767          END-IF
2768          .
=====
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 69

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 70

```

=====
2770          313-Check-For-Numeric-Token SECTION.
2771          MOVE WS-Token-Curr-TXT TO WS-Temp-32-Chars-1-TXT
2772          INSPECT WS-Temp-32-Chars-1-TXT
2773 GC0711          CONVERTING '0123456789' TO SPACES
2774 GC0711          IF WS-Temp-32-Chars-1-TXT = SPACES           *> Simple Unsigned Integer
2775          SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2776          EXIT SECTION
2777          END-IF
2778 GC0711          MOVE SPACES TO WS-Temp-32-Chars-2-TXT
2779 GC0711          WS-Temp-32-Chars-3-TXT
2780 GC0711          WS-Dummy-TXT
2781 GC0711          UNSTRING WS-Temp-32-Chars-1-TXT
2782 GC0711          DELIMITED BY 'e' OR 'E'
2783 GC0711          INTO WS-Temp-32-Chars-2-TXT
2784 GC0711          WS-Temp-32-Chars-3-TXT
2785 GC0711          WS-Dummy-TXT
2786 GC0711          IF WS-Dummy-TXT NOT = SPACES                 *> More than one 'E' - Not Numeric
2787 GC0711          EXIT SECTION
2788 GC0711          END-IF
2789 GC0711          IF WS-Temp-32-Chars-2-TXT(1:1) = '+' OR '-'
2790 GC0711          MOVE SPACE TO WS-Temp-32-Chars-2-TXT(1:1)
2791 GC0711          END-IF
2792 GC0711          IF WS-Temp-32-Chars-3-TXT(1:1) = '+' OR '-'
2793 GC0711          MOVE SPACE TO WS-Temp-32-Chars-3-TXT(1:1)
2794 GC0711          END-IF
2795          MOVE 0 TO WS-Tally-QTY
2796 GC0711          INSPECT WS-Temp-32-Chars-2-TXT
2797          TALLYING WS-Tally-QTY FOR ALL '.'
2798          IF WS-Tally-QTY = 1
2799 GC0711          INSPECT WS-Temp-32-Chars-2-TXT REPLACING ALL '.' BY SPACE
2800          END-IF
2801 GC0711          INSPECT WS-Temp-32-Chars-3-TXT
2802 GC0711          TALLYING WS-Tally-QTY FOR ALL '.'
2803 GC0711          IF WS-Tally-QTY = 1
2804 GC0711          INSPECT WS-Temp-32-Chars-3-TXT REPLACING ALL '.' BY SPACE
2805 GC0711          END-IF
2806 GC0711          IF WS-Temp-32-Chars-2-TXT = SPACES AND WS-Temp-32-Chars-3-TXT = SPACES
2807          SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2808          EXIT SECTION
2809          END-IF
2810          .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 70

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 71

```

=====
2812          320-IDENTIFICATION-DIVISION SECTION.
2813 GC0712    IF WS-TT-Token-Is-Argtype-BOOL
2814 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2815 GC0712    END-IF
2816 GC0710    MOVE 'N' TO WS-RS-Verb-Has-Been-Found-CHR
2817          IF WS-TT-Token-Is-Keyword-BOOL
2818          AND WS-Token-Curr-TXT = 'DIVISION'
2819          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2820          EXIT SECTION
2821          END-IF
2822 GC0712    IF WS-Token-Prev-TXT = 'PROGRAM-ID' OR 'FUNCTION-ID'
2823          MOVE SPACES TO WS-Token-Prev-TXT
2824          MOVE WS-Token-Curr-TXT TO WS-Curr-Prog-ID-TXT
2825 GC0712    IF WS-CPI-16-CHR NOT = SPACES
2826          MOVE '...' TO WS-CPI-13-15-TXT
2827          END-IF
2828          EXIT SECTION
2829          END-IF
2830          .
=====

```

```

=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 71

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 72

=====

```
2832      330-ENVIRONMENT-DIVISION SECTION.
2833 GC0712      IF WS-TT-Token-Is-Argtype-BOOL
2834 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2835 GC0712      END-IF
2836          IF WS-TT-Token-Is-Keyword-BOOL
2837      AND WS-Token-Curr-TXT = 'DIVISION'
2838          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2839      EXIT SECTION
2840      END-IF
2841          IF WS-TT-Token-Is-Keyword-BOOL
2842      AND WS-Token-Curr-TXT = 'SECTION'
2843          MOVE WS-Token-Prev-TXT TO WS-Curr-Section-TXT
2844      EXIT SECTION
2845      END-IF
2846          IF WS-TT-Token-Is-Identifier-BOOL
2847 GC0712          IF WS-Token-Prev-TXT = 'FUNCTION'
2848 GC0712              PERFORM 360-Release-Def
2849 GC0712          ELSE
2850 GC0712              PERFORM 361-Release-Ref
2851 GC0712          END-IF
2852      END-IF
2853 GC1213      IF WS-TT-Token-Is-Function-BOOL
2854 GC1213          PERFORM 361-Release-Ref
2855 GC1213      END-IF
2856      .
```

=====

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 72

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 73

```

=====
2858          340-DATA-DIVISION SECTION.
2859 GC0712      IF WS-TT-Token-Is-Argtype-BOOL
2860 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2861 GC0712      END-IF
2862          IF WS-TT-Token-Is-Keyword-BOOL
2863          AND WS-Token-Curr-TXT = 'DIVISION'
2864              MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2865          EXIT SECTION
2866      END-IF
2867          IF WS-TT-Token-Is-Keyword-BOOL
2868          AND WS-Token-Curr-TXT = 'SECTION'
2869              MOVE WS-Token-Prev-TXT TO WS-Curr-Section-TXT
2870          EXIT SECTION
2871      END-IF
2872          IF (WS-Token-Curr-TXT = 'PIC' OR 'PICTURE')
2873          AND (WS-TT-Token-Is-Keyword-BOOL)
2874              MOVE 'Y' TO WS-RS-Processing-PICTURE-CHR
2875          EXIT SECTION
2876      END-IF
2877 GC0710      IF WS-TT-Token-Is-Reserved-Wd-BOOL
2878 GC0710          AND WS-Token-Prev-TXT = 'LEVEL #'
2879 GC0710              MOVE SPACES TO WS-Token-Prev-TXT
2880 GC0710          EXIT SECTION
2881 GC0710      END-IF
2882          IF WS-TT-Token-Is-Identifier-BOOL
2883          EVALUATE WS-Token-Prev-TXT
2884              WHEN 'FD'
2885                  PERFORM 360-Release-Def
2886                  MOVE SPACES TO WS-Token-Prev-TXT
2887 GC1213          WHEN 'RD'
2888 GC1213              PERFORM 360-Release-Def
2889 GC1213              MOVE SPACES TO WS-Token-Prev-TXT
2890          WHEN 'SD'
2891              PERFORM 360-Release-Def
2892              MOVE SPACES TO WS-Token-Prev-TXT
2893          WHEN 'LEVEL #'
2894              PERFORM 360-Release-Def
2895              MOVE SPACES TO WS-Token-Prev-TXT
2896          WHEN 'INDEXED'
2897              PERFORM 360-Release-Def
2898              MOVE SPACES TO WS-Token-Prev-TXT
2899          WHEN 'USING'
2900              PERFORM 362-Release-Upd
2901              MOVE SPACES TO WS-Token-Prev-TXT
2902          WHEN 'INTO'
2903              PERFORM 362-Release-Upd
2904              MOVE SPACES TO WS-Token-Prev-TXT
2905          WHEN OTHER
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 73

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 74

```
=====
2906 GC1213          IF WS-Token-Curr-TXT NOT = 'SUM'
2907 GC1213          PERFORM 361-Release-Ref
2908 GC1213          END-IF
2909                END-EVALUATE
2910                EXIT SECTION
2911                END-IF
2912                .
=====
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 74

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 75

```

=====
2914      350-PROCEDURE-DIVISION SECTION.
2915          IF WS-Curr-Section-TXT NOT = 'PROCEDURE'
2916              MOVE 'PROCEDURE' TO WS-Curr-Section-TXT
2917          END-IF
2918 GC0710      IF WS-Token-Curr-Uc-TXT = 'PROGRAM'
2919 GC0710      AND WS-Token-Prev-TXT = 'END'
2920 GC0710          MOVE '?' TO WS-Curr-Division-TXT
2921 GC0710          EXIT SECTION
2922 GC0710      END-IF
2923          IF WS-TT-Token-Is-Keyword-BOOL
2924      AND WS-Token-Curr-TXT = 'DIVISION'
2925          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2926          EXIT SECTION
2927      END-IF
2928 GC0313      IF WS-TT-Token-Is-Identifier-BOOL
2929 GC0313      AND WS-Token-Prev-TXT = SPACES
2930 GC0313      AND WS-Curr-Verb-TXT = SPACES
2931 GC0313*> ----- Definition of a Paragraph or Section
2932 GC0313          PERFORM 360-Release-Def
2933 GC0313          MOVE SPACES TO WS-Token-Prev-TXT
2934 GC0313          EXIT SECTION
2935 GC0313      END-IF
2936          IF NOT WS-TT-Token-Is-Identifier-BOOL
2937              EXIT SECTION
2938          END-IF
2939          EVALUATE WS-Curr-Verb-TXT
2940      WHEN 'ACCEPT'
2941          PERFORM 351-ACCEPT
2942      WHEN 'ADD'
2943          PERFORM 351-ADD
2944      WHEN 'ALLOCATE'
2945          PERFORM 351-ALLOCATE
2946      WHEN 'CALL'
2947          PERFORM 351-CALL
2948      WHEN 'COMPUTE'
2949          PERFORM 351-COMPUTE
2950      WHEN 'DIVIDE'
2951          PERFORM 351-DIVIDE
2952      WHEN 'FREE'
2953          PERFORM 351-FREE
2954 GC1213      WHEN 'GENERATE'
2955 GC1213          PERFORM 351-GENERATE
2956      WHEN 'INITIALIZE'
2957          PERFORM 351-INITIALIZE
2958 GC1213      WHEN 'INITIATE'
2959 GC1213          PERFORM 351-GENERATE
2960      WHEN 'INSPECT'
2961          PERFORM 351-INSPECT
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 75

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 76

```
=====
2962          WHEN 'MOVE'
2963             PERFORM 351-MOVE
2964          WHEN 'MULTIPLY'
2965             PERFORM 351-MULTIPLY
2966          WHEN 'PERFORM'
2967             PERFORM 351-PERFORM
2968          WHEN 'SET'
2969             PERFORM 351-SET
2970          WHEN 'STRING'
2971             PERFORM 351-STRING
2972          WHEN 'SUBTRACT'
2973             PERFORM 351-SUBTRACT
2974 GC1213     WHEN 'TERMINATE'
2975 GC1213     PERFORM 351-GENERATE
2976          WHEN 'TRANSFORM'
2977             PERFORM 351-TRANSFORM
2978          WHEN 'UNSTRING'
2979             PERFORM 351-UNSTRING
2980          WHEN OTHER
2981             PERFORM 361-Release-Ref
2982          END-EVALUATE
2983          .
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 76

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 77

```

=====
2985      351-ACCEPT SECTION.
2986          EVALUATE WS-Token-Prev-TXT
2987          WHEN 'ACCEPT'
2988              PERFORM 362-Release-Upd
2989              MOVE SPACES TO WS-Token-Prev-TXT
2990          WHEN OTHER
2991              PERFORM 361-Release-Ref
2992          END-EVALUATE
2993          .
2994
2995      351-ADD SECTION.
2996          EVALUATE WS-Token-Prev-TXT
2997          WHEN 'GIVING'
2998              PERFORM 362-Release-Upd
2999          WHEN 'TO'
3000              PERFORM 362-Release-Upd
3001          WHEN OTHER
3002              PERFORM 361-Release-Ref
3003          END-EVALUATE
3004          .
3005
3006      351-ALLOCATE SECTION.
3007          EVALUATE WS-Token-Prev-TXT
3008          WHEN 'ALLOCATE'
3009              PERFORM 362-Release-Upd
3010              MOVE SPACES TO WS-Token-Prev-TXT
3011          WHEN 'RETURNING'
3012              PERFORM 362-Release-Upd
3013          WHEN OTHER
3014              PERFORM 361-Release-Ref
3015          END-EVALUATE
3016          .
3017
3018      351-CALL SECTION.
3019          EVALUATE WS-Token-Prev-TXT
3020          WHEN 'RETURNING'
3021              PERFORM 362-Release-Upd
3022          WHEN 'GIVING'
3023              PERFORM 362-Release-Upd
3024          WHEN OTHER
3025 GC1213      PERFORM 365-Release-Arg
3026          END-EVALUATE
3027          .
3028
3029      351-COMPUTE SECTION.
3030          EVALUATE WS-Token-Prev-TXT
3031          WHEN 'COMPUTE'
3032          PERFORM 362-Release-Upd
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 77

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 78

```

=====
3033          WHEN OTHER
3034              PERFORM 361-Release-Ref
3035          END-EVALUATE
3036          .
3037
3038          351-DIVIDE SECTION.
3039          EVALUATE WS-Token-Prev-TXT
3040          WHEN 'INTO'
3041              PERFORM 363-Set-Upd
3042              MOVE F-Sort-Work-REC TO WS-Held-Reference-TXT
3043          WHEN 'GIVING'
3044              IF WS-Held-Reference-TXT NOT = SPACES
3045                  MOVE WS-Held-Reference-TXT To F-Sort-Work-REC
3046                  MOVE SPACES          To WS-Held-Reference-TXT
3047                      F-SW-Ref-Flag-CHR
3048                  RELEASE F-Sort-Work-REC
3049              END-IF
3050              PERFORM 362-Release-Upd
3051          WHEN 'REMAINDER'
3052              PERFORM 362-Release-Upd
3053          WHEN OTHER
3054              PERFORM 361-Release-Ref
3055          END-EVALUATE
3056          .
3057
3058          351-FREE SECTION.
3059          PERFORM 362-Release-Upd
3060          .
3061
3062 GC1213 351-GENERATE SECTION.
3063 GC1213 PERFORM 362-Release-Upd
3064 GC1213 .
3065
3066          351-INITIALIZE SECTION.
3067          EVALUATE WS-Token-Prev-TXT
3068          WHEN 'INITIALIZE'
3069              PERFORM 362-Release-Upd
3070          WHEN 'REPLACING'
3071              PERFORM 361-Release-Ref
3072          END-EVALUATE
3073          .
3074
3075 GC1213 351-INITIATE SECTION.
3076 GC1213 PERFORM 362-Release-Upd
3077 GC1213 .
3078
3079          351-INSPECT SECTION.
3080          EVALUATE WS-Token-Prev-TXT
3081          WHEN 'INSPECT'
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 78

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

Line Statement

Page: 79

```

=====
3082          PERFORM 364-Set-Ref
3083          MOVE SPACES TO WS-Held-Reference-TXT
3084          MOVE SPACES TO WS-Token-Prev-TXT
3085          WHEN 'TALLYING'
3086          PERFORM 362-Release-Upd
3087          MOVE SPACES TO WS-Token-Prev-TXT
3088          WHEN 'REPLACING'
3089          IF WS-Held-Reference-TXT NOT = SPACES
3090             MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3091             MOVE SPACES          TO WS-Held-Reference-TXT
3092             MOVE '*'            TO F-SW-Ref-Flag-CHR
3093             RELEASE F-Sort-Work-REC
3094          END-IF
3095          MOVE SPACES TO WS-Token-Prev-TXT
3096          WHEN 'CONVERTING'
3097          IF WS-Held-Reference-TXT NOT = SPACES
3098             MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3099             MOVE SPACES          TO WS-Held-Reference-TXT
3100             MOVE '*'            TO F-SW-Ref-Flag-CHR
3101             RELEASE F-Sort-Work-REC
3102          END-IF
3103          MOVE SPACES TO WS-Token-Prev-TXT
3104          WHEN OTHER
3105             PERFORM 361-Release-Ref
3106          END-EVALUATE
3107          .
3108
3109          351-MOVE SECTION.
3110             EVALUATE WS-Token-Prev-TXT
3111             WHEN 'TO'
3112                PERFORM 362-Release-Upd
3113             WHEN OTHER
3114                PERFORM 361-Release-Ref
3115             END-EVALUATE
3116             .
3117
3118          351-MULTIPLY SECTION.
3119             EVALUATE WS-Token-Prev-TXT
3120             WHEN 'BY'
3121                PERFORM 363-Set-Upd
3122                MOVE F-Sort-Work-REC TO WS-Held-Reference-TXT
3123             WHEN 'GIVING'
3124                MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3125                MOVE SPACES          TO WS-Held-Reference-TXT
3126                F-SW-Ref-Flag-CHR
3127                RELEASE F-Sort-Work-REC
3128                PERFORM 362-Release-Upd
3129             WHEN OTHER
3130                PERFORM 361-Release-Ref
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 79

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 80

```

=====
3131         END-EVALUATE
3132         .
3133
3134     351-PERFORM SECTION.
3135         EVALUATE WS-Token-Prev-TXT
3136         WHEN 'VARYING'
3137             PERFORM 362-Release-Upd
3138             MOVE SPACES TO WS-Token-Prev-TXT
3139         WHEN 'AFTER'
3140             PERFORM 362-Release-Upd
3141             MOVE SPACES TO WS-Token-Prev-TXT
3142         WHEN OTHER
3143             PERFORM 361-Release-Ref
3144         END-EVALUATE
3145         .
3146
3147     351-SET SECTION.
3148         EVALUATE WS-Token-Prev-TXT
3149         WHEN 'SET'
3150             PERFORM 362-Release-Upd
3151         WHEN OTHER
3152             PERFORM 361-Release-Ref
3153         END-EVALUATE
3154         .
3155
3156     351-STRING SECTION.
3157         EVALUATE WS-Token-Prev-TXT
3158         WHEN 'INTO'
3159             PERFORM 362-Release-Upd
3160         WHEN 'POINTER'
3161             PERFORM 362-Release-Upd
3162         WHEN OTHER
3163             PERFORM 361-Release-Ref
3164         END-EVALUATE
3165         .
3166
3167     351-SUBTRACT SECTION.
3168         EVALUATE WS-Token-Prev-TXT
3169         WHEN 'GIVING'
3170             PERFORM 362-Release-Upd
3171         WHEN 'FROM'
3172             PERFORM 362-Release-Upd
3173         WHEN OTHER
3174             PERFORM 361-Release-Ref
3175         END-EVALUATE
3176         .
3177
3178 GC1213 351-TERMINATE SECTION.
3179 GC1213     PERFORM 362-Release-Upd
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 80

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 81

```

=====
3180 GC1213      .
3181
3182      351-TRANSFORM SECTION.
3183          EVALUATE WS-Token-Prev-TXT
3184          WHEN 'TRANSFORM'
3185              PERFORM 362-Release-Upd
3186              MOVE SPACES TO WS-Token-Prev-TXT
3187          WHEN OTHER
3188              PERFORM 361-Release-Ref
3189          END-EVALUATE
3190      .
3191
3192      351-UNSTRING SECTION.
3193          EVALUATE WS-Token-Prev-TXT
3194          WHEN 'INTO'
3195              PERFORM 362-Release-Upd
3196          WHEN 'DELIMITER'
3197              PERFORM 362-Release-Upd
3198          WHEN 'COUNT'
3199              PERFORM 362-Release-Upd
3200          WHEN 'POINTER'
3201              PERFORM 362-Release-Upd
3202          WHEN 'TALLYING'
3203              PERFORM 362-Release-Upd
3204          WHEN OTHER
3205              PERFORM 361-Release-Ref
3206          END-EVALUATE
3207      .
3208
3209      360-Release-Def SECTION.
3210          MOVE SPACES                TO F-Sort-Work-REC
3211          MOVE WS-Curr-Prog-ID-TXT    TO F-SW-Prog-ID-TXT
3212          MOVE WS-Token-Curr-Uc-TXT   TO F-SW-Token-Uc-TXT
3213          MOVE WS-Token-Curr-TXT      TO F-SW-Token-TXT
3214          MOVE WS-Curr-Section-TXT    TO F-SW-Section-TXT
3215          MOVE WS-Curr-Line-NUM       TO F-SW-Def-Line-NUM
3216          MOVE 0                      TO F-SW-Ref-Line-NUM
3217          RELEASE F-Sort-Work-REC
3218      .
3219
3220      361-Release-Ref SECTION.
3221          PERFORM 364-Set-Ref
3222          RELEASE F-Sort-Work-REC
3223      .
3224
3225      362-Release-Upd SECTION.
3226          PERFORM 363-Set-Upd
3227          RELEASE F-Sort-Work-REC
3228      .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 81

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 82

```

=====
3229
3230      363-Set-Upd SECTION.
3231      MOVE SPACES              TO F-Sort-Work-REC
3232      MOVE WS-Curr-Prog-ID-TXT TO F-SW-Prog-ID-TXT
3233      MOVE WS-Token-Curr-Uc-TXT TO F-SW-Token-Uc-TXT
3234      MOVE WS-Token-Curr-TXT   TO F-SW-Token-TXT
3235      MOVE WS-Curr-Section-TXT TO F-SW-Section-TXT
3236      MOVE WS-Curr-Line-NUM    TO F-SW-Ref-Line-NUM
3237      MOVE '*'                 TO F-SW-Ref-Flag-CHR
3238      .
3239
3240      364-Set-Ref SECTION.
3241      MOVE SPACES              TO F-Sort-Work-REC
3242      MOVE WS-Curr-Prog-ID-TXT TO F-SW-Prog-ID-TXT
3243      MOVE WS-Token-Curr-Uc-TXT TO F-SW-Token-Uc-TXT
3244      MOVE WS-Token-Curr-TXT   TO F-SW-Token-TXT
3245      MOVE WS-Curr-Section-TXT TO F-SW-Section-TXT
3246      MOVE WS-Curr-Line-NUM    TO F-SW-Ref-Line-NUM
3247      .
3248
3249 GC1213 365-Release-Arg SECTION.
3250 GC1213 PERFORM 366-Set-Arg
3251 GC1213 RELEASE F-Sort-Work-REC
3252 GC1213 .
3253
3254 GC1213 366-Set-Arg SECTION.
3255 GC1213 MOVE SPACES              TO F-Sort-Work-REC
3256 GC1213 MOVE WS-Curr-Prog-ID-TXT TO F-SW-Prog-ID-TXT
3257 GC1213 MOVE WS-Token-Curr-Uc-TXT TO F-SW-Token-Uc-TXT
3258 GC1213 MOVE WS-Token-Curr-TXT   TO F-SW-Token-TXT
3259 GC1213 MOVE WS-Curr-Section-TXT TO F-SW-Section-TXT
3260 GC1213 MOVE WS-Curr-Line-NUM    TO F-SW-Ref-Line-NUM
3261 GC1213 MOVE 'C'                 TO F-SW-Ref-Flag-CHR
3262 GC1213 .
3263
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 82

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 83

```

=====
3265      400-Produce-Xref-Listing SECTION.
3266      MOVE SPACES          TO WS-Xref-Detail-Line-TXT
3267                                     WS-Group-Indicators-TXT
3268      MOVE 0                TO WS-I-SUB
3269                                     WS-Lines-Left-NUM
3270 GC0710  MOVE 'N'          TO WS-RS-Duplicate-CHR
3271      PERFORM FOREVER
3272      RETURN F-Sort-Work-FILE AT END
3273 GC1213  IF WS-Xref-Detail-Line-TXT NOT = SPACES
3274 GC1213      PERFORM 410-Generate-Report-Line
3275 GC1213  END-IF
3276 GC1213  MOVE SPACES TO WS-Xref-Detail-Line-TXT
3277 GC1213  PERFORM 410-Generate-Report-Line
3278 GC1213  UNTIL WS-Lines-Left-NUM = 0
3279 GC1213  MOVE 'Y' TO WS-Suppress-FF-CHR
3280 GC1213  PERFORM 420-Generate-Xref-Footer
3281      EXIT PERFORM
3282  END-RETURN
3283  IF F-SW-Prog-ID-TXT NOT = WS-GI-Prog-ID-TXT
3284  OR F-SW-Token-Uc-TXT NOT = WS-GI-Token-TXT
3285 GC0710  MOVE 'N' TO WS-RS-Duplicate-CHR
3286      IF WS-Xref-Detail-Line-TXT NOT = SPACES
3287      PERFORM 410-Generate-Report-Line
3288  END-IF
3289  IF F-SW-Prog-ID-TXT NOT = WS-GI-Prog-ID-TXT
3290 GC1213  MOVE SPACES TO WS-Xref-Detail-Line-TXT
3291 GC1213  PERFORM 410-Generate-Report-Line
3292 GC1213  UNTIL WS-Lines-Left-NUM = 0
3293  END-IF
3294  MOVE F-SW-Prog-ID-TXT TO WS-GI-Prog-ID-TXT
3295  MOVE F-SW-Token-Uc-TXT TO WS-GI-Token-TXT
3296  END-IF
3297 GC0710  IF F-SW-Token-Uc-TXT = WS-GI-Token-TXT
3298 GC0710  AND F-SW-Def-Line-NUM NOT = SPACES
3299 GC0710  AND WS-Xref-Detail-Line-TXT NOT = SPACES
3300 GC0710  MOVE 'Y' TO WS-RS-Duplicate-CHR
3301 GC0710  PERFORM 410-Generate-Report-Line
3302 GC0710  MOVE 0 TO WS-I-SUB
3303 GC0710  MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3304 GC0710  MOVE ' (Duplicate Definition)' TO WS-XDL-Token-TXT
3305 GC0710  MOVE F-SW-Section-TXT TO WS-XDL-Section-TXT
3306 GC0710  MOVE F-SW-Def-Line-NUM TO WS-XDL-Def-Line-NUM
3307 GC0710  EXIT PERFORM CYCLE
3308 GC0710  END-IF
3309 GC0710  IF F-SW-Token-Uc-TXT = WS-GI-Token-TXT
3310 GC0710  AND F-SW-Def-Line-NUM = SPACES
3311 GC0710  AND WS-RS-Duplicate-CHR = 'Y'
3312 GC0710  MOVE 'N' TO WS-RS-Duplicate-CHR
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 83

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 84

```

=====
3313 GC0710          PERFORM 410-Generate-Report-Line
3314 GC0710          MOVE 0 TO WS-I-SUB
3315 GC0710          MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3316 GC0710          MOVE ' (Duplicate References)' TO WS-XDL-Token-TXT
3317 GC0710          END-IF
3318                IF WS-Xref-Detail-Line-TXT = SPACES
3319                    MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3320                    MOVE F-SW-Token-TXT TO WS-XDL-Token-TXT
3321                    MOVE F-SW-Section-TXT TO WS-XDL-Section-TXT
3322                    IF F-SW-Def-Line-NUM NOT = SPACES
3323                        MOVE F-SW-Def-Line-NUM TO WS-XDL-Def-Line-NUM
3324                    END-IF
3325                END-IF
3326                IF F-SW-Reference-TXT > '000000'
3327                    ADD 1 TO WS-I-SUB
3328                    IF WS-I-SUB > WS-Xref-Lines-Per-Rec-NUM
3329                        PERFORM 410-Generate-Report-Line
3330                        MOVE 1 TO WS-I-SUB
3331                    END-IF
3332                    MOVE F-SW-Ref-Line-NUM
3333                        TO WS-XDL-Ref-Line-NUM (WS-I-SUB)
3334                    MOVE F-SW-Ref-Flag-CHR
3335                        TO WS-XDL-Ref-Flag-CHR (WS-I-SUB)
3336                END-IF
3337            END-PERFORM
3338            IF WS-Xref-Detail-Line-TXT NOT = SPACES
3339                PERFORM 410-Generate-Report-Line
3340            END-IF
3341            .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 84

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 85

```

=====
3343      410-Generate-Report-Line SECTION.
3344      IF WS-Lines-Left-NUM < 1
3345 GC1213      PERFORM 420-Generate-Xref-Footer
3346 GC1213      ADD 1          TO WS-Page-NUM
3347 GC1213      MOVE 'Page:'      TO WS-PN-Literal-TXT
3348 GC1213      MOVE WS-Page-NUM TO WS-PN-Page-NUM
3349 GC1213      CALL 'C$JUSTIFY' USING WS-PN-Page-NUM, 'Left'
3350 GC1213      CALL 'C$JUSTIFY' USING WS-Page-No-TXT, 'Right'
3351 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
3352 GC1213          MOVE WS-Version-TXT
3353 GC1213              TO F-Listing-135-REC
3354 GC1213          MOVE 'Cross-Reference Listing'
3355 GC1213              TO F-Listing-135-REC(25:23)
3356 GC1213          MOVE WS-Formatted-DT
3357 GC1213              TO F-Listing-135-REC(126:10)
3358 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #1
3359 GC1213          MOVE WS-Program-Path-TXT
3360 GC1213              TO F-Listing-135-REC
3361 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #2
3362 GC1213          MOVE 'PROGRAM-ID      Identifier/Register/Function' &
3363 GC1213              '      Defn Where Defined References'
3364 GC1213              TO F-Listing-135-REC
3365 GC1213          MOVE WS-Page-No-TXT
3366 GC1213              TO F-Listing-135-REC(126:10)
3367 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #3
3368 GC1213          MOVE ALL '=' TO F-Listing-135-REC
3369 GC1213          MOVE SPACE TO F-Listing-135-REC(16:1)
3370 GC1213              F-Listing-135-REC(49:1)
3371 GC1213              F-Listing-135-REC(56:1)
3372 GC1213              F-Listing-135-REC(72:1)
3373 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #4
3374 GC1213      ELSE *> PORTRAIT
3375 GC1213          MOVE WS-Version-TXT
3376 GC1213              TO F-Listing-96-REC
3377 GC1213          MOVE 'Cross-Reference Listing'
3378 GC1213              TO F-Listing-96-REC(25:23)
3379 GC1213          MOVE WS-Formatted-DT
3380 GC1213              TO F-Listing-96-REC(87:10)
3381 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #1
3382 GC1213          MOVE WS-Program-Path-TXT(40:96)
3383 GC1213              TO F-Listing-96-REC
3384 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #2
3385 GC1213          MOVE 'PROGRAM-ID      Identifier/Register/Function' &
3386 GC1213              '      Defn Where Defined References'
3387 GC1213              TO F-Listing-96-REC
3388 GC1213          MOVE WS-Page-No-TXT
3389 GC1213              TO F-Listing-96-REC(87:10)
3390 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #3
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 85

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement Page: 86

```

=====
3391 GC1213          MOVE ALL '=' TO F-Listing-96-REC
3392 GC1213          MOVE SPACE TO F-Listing-96-REC(16:1)
3393 GC1213          F-Listing-96-REC(49:1)
3394 GC1213          F-Listing-96-REC(56:1)
3395 GC1213          F-Listing-96-REC(72:1)
3396 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #4
3397 GC1213          END-IF
3398 GC1213          COMPUTE WS-Lines-Left-NUM = WS-Lines-Per-Page-NUM - 4
3399                END-IF
3400 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3401 GC1213              WRITE F-Listing-135-REC FROM WS-Xref-Detail-Line-TXT
3402 GC1213              BEFORE 1
3403 GC1213          ELSE                *> PORTRAIT
3404 GC1213              WRITE F-Listing-96-REC FROM WS-Xref-Detail-Line-TXT
3405 GC1213              BEFORE 1
3406 GC1213          END-IF
3407                MOVE SPACES TO WS-Xref-Detail-Line-TXT
3408                MOVE 0 TO WS-I-SUB
3409                SUBTRACT 1 FROM WS-Lines-Left-NUM
3410                .
3411 GC1213 420-Generate-Xref-Footer SECTION.
3412 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3413 GC1213              WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Footer Line #1
3414 GC1213              MOVE ALL '='
3415 GC1213                  TO F-Listing-135-REC
3416 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #2
3417 GC1213              MOVE WS-Copyright-TXT
3418 GC1213                  TO F-Listing-135-REC
3419 GC1213              MOVE WS-Page-No-TXT
3420 GC1213                  TO F-Listing-135-REC(126:10)
3421 GC1213              IF WS-Suppress-FF-CHR = 'Y'
3422 GC1213                  WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #3
3423 GC1213              ELSE
3424 GC1213                  WRITE F-Listing-135-REC BEFORE PAGE *> Footer Line #3
3425 GC1213                  WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Spaces After FF Charac
3426 GC1213                  ter
3427 GC1213              END-IF
3428 GC1213          ELSE                *> PORTRAIT
3429 GC1213              WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Footer Line #1
3430 GC1213              MOVE ALL '='
3431 GC1213                  TO F-Listing-96-REC
3432 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #2
3433 GC1213              MOVE WS-Copyright-TXT
3434 GC1213                  TO F-Listing-96-REC
3435 GC1213              MOVE WS-Page-No-TXT
3436 GC1213                  TO F-Listing-96-REC(87:10)
3437 GC1213              IF WS-Suppress-FF-CHR = 'Y'
3438 GC1213                  WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #3
3439 GC1213              ELSE
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 86

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 87

```
=====
3439 GC1213          WRITE F-Listing-96-REC BEFORE PAGE *> Footer Line #3
3440 GC1213          WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Spaces After FF Charact
er
3441 GC1213          END-IF
3442 GC1213          END-IF
3443 GC1213          .
=====
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 87

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 88

=====

```
3445      500-Produce-Source-Listing SECTION.
3446      OPEN INPUT F-Original-Src-FILE
3447              F-Expanded-Src-FILE
3448      MOVE 0 TO WS-Src-Line-NUM
3449      PERFORM FOREVER
3450              READ F-Expanded-Src-FILE AT END
3451 GC1213      MOVE SPACES TO WS-Src-Detail-Line-TXT
3452 GC1213      PERFORM 530-Generate-Source-Line
3453 GC1213      UNTIL WS-Lines-Left-NUM = 0
3454      EXIT PERFORM
3455      END-READ
3456 GC0712      IF F-ES-1-7-TXT NOT = '#DEFLIT'
3457 GC0712      IF F-ES-1-CHR = '#'
3458 GC0712      PERFORM 510-Control-Record
3459 GC0712      ELSE
3460 GC0712      PERFORM 520-Expanded-Src-Record
3461 GC0712      END-IF
3462 GC0712      END-IF
3463      END-PERFORM
3464      CLOSE F-Original-Src-FILE
3465              F-Expanded-Src-FILE
3466      .
```

=====

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 88

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 89

```

=====
3468      510-Control-Record SECTION.
3469      UNSTRING F-ES-2-256-TXT-256
3470          DELIMITED BY '''
3471      INTO WS-Temp-10-Chars-TXT
3472          WS-Temp-256-Chars-TXT
3473          WS-Dummy-TXT
3474 GC1010  IF UPPER-CASE(TRIM(WS-Temp-256-Chars-TXT,Trailing)) =
3475 GC1010  TRIM(WS-Main-Module-Name-TXT) *> Main Pgm
3476          SET WS-RS-In-Main-Module-BOOL TO TRUE
3477          IF WS-Src-Line-NUM > 0
3478              READ F-Expanded-Src-FILE END-READ
3479          END-IF
3480      ELSE *> COPY
3481          SET WS-RS-In-Copybook-BOOL TO TRUE
3482      END-IF
3483      .
=====

```

```

=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 89

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 90

```

=====
3485      520-Expanded-Src-Record SECTION.
3486      IF WS-RS-In-Main-Module-BOOL
3487          ADD 1 To WS-Curr-Line-NUM
3488 GC0712      READ F-Original-Src-FILE AT END CONTINUE END-READ
3489          ADD 1 TO WS-Src-Line-NUM
3490          MOVE SPACES TO WS-Src-Detail-Line-TXT
3491          MOVE WS-Src-Line-NUM TO WS-SDL-Line-NUM
3492 GC1213      MOVE F-Original-Src-REC TO WS-SDL-Statement-TXT
3493 GC0712      MOVE LOWER-CASE(TRIM(F-OS-8-72-TXT,LEADING))
3494 GC0712          TO WS-Temp-65-Chars-TXT
3495 GC0712      INSPECT WS-Temp-65-Chars-TXT REPLACING ALL '.' BY SPACE
3496 GC0712      EVALUATE TRUE
3497 GC0712          WHEN F-OS-7-CHR = '/'
3498 GC1213          MOVE SPACES TO WS-Src-Detail-Line-TXT
3499 GC1213          PERFORM 530-Generate-Source-Line
3500 GC1213              UNTIL WS-Lines-Left-NUM = 0
3501 GC0712          WHEN WS-Temp-65-Chars-TXT = "eject"
3502 GC1213          MOVE SPACES TO WS-Src-Detail-Line-TXT
3503 GC1213          PERFORM 530-Generate-Source-Line
3504 GC1213              UNTIL WS-Lines-Left-NUM = 0
3505 GC0712          EXIT SECTION
3506 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip1"
3507 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3508 GC0712          PERFORM 530-Generate-Source-Line
3509 GC0712          EXIT SECTION
3510 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip2"
3511 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3512 GC0712          PERFORM 530-Generate-Source-Line 2 TIMES
3513 GC0712          EXIT SECTION
3514 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip3"
3515 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3516 GC0712          PERFORM 530-Generate-Source-Line 3 TIMES
3517 GC0712          EXIT SECTION
3518 GC0712      END-EVALUATE
3519      PERFORM 530-Generate-Source-Line
3520      ELSE
3521      IF F-Expanded-Src-REC NOT = SPACES
3522          MOVE SPACES TO WS-Src-Detail-Line-TXT
3523 GC1213      MOVE F-Expanded-Src-REC
3524          TO WS-SDL-Statement-TXT
3525 GC0712      MOVE LOWER-CASE(TRIM(F-OS-8-72-TXT,LEADING))
3526 GC0712          TO WS-Temp-65-Chars-TXT
3527 GC0712      INSPECT WS-Temp-65-Chars-TXT
3528 GC0712          REPLACING ALL '.' BY SPACE
3529 GC0712      EVALUATE TRUE
3530 GC0712          WHEN WS-Temp-65-Chars-TXT = "eject"
3531 GC0712          MOVE 0 TO WS-Lines-Left-NUM
3532 GC0712          EXIT SECTION
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 90

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 91

```

=====
3533 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip1"
3534 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3535 GC0712          PERFORM 530-Generate-Source-Line
3536 GC0712          EXIT SECTION
3537 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip2"
3538 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3539 GC0712          PERFORM 530-Generate-Source-Line 2 TIMES
3540 GC0712          EXIT SECTION
3541 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip3"
3542 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3543 GC0712          PERFORM 530-Generate-Source-Line 3 TIMES
3544 GC0712          EXIT SECTION
3545 GC0712          END-EVALUATE
3546                  PERFORM 530-Generate-Source-Line
3547                  END-IF
3548          END-IF
3549          .
=====

```

```

=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

```

Page: 91

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 92

```

=====
3551          530-Generate-Source-Line SECTION.
3552 GC1213      MOVE 1 TO WS-Src-Lines-NUM
3553 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
3554 GC1213          IF WS-SDL-Statement-TXT(129:128) > SPACES
3555 GC1213              ADD 1 TO WS-Src-Lines-NUM
3556 GC1213          END-IF
3557 GC1213      ELSE
3558 GC1213          IF WS-SDL-Statement-TXT(90:167) > SPACES
3559 GC1213              ADD 1 TO WS-Src-Lines-NUM
3560 GC1213          IF WS-SDL-Statement-TXT(179:78) > SPACES
3561 GC1213              ADD 1 TO WS-Src-Lines-NUM
3562 GC1213          END-IF
3563 GC1213      END-IF
3564 GC1213      END-IF
3565 GC1213      IF WS-Lines-Left-NUM < WS-Src-Lines-NUM
3566 GC1213          IF WS-Page-Num > 0 *> Don't print footer before page 1
3567 GC1213              IF L-Listing-CD = 1 *> LANDSCAPE
3568 GC1213                  IF WS-Src-Lines-NUM = 2
3569 GC1213                      WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Blank Line
3570 GC1213                  END-IF
3571 GC1213                      WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Footer Line #1
3572 GC1213                      MOVE ALL '='
3573 GC1213                          TO F-Listing-135-REC
3574 GC1213                      WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #2
3575 GC1213                      MOVE WS-Copyright-TXT
3576 GC1213                          TO F-Listing-135-REC
3577 GC1213                      MOVE WS-Page-No-TXT
3578 GC1213                          TO F-Listing-135-REC(126:10)
3579 GC1213                      WRITE F-Listing-135-REC BEFORE PAGE *> Footer Line #3
3580 GC1213                      WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Spaces After FF Ch
aracter
3581 GC1213      ELSE
3582 GC1213          EVALUATE WS-Src-Lines-NUM
3583 GC1213              WHEN 1 *> Need no extra blank lines
3584 GC1213                  CONTINUE
3585 GC1213              WHEN 2 *> Need 1 extra blank line
3586 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3587 GC1213              WHEN 3 *> Need 2 extra blank lines
3588 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3589 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3590 GC1213              END-EVALUATE
3591 GC1213          WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Footer Line #1
3592 GC1213          MOVE ALL '='
3593 GC1213              TO F-Listing-96-REC
3594 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #2
3595 GC1213          MOVE WS-Copyright-TXT
3596 GC1213              TO F-Listing-96-REC
3597 GC1213          MOVE WS-Page-No-TXT
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 92

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 93

```

=====
3598 GC1213          TO F-Listing-96-REC(87:10)
3599 GC1213          WRITE F-Listing-96-REC BEFORE PAGE *> Footer Line #3
3600 GC1213          WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Spaces After FF Cha
      racter
3601 GC1213          END-IF
3602 GC1213          END-IF
3603 GC1213          ADD 1          TO WS-Page-NUM
3604 GC1213          MOVE 'Page:'    TO WS-PN-Literal-TXT
3605 GC1213          MOVE WS-Page-NUM TO WS-PN-Page-NUM
3606 GC1213          CALL 'C$JUSTIFY' USING WS-PN-Page-NUM, 'Left'
3607 GC1213          CALL 'C$JUSTIFY' USING WS-Page-No-TXT, 'Right'
3608 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3609 GC1213             MOVE WS-Version-TXT
3610 GC1213             TO F-Listing-135-REC
3611 GC1213             MOVE 'Source Listing'
3612 GC1213             TO F-Listing-135-REC(25:14)
3613 GC1213             MOVE WS-Formatted-DT
3614 GC1213             TO F-Listing-135-REC(126:10)
3615 GC1213             WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #1
3616 GC1213             MOVE WS-Program-Path-TXT
3617 GC1213             TO F-Listing-135-REC
3618 GC1213             WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #2
3619 GC1213             MOVE 'Line Statement'
3620 GC1213             TO F-Listing-135-REC
3621 GC1213             MOVE WS-Page-No-TXT
3622 GC1213             TO F-Listing-135-REC(126:10)
3623 GC1213             WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #3
3624 GC1213             MOVE WS-Src-Dashes-TXT
3625 GC1213             TO F-Listing-135-REC
3626 GC1213             WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #4
3627 GC1213          ELSE          *> PORTRAIT
3628 GC1213             MOVE WS-Version-TXT
3629 GC1213             TO F-Listing-96-REC
3630 GC1213             MOVE 'Source Listing'
3631 GC1213             TO F-Listing-96-REC(25:14)
3632 GC1213             MOVE WS-Formatted-DT
3633 GC1213             TO F-Listing-96-REC(87:10)
3634 GC1213             WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #1
3635 GC1213             MOVE WS-Program-Path-TXT(40:96)
3636 GC1213             TO F-Listing-96-REC
3637 GC1213             WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #2
3638 GC1213             MOVE 'Line Statement'
3639 GC1213             TO F-Listing-96-REC
3640 GC1213             MOVE WS-Page-No-TXT
3641 GC1213             TO F-Listing-96-REC(87:10)
3642 GC1213             WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #3
3643 GC1213             MOVE WS-Src-Dashes-TXT
3644 GC1213             TO F-Listing-96-REC
3645 GC1213             WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #4
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 93

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 94

```

=====
3646 GC1213      END-IF
3647 GC1213      COMPUTE WS-Lines-Left-NUM = WS-Lines-Per-Page-NUM - 4
3648 GC1213      END-IF
3649 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
3650 GC1213      EVALUATE WS-Src-Lines-NUM
3651 GC1213      WHEN 1
3652 GC1213          MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3653 GC1213          WRITE F-Listing-96-REC BEFORE 1
3654 GC1213          SUBTRACT 1 FROM WS-Lines-Left-NUM
3655 GC1213      WHEN 2
3656 GC1213          MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3657 GC1213          MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3658 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Prints chars 1-128 of stmtnt
3659 GC1213          MOVE SPACES TO WS-Src-Detail-Line-TXT
3660 GC1213          MOVE WS-Src-Hold-TXT(129:128) TO WS-SDL-Statement-TXT
3661 GC1213          MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3662 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Prints chars 129-256 of stmtnt
3663 GC1213          SUBTRACT 2 FROM WS-Lines-Left-NUM
3664 GC1213      END-EVALUATE
3665 GC1213      ELSE          *> PORTRAIT
3666 GC1213          EVALUATE WS-Src-Lines-NUM
3667 GC1213          WHEN 1 *> Print only chars 1-89 of stmtnt
3668 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3669 GC1213                  BEFORE 1
3670 GC1213              SUBTRACT 1 FROM WS-Lines-Left-NUM
3671 GC1213          WHEN 2 *> Print only chars 1-89 and 90-178 of text
3672 GC1213              MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3673 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3674 GC1213                  BEFORE 1
3675 GC1213              MOVE SPACES TO WS-Src-Detail-Line-TXT
3676 GC1213              MOVE WS-Src-Hold-TXT(90:89) TO WS-SDL-Statement-TXT
3677 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3678 GC1213                  BEFORE 1
3679 GC1213              SUBTRACT 2 FROM WS-Lines-Left-NUM
3680 GC1213          WHEN 3 *> Print chars 1-89, 90-178 and 179-256 of stmtnt
3681 GC1213              MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3682 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3683 GC1213                  BEFORE 1
3684 GC1213              MOVE SPACES TO WS-Src-Detail-Line-TXT
3685 GC1213              MOVE WS-Src-Hold-TXT(90:89) TO WS-SDL-Statement-TXT
3686 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3687 GC1213                  BEFORE 1
3688 GC1213              MOVE SPACES TO WS-Src-Detail-Line-TXT
3689 GC1213              MOVE WS-Src-Hold-TXT(179:78) TO WS-SDL-Statement-TXT
3690 GC1213              WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3691 GC1213                  BEFORE 1
3692 GC1213              SUBTRACT 3 FROM WS-Lines-Left-NUM
3693 GC1213      END-EVALUATE
3694 GC1213      END-IF
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 94

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

Line Statement

Page: 95

```
=====
3695          MOVE SPACES TO WS-Src-Detail-Line-TXT
3696          .
3697
3698          END PROGRAM LISTING.
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 95

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 96
CHECKSRC	000-Main	1321	PROCEDURE		
CHECKSRC	L-A1-CHR	1311	LINKAGE	1323 1335 1338 1345	
CHECKSRC	L-A2-IDENT-DIVISION-BOOL	1316	LINKAGE	1367*	
CHECKSRC	L-A2-LINKAGE-SECTION-BOOL	1315	LINKAGE	1361*	
CHECKSRC	L-A2-Nothing-Special-BOOL	1317	LINKAGE	1322*	
CHECKSRC	L-Argument-1-TXT	1310	LINKAGE	1319	
CHECKSRC	L-Argument-2-CHR	1314	LINKAGE	1320	
CHECKSRC	WS-Compressed-Src-TXT	1297	WORKING-STORAGE	1332* 1355 1359 1365	
CHECKSRC	WS-CS-CHR	1298	WORKING-STORAGE	1339* 1345* 1354 1358 1364	
CHECKSRC	WS-I-SUB	1306	WORKING-STORAGE	1333* 1334 1335 1338 1345 1351* 1352 1354 1355 1358 1358 1359 1364 1364 1365	
CHECKSRC	WS-J-SUB	1308	WORKING-STORAGE	1331* 1337* 1339 1344* 1345	
CHECKSRC	WS-RS-Found-SPACE-CHR	1302	WORKING-STORAGE		
CHECKSRC	WS-RS-Not-Skipping-SPACE-BOOL	1304	WORKING-STORAGE	1330* 1336 1343*	
CHECKSRC	WS-RS-Skipping-SPACE-BOOL	1303	WORKING-STORAGE	1340*	
CHECKSRC	WS-Runtime-Switches-TXT	1301	WORKING-STORAGE		

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 97
GCic	000-File-Error	661	PROCEDURE		
GCic	000-Main	682	PROCEDURE		
GCic	100-Initialization	706	PROCEDURE	683	
GCic	200-Let-User-Set-Switches	819	PROCEDURE	686	
GCic	210-Run-Compiler	910	PROCEDURE	687	
GCic	220-Make-Listing	1046	PROCEDURE	691	
GCic	230-Run-Program	1077	PROCEDURE	695	
GCic	240-Find-LINKAGE-SECTION	1179	PROCEDURE	753	
GCic	250-Autoload-Listing	1218	PROCEDURE	697	1037 1071
GCic	900-Terminate	1264	PROCEDURE	699	747 890
				1038	1172
GCic	COB-COLOR-BLACK	185	[screenio]	446	451 541
				551	561 566
				576	583 598
				613	629 636
				643	
GCic	COB-COLOR-BLUE	185	[screenio]	529	
GCic	COB-COLOR-CYAN	185	[screenio]	542	
GCic	COB-COLOR-GREEN	185	[screenio]	452	567 614
				630	
GCic	COB-COLOR-MAGENTA	185	[screenio]		
GCic	COB-COLOR-RED	185	[screenio]	535	599
GCic	COB-COLOR-WHITE	185	[screenio]	447	530 536
				552	562 577
				584	637 644
GCic	COB-COLOR-YELLOW	185	[screenio]		
GCic	COB-SCR-ESC	185	[screenio]	889	
GCic	COB-SCR-F1	185	[screenio]	836	
GCic	COB-SCR-F10	185	[screenio]		
GCic	COB-SCR-F11	185	[screenio]		
GCic	COB-SCR-F12	185	[screenio]	892	
GCic	COB-SCR-F13	185	[screenio]		
GCic	COB-SCR-F14	185	[screenio]		
GCic	COB-SCR-F15	185	[screenio]		
GCic	COB-SCR-F16	185	[screenio]		
GCic	COB-SCR-F17	185	[screenio]		
GCic	COB-SCR-F18	185	[screenio]		
GCic	COB-SCR-F19	185	[screenio]		
GCic	COB-SCR-F2	185	[screenio]	842	
GCic	COB-SCR-F20	185	[screenio]		
GCic	COB-SCR-F21	185	[screenio]		
GCic	COB-SCR-F22	185	[screenio]		
GCic	COB-SCR-F23	185	[screenio]		
GCic	COB-SCR-F24	185	[screenio]		
GCic	COB-SCR-F25	185	[screenio]		
GCic	COB-SCR-F26	185	[screenio]		
GCic	COB-SCR-F27	185	[screenio]		
GCic	COB-SCR-F28	185	[screenio]		
GCic	COB-SCR-F29	185	[screenio]		

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 97

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 98
GCic	COB-SCR-F3	185	[screenio]	848	
GCic	COB-SCR-F30	185	[screenio]		
GCic	COB-SCR-F31	185	[screenio]		
GCic	COB-SCR-F32	185	[screenio]		
GCic	COB-SCR-F33	185	[screenio]		
GCic	COB-SCR-F34	185	[screenio]		
GCic	COB-SCR-F35	185	[screenio]		
GCic	COB-SCR-F36	185	[screenio]		
GCic	COB-SCR-F37	185	[screenio]		
GCic	COB-SCR-F38	185	[screenio]		
GCic	COB-SCR-F39	185	[screenio]		
GCic	COB-SCR-F4	185	[screenio]	854	
GCic	COB-SCR-F40	185	[screenio]		
GCic	COB-SCR-F41	185	[screenio]		
GCic	COB-SCR-F42	185	[screenio]		
GCic	COB-SCR-F43	185	[screenio]		
GCic	COB-SCR-F44	185	[screenio]		
GCic	COB-SCR-F45	185	[screenio]		
GCic	COB-SCR-F46	185	[screenio]		
GCic	COB-SCR-F47	185	[screenio]		
GCic	COB-SCR-F48	185	[screenio]		
GCic	COB-SCR-F49	185	[screenio]		
GCic	COB-SCR-F5	185	[screenio]	860	
GCic	COB-SCR-F50	185	[screenio]		
GCic	COB-SCR-F51	185	[screenio]		
GCic	COB-SCR-F52	185	[screenio]		
GCic	COB-SCR-F53	185	[screenio]		
GCic	COB-SCR-F54	185	[screenio]		
GCic	COB-SCR-F55	185	[screenio]		
GCic	COB-SCR-F56	185	[screenio]		
GCic	COB-SCR-F57	185	[screenio]		
GCic	COB-SCR-F58	185	[screenio]		
GCic	COB-SCR-F59	185	[screenio]		
GCic	COB-SCR-F6	185	[screenio]	865	
GCic	COB-SCR-F60	185	[screenio]		
GCic	COB-SCR-F61	185	[screenio]		
GCic	COB-SCR-F62	185	[screenio]		
GCic	COB-SCR-F63	185	[screenio]		
GCic	COB-SCR-F64	185	[screenio]		
GCic	COB-SCR-F7	185	[screenio]	871	
GCic	COB-SCR-F8	185	[screenio]	877	
GCic	COB-SCR-F9	185	[screenio]	883	
GCic	COB-SCR-FATAL	185	[screenio]		
GCic	COB-SCR-KEY-DOWN	185	[screenio]		
GCic	COB-SCR-KEY-UP	185	[screenio]		
GCic	COB-SCR-MAX-FIELD	185	[screenio]		
GCic	COB-SCR-NO-FIELD	185	[screenio]		
GCic	COB-SCR-OK	185	[screenio]		
GCic	COB-SCR-PAGE_DOWN	185	[screenio]		

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 98

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 99
GCic	COB-SCR-PAGE_UP	185	[screenio]		
GCic	COB-SCR-PRINT	185	[screenio]		
GCic	COB-SCR-TIME-OUT	185	[screenio]		
GCic	F-Cobc-Output-FILE	178	FILE	169 1014 1032	
GCic	F-Cobc-Output-REC	179	FILE	1015 1020* 1021	
				1029* 1030	
GCic	F-Source-Code-FILE	181	FILE	172 662 1180	
				1184 1185 1198	
				1199 1206	
GCic	F-Source-Code-REC	182	FILE	1189C 1203C	
GCic	F1		WORKING-STORAGE	213	
GCic	F12		WORKING-STORAGE	207	
GCic	F2		WORKING-STORAGE	220	
GCic	F3		WORKING-STORAGE	216	
GCic	F4		WORKING-STORAGE	214	
GCic	F5		WORKING-STORAGE	217 264	
GCic	F6		WORKING-STORAGE	218	
GCic	F7		WORKING-STORAGE	221	
GCic	F8		WORKING-STORAGE	215	
GCic	F9		WORKING-STORAGE	219	
GCic	LD-Horiz-Line	431	SCREEN	807	
GCic	LD-LL-Corner	426	SCREEN	463 493 509	
				523	
GCic	LD-Lower-T	430	SCREEN	495	
GCic	LD-LR-Corner	428	SCREEN	465 497 511	
				525	
GCic	LD-UL-Corner	425	SCREEN	453 467 499	
				513	
GCic	LD-Upper-T	429	SCREEN	469	
GCic	LD-UR-Corner	427	SCREEN	455 471 501	
				515	
GCic	LD-Vert-Line	432	SCREEN	457 458 460	
				461 473 474	
				475 477 478	
				479 481 482	
				483 485 486	
				487 489 490	
				491 503 504	
				506 507 517	
				518 520 521	
GCic	LPP		PROCEDURE	1057C	
GCic	LPPP		PROCEDURE	1058C	
GCic	RETURN-CODE		PROCEDURE	1016 1049* 1063*	
				1065	
GCic	S-Blank-SCR	444	SCREEN	690 1240 1269	
GCic	S-Switches-SCR	446	SCREEN	833* 914 1004	
				1033 1048 1069	
				1080 1266	
GCic	SELCHAR		PROCEDURE	725 828 831	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 99

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 100
				838 844 850	
				856 867 873	
				879 885 1208	
GCic	WS-Cmd-Args-TXT	236	WORKING-STORAGE	729* 731 732	
				735 740	
GCic	WS-Cmd-End-Quote-CHR	238	WORKING-STORAGE	733* 736	
GCic	WS-Cmd-SUB	240	WORKING-STORAGE	730* 731 732	
				734* 738* 743*	
GCic	WS-Cmd-TXT	234	WORKING-STORAGE	911* 1006* 1011*	
				1013C 1082* 1089*	
				1099* 1102* 1109*	
				1113* 1119* 1124*	
				1129* 1137* 1145*	
				1151* 1157* 1162*	
				1169C 1221* 1225*	
				1226C 1228* 1232*	
				1233C 1243* 1246*	
				1249C 1251C 1253C	
				1255C 1257C	
GCic	WS-Cobc-Cmd-TXT	242	WORKING-STORAGE	912* 921* 925*	
				929* 933* 938*	
				943* 948* 953*	
				958* 963* 967*	
				980* 988* 992*	
				1007	
GCic	WS-Compilation-Switches-TXT	187	WORKING-STORAGE		
GCic	WS-Config-Fn-TXT	244	WORKING-STORAGE	917* 923	
GCic	WS-CS-All-Switches-TXT	222	WORKING-STORAGE		
GCic	WS-CS-Arg-H1-TXT	189	WORKING-STORAGE	647*	
GCic	WS-CS-Arg-H2-TXT	190	WORKING-STORAGE	648*	
GCic	WS-CS-Args-TXT	188	WORKING-STORAGE	1160 1161	
GCic	WS-CS-Config-NUM	207	WORKING-STORAGE	639 893* 894	
				895* 916	
GCic	WS-CS-DEBUG-CHR	224	WORKING-STORAGE	600 837 838*	
				840* 936	
GCic	WS-CS-EXECUTE-CHR	225	WORKING-STORAGE	603 693 855	
				856* 858*	
GCic	WS-CS-Extra-H1-TXT	210	WORKING-STORAGE	645*	
GCic	WS-CS-Extra-H2-TXT	211	WORKING-STORAGE	646*	
GCic	WS-CS-Extra-TXT	209	WORKING-STORAGE	984 986	
GCic	WS-CS-Filename-TXT	200	WORKING-STORAGE	639 916	
GCic	WS-CS-Filenames-Table-TXT	199	WORKING-STORAGE		
GCic	WS-CS-Filenames-TXT	191	WORKING-STORAGE	199	
GCic	WS-CS-FREE-CHR	226	WORKING-STORAGE	608 878 879*	
				881* 961	
GCic	WS-CS-LIBRARY-CHR	227	WORKING-STORAGE	602 849 850*	
				852* 927 1087	
				1142 1181* 1208*	
GCic	WS-CS-LISTING-CHR	228	WORKING-STORAGE	604 689 825*	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 100

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 101
				828*	974
				976*	978
GCic	WS-CS-NOFUNC-CHR	229	WORKING-STORAGE	606	867*
				869*	951
GCic	WS-CS-NOTRUNC-CHR	230	WORKING-STORAGE	609	885*
				887*	941
GCic	WS-CS-Switch-Defaults-TXT	212	WORKING-STORAGE	223	
GCic	WS-CS-TRACEALL-CHR	231	WORKING-STORAGE	601	844*
				846*	946
GCic	WS-CS-WARNALL-CHR	232	WORKING-STORAGE	607	873*
				875*	956
GCic	WS-Delete-Fn-TXT	246	WORKING-STORAGE		
GCic	WS-File-Name-TXT	248	WORKING-STORAGE	172	675
				737*	745
				758	768
				771	1055C
GCic	WS-File-Status-Message-TXT	252	WORKING-STORAGE		
GCic	WS-FN-CHR	249	WORKING-STORAGE	763	774*
GCic	WS-FSM-Msg-TXT	256	WORKING-STORAGE	665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
				665*	665*
GCic	WS-FSM-Status-CD	254	WORKING-STORAGE	174	667
GCic	WS-Horizontal-Line-TXT	258	WORKING-STORAGE	454	468
				470	496
				500	514
				524	807*
GCic	WS-I-SUB	260	WORKING-STORAGE	761*	763
				764	770
				774	790
				791	794
				798	915*
				926*	934*
				939*	949*
				954*	964*
				968*	989*
				993*	1090*
				1100*	1110*
				1114*	1125*
				1130*	1146*
				1152*	1163*
GCic	WS-J-SUB	262	WORKING-STORAGE	1105*	1107
				1112	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 101

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 102
GCic	WS-Listing-CD	264	WORKING-STORAGE	822 861* 862 863* 1059C	
GCic	WS-Listing-Filename-TXT	266	WORKING-STORAGE	169 998* 999C 1008 1026 1054C 1224 1231	
GCic	WS-Listing-TXT	268	WORKING-STORAGE	620 824* 827* 830*	
GCic	WS-OC-Compile-DT	270	WORKING-STORAGE	532 715*	
GCic	WS-OS-Cygwin-BOOL	304	WORKING-STORAGE	758 782 1097 1127 1220	
GCic	WS-OS-Dir-CHR	279	WORKING-STORAGE	759* 763 774 783* 1123	
GCic	WS-OS-Exe-Ext-CONST	280	WORKING-STORAGE	1143 1144	
GCic	WS-OS-Lib-Ext-CONST	281	WORKING-STORAGE	1149 1150	
GCic	WS-OS-Lib-Type-CONST	282	WORKING-STORAGE	618	
GCic	WS-OS-OSX-BOOL	306	WORKING-STORAGE	1227	
GCic	WS-OS-Type-CD	283	WORKING-STORAGE	809 1056C	
GCic	WS-OS-Type-FILLER-TXT	308	WORKING-STORAGE	314	
GCic	WS-OS-Type-TXT	315	WORKING-STORAGE	809	
GCic	WS-OS-Types-TXT	314	WORKING-STORAGE		
GCic	WS-OS-UNIX-BOOL	305	WORKING-STORAGE	1127	
GCic	WS-OS-Windows-BOOL	303	WORKING-STORAGE	1220 1241	
GCic	WS-Output-Msg-TXT	318	WORKING-STORAGE	537 666* 812* 899* 913* 1003* 1018* 1019 1027* 1035* 1047* 1053* 1062* 1067* 1079* 1170* 1171* 1265	
GCic	WS-Path-Delimiter-CHR	320	WORKING-STORAGE		
GCic	WS-PFN-CHR	327	WORKING-STORAGE	791 798* 802*	
GCic	WS-Pgm-Nm-TXT	330	WORKING-STORAGE	795* 800* 997 1136 1242 1245	
GCic	WS-Prog-Extension-TXT	322	WORKING-STORAGE	796* 801*	
GCic	WS-Prog-File-Name-TXT	326	WORKING-STORAGE	578 768* 773* 789 795 799 991	
GCic	WS-Prog-Folder-TXT	324	WORKING-STORAGE	579 767* 772* 776 777* 780C 1096 1097 1101 1106 1107 1112 1118	
GCic	WS-RS-1st-Prog-Complete-BOOL	343	WORKING-STORAGE	1183 1192*	
GCic	WS-RS-Compile-Failed-BOOL	336	WORKING-STORAGE	1024* 1036	
GCic	WS-RS-Compile-OK-BOOL	334	WORKING-STORAGE	688 1017*	
GCic	WS-RS-Compile-OK-CHR	333	WORKING-STORAGE		
GCic	WS-RS-Compile-OK-Warn-BOOL	335	WORKING-STORAGE	688	
GCic	WS-RS-Complete-BOOL	338	WORKING-STORAGE	685 1022*	
GCic	WS-RS-Complete-CHR	337	WORKING-STORAGE		
GCic	WS-RS-Double-Quote-Used-BOOL	341	WORKING-STORAGE	1095* 1121* 1155	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 102

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 103
GCic	WS-RS-IDENT-DIV-CHR	342	WORKING-STORAGE		
GCic	WS-RS-More-To-1st-Prog-BOOL	344	WORKING-STORAGE	1182*	
GCic	WS-RS-No-Switch-Changes-BOOL	346	WORKING-STORAGE	821	902*
GCic	WS-RS-No-Switch-Chgs-CHR	345	WORKING-STORAGE		
GCic	WS-RS-Not-Complete-BOOL	339	WORKING-STORAGE	684*	
GCic	WS-RS-Output-File-Avail-BOOL	350	WORKING-STORAGE	694	1005*
GCic	WS-RS-Output-File-Busy-BOOL	349	WORKING-STORAGE		
GCic	WS-RS-Output-File-Busy-CHR	348	WORKING-STORAGE		
GCic	WS-RS-Quote-CHR	340	WORKING-STORAGE		
GCic	WS-RS-Source-Rec-Ident-BOOL	353	WORKING-STORAGE	1191	1197
GCic	WS-RS-Source-Rec-Ignored-BOOL	354	WORKING-STORAGE	1195*	
GCic	WS-RS-Source-Rec-Linkage-BOOL	352	WORKING-STORAGE	1196	1207
GCic	WS-RS-Source-Record-Type-CHR	351	WORKING-STORAGE	1190C	1204C
GCic	WS-RS-Switch-Changes-BOOL	347	WORKING-STORAGE	820*	
GCic	WS-RS-Switch-Error-CHR	355	WORKING-STORAGE		
GCic	WS-RS-Switch-Is-Bad-BOOL	356	WORKING-STORAGE		
GCic	WS-RS-Switch-Is-Good-BOOL	357	WORKING-STORAGE		
GCic	WS-Runtime-Switches-TXT	332	WORKING-STORAGE		
GCic	WS-Tally-QTY	359	WORKING-STORAGE	971*	973* 975

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 103

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 104
LISTING	000-Main	2412	PROCEDURE		
LISTING	100-Initialization	2429	PROCEDURE	2413	
LISTING	300-Tokenize-Source	2502	PROCEDURE	2420	
LISTING	310-Get-Token	2553	PROCEDURE	2511	
LISTING	311-Control-Record	2713	PROCEDURE	2572	
LISTING	312-Expanded-Src-Record	2759	PROCEDURE	2574	
LISTING	313-Check-For-Numeric-Token	2770	PROCEDURE	2700	
LISTING	320-IDENTIFICATION-DIVISION	2812	PROCEDURE	2532	
LISTING	330-ENVIRONMENT-DIVISION	2832	PROCEDURE	2534	
LISTING	340-DATA-DIVISION	2858	PROCEDURE	2536	
LISTING	350-PROCEDURE-DIVISION	2914	PROCEDURE	2538	
LISTING	351-ACCEPT	2985	PROCEDURE	2941	
LISTING	351-ADD	2995	PROCEDURE	2943	
LISTING	351-ALLOCATE	3006	PROCEDURE	2945	
LISTING	351-CALL	3018	PROCEDURE	2947	
LISTING	351-COMPUTE	3029	PROCEDURE	2949	
LISTING	351-DIVIDE	3038	PROCEDURE	2951	
LISTING	351-FREE	3058	PROCEDURE	2953	
LISTING	351-GENERATE	3062	PROCEDURE	2955	2959 2975
LISTING	351-INITIALIZE	3066	PROCEDURE	2957	
LISTING	351-INITIATE	3075	PROCEDURE		
LISTING	351-INSPECT	3079	PROCEDURE	2961	
LISTING	351-MOVE	3109	PROCEDURE	2963	
LISTING	351-MULTIPLY	3118	PROCEDURE	2965	
LISTING	351-PERFORM	3134	PROCEDURE	2967	
LISTING	351-SET	3147	PROCEDURE	2969	
LISTING	351-STRING	3156	PROCEDURE	2971	
LISTING	351-SUBTRACT	3167	PROCEDURE	2973	
LISTING	351-TERMINATE	3178	PROCEDURE		
LISTING	351-TRANSFORM	3182	PROCEDURE	2977	
LISTING	351-UNSTRING	3192	PROCEDURE	2979	
LISTING	360-Release-Def	3209	PROCEDURE	2848	2885 2888
				2891	2894 2897
				2932	
LISTING	361-Release-Ref	3220	PROCEDURE	2850	2854 2907
				2981	2991 3002
				3014	3034 3054
				3071	3105 3114
				3130	3143 3152
				3163	3174 3188
				3205	
LISTING	362-Release-Upd	3225	PROCEDURE	2900	2903 2988
				2998	3000 3009
				3012	3021 3023
				3032	3050 3052
				3059	3063 3069
				3076	3086 3112
				3128	3137 3140
				3150	3159 3161

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 104

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 105
				3170	3172 3179
				3185	3195 3197
				3199	3201 3203
LISTING	363-Set-Upd	3230	PROCEDURE	3041	3121 3226
LISTING	364-Set-Ref	3240	PROCEDURE	3082	3221
LISTING	365-Release-Arg	3249	PROCEDURE	3025	
LISTING	366-Set-Arg	3254	PROCEDURE	3250	
LISTING	400-Produce-Xref-Listing	3265	PROCEDURE	2421	
LISTING	410-Generate-Report-Line	3343	PROCEDURE	3274	3277 3287
				3291	3301 3313
				3329	3339
LISTING	420-Generate-Xref-Footer	3411	PROCEDURE	3280	3345
LISTING	500-Produce-Source-Listing	3445	PROCEDURE	2415	
LISTING	510-Control-Record	3468	PROCEDURE	3458	
LISTING	520-Expanded-Src-Record	3485	PROCEDURE	3460	
LISTING	530-Generate-Source-Line	3551	PROCEDURE	3452	3499 3503
				3508	3512 3516
				3519	3535 3539
				3543	3546
LISTING	F-ES-1-7-TXT	1432	FILE	2570	3456
LISTING	F-ES-1-CHR	1429	FILE	2571	3457
LISTING	F-ES-2-256-TXT-256	1430	FILE	2714	3469
LISTING	F-ES-8-256-TXT	1433	FILE		
LISTING	F-Expanded-Src-FILE	1427	FILE	1418	2503 2550
				2560	3447 3450
				3465	3478
LISTING	F-Expanded-Src-REC	1428	FILE	2504*	2558 2582
				2584	2614 2618
				2627	2631 2640
				2644	2652 2670
				2755*	2760 3521
				3523	
LISTING	F-Expanded-Src2-REC	1431	FILE		
LISTING	F-Listing-135-REC	1437	FILE	3353*	3355* 3357*
				3358	3360* 3361
				3364*	3366* 3367
				3368*	3369* 3370
				3371	3372 3373
				3401	3413 3415*
				3416	3418* 3420*
				3422	3424 3425
				3569	3571 3573*
				3574	3576* 3578*
				3579	3580 3610*
				3612*	3614* 3615
				3617*	3618 3620*
				3622*	3623 3625*
				3626	3652* 3657*
				3658	3661* 3662

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 105

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 106	
LISTING	F-Listing-96-REC	1436	FILE	3376* 3378* 3380* 3381 3383* 3384 3387* 3389* 3390 3391* 3392* 3393 3394 3395 3396 3404 3428 3430* 3431 3433* 3435* 3437 3439 3440 3586 3588 3589 3591 3593* 3594 3596* 3598* 3599 3600 3629* 3631* 3633* 3634 3636* 3637 3639* 3641* 3642 3644* 3645 3653 3668 3673 3677 3682 3686 3690		
LISTING	F-Listing-FILE	1435	FILE	1420	2414 2422	
LISTING	F-Listing-REC	1438	FILE			
LISTING	F-Original-Src-FILE	1440	FILE	1422	3446 3464	
				3488		
LISTING	F-Original-Src-REC	1441	FILE	3492		
LISTING	F-OS-1-128-TXT	1442	FILE			
LISTING	F-OS-129-256-TXT	1447	FILE			
LISTING	F-OS-7-CHR	1444	FILE	3497		
LISTING	F-OS-8-72-TXT	1445	FILE	3493	3525	
LISTING	F-Sort-Work-FILE	1449	FILE	1424	2416 3272	
LISTING	F-Sort-Work-REC	1450	FILE	2525* 2527 2562* 2564 3042 3045* 3048 3090* 3093 3098* 3101 3122 3124* 3127 3210* 3217 3222 3227 3231* 3241* 3251 3255*		
LISTING	F-SW-Def-Line-NUM	1455	FILE	3215* 3298 3306 3310 3322 3323		
LISTING	F-SW-Prog-ID-TXT	1451	FILE	2417 3211* 3232* 3242* 3256* 3283 3289 3294 3303 3315 3319		
LISTING	F-SW-Ref-Flag-CHR	1458	FILE	3047* 3092* 3100* 3126* 3237* 3261* 3334		
LISTING	F-SW-Ref-Line-NUM	1457	FILE	2419 3216* 3236* 3246* 3260* 3332		
LISTING	F-SW-Reference-TXT	1456	FILE	3326		
LISTING	F-SW-Section-TXT	1454	FILE	3214* 3235* 3245*		

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 106

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing		2014/03/27				
		C:/Users/tda010/Documents/Programs/Samples/GCic.cbl				
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 107	
=====						
LISTING	F-SW-Token-TXT	1453	FILE	3259* 3213* 3258*	3305 3234* 3320	3321 3244*
LISTING	F-SW-Token-Uc-TXT	1452	FILE	2418 3243* 3295	3212* 3257* 3297	3233* 3284 3309
LISTING	L-Listing-CD	2404	LINKAGE	2411 3351 3553 3649	2451 3400 3567	2488 3412 3608
LISTING	L-Listing-Fn-TXT	2394	LINKAGE	1420	2406	
LISTING	L-LPP-NUM	2400	LINKAGE	2409	2489	
LISTING	L-LPP-Port-NUM	2402	LINKAGE	2410	2491	
LISTING	L-OS-Type-CD	2398	LINKAGE	2408	2434	
LISTING	L-Src-Fn-TXT	2396	LINKAGE	1422 2439*	2407 2440	2439 2441
				2445 2463	2448 2465	2461 2470
LISTING	RETURN-CODE		PROCEDURE	2481		
LISTING	WS-CD-In-DATA-DIV-BOOL	1475	WORKING-STORAGE	2535		
LISTING	WS-CD-In-ENV-DIV-BOOL	1474	WORKING-STORAGE	2533		
LISTING	WS-CD-In-IDENT-DIV-BOOL	1473	WORKING-STORAGE	2531		
LISTING	WS-CD-In-PROC-DIV-BOOL	1476	WORKING-STORAGE	2537		
LISTING	WS-Copyright-TXT	1461	WORKING-STORAGE	2432* 3432	2437* 3575	3417 3595
LISTING	WS-CPI-13-15-TXT	1482	WORKING-STORAGE	2826*		
LISTING	WS-CPI-16-CHR	1483	WORKING-STORAGE	2825		
LISTING	WS-CS-1-CHR	1486	WORKING-STORAGE	2748*		
LISTING	WS-CS-11-14-TXT	1489	WORKING-STORAGE	2750	2751*	
LISTING	WS-CS-15-CHR	1490	WORKING-STORAGE	2753*		
LISTING	WS-CS-2-14-TXT	1487	WORKING-STORAGE	2749*		
LISTING	WS-Curr-Char-Is-Punct-BOOL	1464	WORKING-STORAGE	2593	2601	2606
LISTING	WS-Curr-Char-Is-Quote-BOOL	1468	WORKING-STORAGE	2612		
LISTING	WS-Curr-Char-Is-X-BOOL	1469	WORKING-STORAGE	2625		
LISTING	WS-Curr-Char-Is-Z-BOOL	1470	WORKING-STORAGE	2638		
LISTING	WS-Curr-CHR	1463	WORKING-STORAGE	2583* 2594 2615	2586 2602	2588 2608
LISTING	WS-Curr-Division-TXT	1472	WORKING-STORAGE	2508* 2603 2838* 2925*	2544 2703	2595 2819* 2920*
LISTING	WS-Curr-Line-NUM	1478	WORKING-STORAGE	2507* 2766* 3246	2567* 3215 3260	2726* 3236 3487*
LISTING	WS-Curr-Prog-ID-TXT	1480	WORKING-STORAGE	2497* 3232	2824* 3242	3211 3256
LISTING	WS-Curr-Section-TXT	1485	WORKING-STORAGE	2729* 2869*	2734 2915	2843* 2916*
=====						

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cb1

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 108
				3214	3235 3245
				3259	
LISTING	WS-Curr-Verb-TXT	1492	WORKING-STORAGE	2498*	2522* 2546*
				2930	2939
LISTING	WS-Delim-TXT	1494	WORKING-STORAGE	2655*	2657 2675*
				2677	2680
LISTING	WS-Dummy-TXT	1496	WORKING-STORAGE	2473*	2718* 2747*
				2780*	2785* 2786
				3473*	
LISTING	WS-Expanded-Src-Fn-TXT	1498	WORKING-STORAGE	1418	2478* 2479C
LISTING	WS-Filename-TXT	1500	WORKING-STORAGE	2472*	2475 2746*
				2749	
LISTING	WS-Flags-TXT	1502	WORKING-STORAGE		
LISTING	WS-Formatted-DT	1505	WORKING-STORAGE	2496*	3356 3379
				3613	3632
LISTING	WS-GI-Prog-ID-TXT	1508	WORKING-STORAGE	3283	3289 3294*
LISTING	WS-GI-Token-TXT	1509	WORKING-STORAGE	3284	3295* 3297
				3309	
LISTING	WS-Group-Indicators-TXT	1507	WORKING-STORAGE	3267*	
LISTING	WS-Held-Reference-TXT	1511	WORKING-STORAGE	2499*	2524 2525
				2526*	2561 2562
				2563*	3042* 3044
				3045	3046* 3083*
				3089	3090 3091*
				3097	3098 3099*
				3122*	3124 3125*
LISTING	WS-I-SUB	1513	WORKING-STORAGE	2440*	2441 2442
				2444	2447* 2448
				2463*	2465 2466
				2467	2470 2723*
				2726	2737* 2739
				2740	2741 2744
				3268*	3302* 3314*
				3327*	3328 3330*
				3333	3335 3408*
LISTING	WS-J-SUB	1515	WORKING-STORAGE	2464*	2468* 2470
				2738*	2742* 2744
LISTING	WS-Lines-Left-NUM	1517	WORKING-STORAGE	3269*	3278 3292
				3344	3398* 3409
				3453	3500 3504
				3531*	3565 3647*
				3654	3663 3670
				3679	3692
LISTING	WS-Lines-Per-Page-Env-TXT	1521	WORKING-STORAGE	2453*	2457* 2484
				2485	
LISTING	WS-Lines-Per-Page-NUM	1519	WORKING-STORAGE	2486*	2489* 2491*
				2494	3398 3647
LISTING	WS-Main-Module-Name-TXT	1523	WORKING-STORAGE	2445*	2449* 2725
				3475	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 108

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing		2014/03/27				
		C:/Users/tda010/Documents/Programs/Samples/GCic.cbl				
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 109	
=====						
LISTING	WS-Next-Char-Is-Quote-BOOL	1526	WORKING-STORAGE	2625	2638	
LISTING	WS-Next-CHR	1525	WORKING-STORAGE	2585*	2628	2641
LISTING	WS-OS-Type-FILLER-TXT	1528	WORKING-STORAGE	1534		
LISTING	WS-OS-Type-TXT	1535	WORKING-STORAGE	2434		
LISTING	WS-OS-Types-TXT	1534	WORKING-STORAGE			
LISTING	WS-Page-No-TXT	1540	WORKING-STORAGE	3350C	3365	3388
				3419	3434	3577
				3597	3607C	3621
				3640		
LISTING	WS-Page-NUM	1538	WORKING-STORAGE	2430*	3346*	3348
				3566	3603*	3605
LISTING	WS-PN-Literal-TXT	1541	WORKING-STORAGE	3347*	3604*	
LISTING	WS-PN-Page-NUM	1542	WORKING-STORAGE	3348*	3349C	3605*
				3606C		
LISTING	WS-Program-Path-TXT	1544	WORKING-STORAGE	2461*	2462C	3359
				3382	3616	3635
LISTING	WS-Reserved-Word-Table-TXT	2301	WORKING-STORAGE			
LISTING	WS-Reserved-Word-TXT	2302	WORKING-STORAGE	2690		
LISTING	WS-Reserved-Words-TXT	1546	WORKING-STORAGE	2301		
LISTING	WS-RS-Duplicate-CHR	2310	WORKING-STORAGE	3270*	3285*	3300*
				3311	3312*	
LISTING	WS-RS-In-Copybook-BOOL	2313	WORKING-STORAGE	2732*	3481*	
LISTING	WS-RS-In-Main-Module-BOOL	2312	WORKING-STORAGE	2727*	2765	3476*
				3486		
LISTING	WS-RS-In-Which-Pgm-CHR	2311	WORKING-STORAGE			
LISTING	WS-RS-Last-Token-Ended-Sent-CHR	2314	WORKING-STORAGE	2556*	2702	
LISTING	WS-RS-Processing-PICTURE-CHR	2315	WORKING-STORAGE	2651	2665*	2874*
LISTING	WS-RS-Token-Ended-Sentence-CHR	2316	WORKING-STORAGE	2543	2555	2557*
				2590*	2619*	2632*
				2645*	2658*	2678*
LISTING	WS-RS-Verb-Has-Been-Found-CHR	2317	WORKING-STORAGE	2509*	2694*	2816*
LISTING	WS-Runtime-Switches	2309	WORKING-STORAGE			
LISTING	WS-RW-IDX	2305	WORKING-STORAGE	2691	2692	
LISTING	WS-RW-Type-CD	2306	WORKING-STORAGE	2692		
LISTING	WS-RW-Word-TXT	2307	WORKING-STORAGE	2304	2691	
LISTING	WS-Saved-Section-TXT	2319	WORKING-STORAGE	2728	2729	2733
				2734*		
LISTING	WS-SDL-Line-NUM	2326	WORKING-STORAGE	3491*		
LISTING	WS-SDL-Statement-TXT	2328	WORKING-STORAGE	3492*	3524*	3554
				3558	3560	3656
				3660*	3672	3676*
				3681	3685*	3689*
LISTING	WS-Src-Dashes-TXT	2321	WORKING-STORAGE	3624	3643	
LISTING	WS-Src-Detail-Line-TXT	2325	WORKING-STORAGE	3451*	3490*	3498*
				3502*	3507*	3511*
				3515*	3522*	3534*
				3538*	3542*	3652
				3657	3659*	3661
				3668	3673	3675*

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing 2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 110
				3677	3682
				3686	3688*
				3695*	3690
LISTING	WS-Src-Hold-TXT	2330	WORKING-STORAGE	3656*	3660
				3676	3681*
				3689	3672*
LISTING	WS-Src-Line-NUM	2332	WORKING-STORAGE	3448*	3477
				3491	3489*
LISTING	WS-Src-Lines-NUM	2334	WORKING-STORAGE	3552*	3555*
				3561*	3565
				3582	3666
LISTING	WS-Src-SUB	2336	WORKING-STORAGE	2505*	2558
				2578*	2582
				2587*	2596*
				2613*	2617*
				2620*	2626*
				2631	2633*
				2643*	2644
				2656*	2659*
				2681	2756*
				2763*	2761*
LISTING	WS-Suppress-FF-CHR	1503	WORKING-STORAGE	2431*	3279*
				3436	3421
LISTING	WS-Tally-QTY	2338	WORKING-STORAGE	2795*	2797*
				2802*	2803
LISTING	WS-Temp-10-Chars-TXT	2340	WORKING-STORAGE	2716*	2720
				2723	3471*
LISTING	WS-Temp-256-Chars-TXT	2350	WORKING-STORAGE	2480C	2717*
				2736	2739
				3472*	3474
LISTING	WS-Temp-32-Chars-1-TXT	2342	WORKING-STORAGE	2771*	2774
LISTING	WS-Temp-32-Chars-2-TXT	2344	WORKING-STORAGE	2778*	2783*
				2790*	2806
LISTING	WS-Temp-32-Chars-3-TXT	2346	WORKING-STORAGE	2779*	2784*
				2793*	2806
LISTING	WS-Temp-65-Chars-TXT	2348	WORKING-STORAGE	3494*	3501
				3510	3514
				3530	3533
				3541	3526*
LISTING	WS-Today-DT	2352	WORKING-STORAGE	2495*	2496
LISTING	WS-Token-Curr-TXT	2354	WORKING-STORAGE	2515	2519*
				2597*	2608*
				2629*	2642*
				2661	2674*
				2686*	2704*
				2818	2824
				2842	2863
				2872	2906
				3213	3234
					3244

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 111
				3258	
LISTING	WS-Token-Curr-Uc-TXT	2356	WORKING-STORAGE	2516* 2519 2522 2541 2918 3212 3233 3243 3257	
LISTING	WS-Token-Prev-TXT	2358	WORKING-STORAGE	2523* 2541* 2545* 2604* 2819 2822 2823* 2838 2843 2847 2864 2869 2878 2879* 2883 2886* 2889* 2892* 2895* 2898* 2901* 2904* 2919 2925 2929 2933* 2986 2989* 2996 3007 3010* 3019 3030 3039 3067 3080 3084* 3087* 3095* 3103* 3110 3119 3135 3138* 3141* 3148 3157 3168 3183 3186* 3193	
LISTING	WS-Token-Search-TXT	2360	WORKING-STORAGE	2684* 2685 2691	
LISTING	WS-Token-Type-CD	2362	WORKING-STORAGE	2589* 2598* 2609* 2662* 2666* 2687* 2692* 2705*	
LISTING	WS-TT-Token-Is-Argtype-BOOL	2363	WORKING-STORAGE	2813 2833 2859	
LISTING	WS-TT-Token-Is-EOF-BOOL	2364	WORKING-STORAGE	2512 2566*	
LISTING	WS-TT-Token-Is-Function-BOOL	2365	WORKING-STORAGE	2853	
LISTING	WS-TT-Token-Is-Identifier-BOOL	2366	WORKING-STORAGE	2699* 2846 2882 2928 2936	
LISTING	WS-TT-Token-Is-Keyword-BOOL	2367	WORKING-STORAGE	2517 2540 2817 2836 2841 2862 2867 2873 2923	
LISTING	WS-TT-Token-Is-Lit-Alpha-BOOL	2368	WORKING-STORAGE	2622* 2648*	
LISTING	WS-TT-Token-Is-Lit-Number-BOOL	2369	WORKING-STORAGE	2635* 2701 2775* 2807*	
LISTING	WS-TT-Token-Is-Reserved-Wd-BOOL	2371	WORKING-STORAGE	2518 2814* 2834* 2860* 2877	
LISTING	WS-TT-Token-Is-Verb-BOOL	2370	WORKING-STORAGE	2521 2693	
LISTING	WS-Usernames-QTY	2373	WORKING-STORAGE	2506*	
LISTING	WS-Version-TXT	2375	WORKING-STORAGE	2438* 3352 3375 3609 3628	
LISTING	WS-XDL-Def-Line-NUM	2382	WORKING-STORAGE	3306* 3323*	
LISTING	WS-XDL-Prog-ID-TXT	2378	WORKING-STORAGE	3303* 3315* 3319*	
LISTING	WS-XDL-Ref-Flag-CHR	2388	WORKING-STORAGE	3335*	
LISTING	WS-XDL-Ref-Line-NUM	2387	WORKING-STORAGE	3333*	
LISTING	WS-XDL-Reference-TXT	2386	WORKING-STORAGE		
LISTING	WS-XDL-Section-TXT	2384	WORKING-STORAGE	3305* 3321*	
LISTING	WS-XDL-Token-TXT	2380	WORKING-STORAGE	3304* 3316* 3320*	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 111


```

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing                                2014/03/27
                                                                 C:/Users/tda010/Documents/Programs/Samples/GCic.cbl
PROGRAM-ID      Identifier/Register/Function  Defn  Where Defined  References  Page: 112
=====
LISTING         WS-Xref-Detail-Line-TXT                2377 WORKING-STORAGE  3266*  3273  3276*
                                                         3286  3290*  3299
                                                         3318  3338  3401
                                                         3404  3407*
LISTING         WS-Xref-Lines-Per-Rec-NUM                2391 WORKING-STORAGE  2452*  2456*  3328

```


6. STREAMIO

STREAMIO is a utility I created to assist with handling stream I/O functions. I've used it to construct a number of useful little command-line utilities.

Usage of this subroutine is completely documented in the program comments. The program COPYs a copybook named STREAMIOcb, the format of which is described in the program comments.

Both STREAMIO.cbl and STREAMIOcb.cpy are included in the "samples" directory of any pre-built distributions of GNU COBOL that I have created.

In addition to general GNU COBOL concepts, this program provides a useful demonstration of the following:

- Coding a GNU COBOL subroutine
- Using the "REPLACING" clause on a CDF "COPY" statement
- Using hexadecimal alphanumeric literals
- Using the following statements:
 - "ACCEPT FROM ENVIRONMENT" statement
 - "INSPECT" statement
 - "STRING" statement
- Using the following built-in subroutines:
 - "C\$PARAMSIZE" built-in system subroutine
 - "CBL_CLOSE_FILE" built-in system subroutine
 - "CBL_DELETE_FILE" built-in system subroutine
 - "CBL_EXIT_PROC" built-in system subroutine
 - "CBL_OPEN_FILE" built-in system subroutine
 - "CBL_READ_FILE" built-in system subroutine
 - "CBL_WRITE_FILE" built-in system subroutine
- Using the following intrinsic functions:
 - "RANDOM" intrinsic function
 - "TRIM" intrinsic function

First, here is the STREAMIOcb.cpy copybook:

```

05 SCB-Handle-NUM                PIC X(4) COMP-X.
05 SCB-Mode-CD                   PIC X(1).
   88 SCB-MODE-Input-BOOL        VALUE 'I', 'i'.
   88 SCB-MODE-Output-BOOL       VALUE 'O', 'o'.
   88 SCB-MODE-Both-BOOL         VALUE 'B', 'b'.
05 SCB-Function-CD              PIC X(2).
   88 SCB-Func-CLOSE-BOOL        VALUE 'C ', 'c '.
   88 SCB-Func-DELETE-BOOL       VALUE 'D ', 'd '.
   88 SCB-Func-OPEN-BOOL         VALUE 'O ', 'o '.
   88 SCB-Func-READ-BOOL         VALUE 'R ', 'r '.
   88 SCB-Func-READ-Delim-BOOL   VALUE 'RD', 'rd',
                                   'rD', 'Rd'.
   88 SCB-Func-WRITE-BOOL        VALUE 'W ', 'w '.
   88 SCB-Func-WRITE-Delim-BOOL  VALUE 'WD', 'wd',
                                   'wD', 'Wd'.

05 SCB-Delimiter-Mode-CD        PIC X(1).
   88 SCB-DELIM-Unix-BOOL        VALUE 'U', 'u'.
   88 SCB-DELIM-Windows-BOOL     VALUE 'W', 'w'.
05 SCB-Offset-NUM              PIC X(8) COMP-X.
05 SCB-Error-Routine-PTR        USAGE PROGRAM-POINTER.
05 SCB-Error-Routine-NUM REDEFINES SCB-Error-Routine-PTR
                                   USAGE BINARY-LONG.
05 SCB-Return-CD                USAGE BINARY-LONG.
05 SCB-Filename-TXT            PIC X(256).

```

The program source and cross-reference listing, produced using the GNU COBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      PROGRAM-ID. STREAMIO.
4      *>*****
5      *> Author: Gary L. Cutler **
6      *> **
7      *> This routine centralizes all bytestream file I/O functions **
8      *> into one routine. The manner in which this routine is **
9      *> CALLED is as follows: **
10     *> **
11     *>         CALL "STREAMIO" USING control-block [ , arg2 ] **
12     *> **
13     *> where 'control-block' is defined by the "STREAMIOcb.cpy" **
14     *> copybook and 'arg2' will vary, depending upon the function **
15     *> specified in the control block. **
16     *> **
17     *> The STREAMIO routine has an advantage over the various **
18     *> "CBL_XXXXXX_FILE" routines in that: **
19     *> **
20     *> 1. It automates the establishment and on-going adjustment of **
21     *> the file-offset value in such a way as to simplify the **
22     *> sequential processing of a bytestream file (you may still **
23     *> specify a file-offset manually on each read or write, if **
24     *> you wish) **
25     *> **
26     *> 2. It auto-detects the size of the I/O buffer you supply to **
27     *> STREAMIO, using that as the byte-count of all read and **
28     *> write operations. **
29     *> **
30     *> 3. Not only does it support the raw input and output of data **
31     *> that the CBL_READ_FILE and CBL_WRITE_FILE routines do, **
32     *> but on input it is also capable of delivering just a **
33     *> single newline-delimited or carriage-return/newline de- **
34     *> limited record to the caller. **
35     *> **
36     *> 4. On output, STREAMIO can optionally append either a new- **
37     *> line or carriage-return/newline sequence (your choice) to **
38     *> the end of every record it writes. **
39     *> **
40     *> 5. STREAMIO can automatically generate filenames for output **
41     *> files if you wish, simplifying the process of creating **
42     *> scratch or work files. **
43     *> **
44     *> 6. The STREAMIO routine also allows you to (optionally) re- **
45     *> gister a general error-handling routine to be given con- **
46     *> trol should a fatal error be detected with STREAMIO. **
47     *> **
48     *> This routine can be "turned on" and "turned off" at will. **
49     *> **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cb1

Line Statement

Page: 2

```

=====
50     *> The control block format is as follows. This structure must **
51     *> be defined under an 01-level data item of your creation and **
52     *> should be INITIALIZED before any items within it are used. **
53     *> **
54     *> 05 SCB-Handle-NUM          PIC X(4) COMP-X. **
55     *> 05 SCB-Mode-CD            PIC X(1). **
56     *>     88 SCB-Mode-Input-BOOL VALUE 'I', 'i'. **
57     *>     88 SCB-Mode-Output-BOOL VALUE 'O', 'o'. **
58     *>     88 SCB-Mode-Both-BOOL  VALUE 'B', 'b'. **
59     *> 05 SCB-Function-CD        PIC X(2). **
60     *>     88 SCB-Func-CLOSE-BOOL  VALUE 'C ', 'c '. **
61     *>     88 SCB-Func-DELETE-BOOL VALUE 'D ', 'd '. **
62     *>     88 SCB-Func-OPEN-BOOL   VALUE 'O ', 'o '. **
63     *>     88 SCB-Func-READ-BOOL   VALUE 'R ', 'r '. **
64     *>     88 SCB-Func-READ-Delim-BOOL VALUE 'RD', 'rd', **
65     *>                               'rD', 'Rd'. **
66     *>     88 SCB-Func-WRITE-BOOL  VALUE 'W ', 'w '. **
67     *>     88 SCB-Func-WRITE-Delim-BOOL VALUE 'WD', 'wd', **
68     *>                               'wD', 'Wd'. **
69     *> 05 SCB-Delimiter-Mode-CD   PIC X(1). **
70     *>     88 SCB-Delim-Unix-BOOL  VALUE 'U', 'u'. **
71     *>     88 SCB-Delim-Windows-BOOL VALUE 'W', 'w'. **
72     *> 05 SCB-Offset-NUM          PIC X(8) COMP-X. **
73     *> 05 SCB-Error-Routine-PTR   USAGE PROGRAM-POINTER. **
74     *> 05 SCB-Error-Routine-NUM REDEFINES SCB-Error-Routine-PTR **
75     *>                               USAGE BINARY-LONG. **
76     *> 05 SCB-Return-CD           USAGE BINARY-LONG. **
77     *> 05 SCB-Filename-TXT        PIC X(256). **
78     *> **
79     *> Such a structure is defined for your use using the copybook **
80     *> "STREAMIOcb.cpy" (you may also define your own, provided it **
81     *> conforms to the above layout). **
82     *>-----**
83     *> SCB-Handle-NUM **
84     *>-----**
85     *> **
86     *> Serves as a file handle to the file once it has been opened **
87     *> (via the "SCB-Func-OPEN-BOOL" function). **
88     *> **
89     *>-----**
90     *> SCB-Mode-CD **
91     *>-----**
92     *> **
93     *> Prior to calling "STREAMIO" for the first time for a file, **
94     *> the appropriate subordinate level-88 must be set to TRUE to **
95     *> select an I/O mode. You may also simply move one of the **
96     *> string values listed on the level-88 items to "SCB-Mode-CD". **
97     *> **
98     *>-----**
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 3

```

=====
 99      *> SCB-Function-CD                                **
100      *>-----**
101      *>                                              **
102      *> The appropriate subordinate level-88 must be set to TRUE to **
103      *> select a function you'd like to execute against a file. You **
104      *> may also simply move one of the string values listed on the **
105      *> level-88 items to "SCB-Function-CD".          **
106      *>                                              **
107      *> Available functions are as follows:           **
108      *>                                              **
109      *> SCB-Func-OPEN-BOOL                            **
110      *>                                              **
111      *>     This must be the function specified the first time you **
112      *>     call STREAMIO for any given file. It opens the file & **
113      *>     makes it available for use according to the **
114      *>     "SCB-Mode-CD" specification.              **
115      *>                                              **
116      *>     The filename being opened must be specified in the **
117      *>     "SCB-Filename-TXT" field.                  **
118      *>                                              **
119      *>     The SCB-Offset-NUM field will be initialized to ZERO. **
120      *>                                              **
121      *>     If "arg2" is specified in conjunction with this funct- **
122      *>     ion, it will be ignored.                    **
123      *>                                              **
124      *> SCB-Func-CLOSE-BOOL                            **
125      *>                                              **
126      *>     This function should be the one specified the LAST time **
127      *>     you call STREAMIO against a specific file. After this **
128      *>     function has been executed, you'll have to re-open the **
129      *>     file if you wish to use it with STREAMIO again.    **
130      *>                                              **
131      *>     The SCB-Handle-NUM item will be reset to ZERO.    **
132      *>                                              **
133      *>     If "arg2" is specified in conjunction with this funct- **
134      *>     ion, it will be ignored.                    **
135      *>                                              **
136      *> SCB-Func-DELETE-BOOL                            **
137      *>                                              **
138      *>     This function will delete the file specified in the **
139      *>     control block (see SCB-Filename-TXT).          **
140      *>                                              **
141      *>     This function should not be performed against a file **
142      *>     that is open.                                    **
143      *>                                              **
144      *>     If "arg2" is specified in conjunction with this funct- **
145      *>     ion, it will be ignored.                    **
146      *>                                              **
147      *> SCB-Func-READ-BOOL                              **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 4

```

=====
148      *>
149      *>      This function invokes a standard CBL_READ_FILE against **
150      *>      the file specified in the control block (see **
151      *>      SCB-Filename-TXT). **
152      *> **
153      *>      The buffer into which you wish to read data must be **
154      *>      supplied as "arg2". The size of that buffer, in bytes, **
155      *>      will define the "byte-count" value supplied to the **
156      *>      CBL_READ_FILE subroutine. The buffer data item will be **
157      *>      set to SPACES before the read takes place. **
158      *> **
159      *>      If the file-offset value (SCB-Offset-NUM) is greater **
160      *>      than the size of the file, a "no more data" return code **
161      *>      (01) will be passed back in SCB-Return-CD and the **
162      *>      buffer will have been set to SPACES. **
163      *> **
164      *>      At the conclusion of a successful SCB-Func-READ-BOOL, **
165      *>      the value of SCB-Offset-NUM will have been automati- **
166      *>      cally incremented by the byte-count size of "arg2". **
167      *> **
168      *> SCB-Func-WRITE-BOOL **
169      *> **
170      *>      This function invokes a standard CBL_WRITE_FILE against **
171      *>      the file specified in the control block (see **
172      *>      SCB-Filename-TXT). **
173      *> **
174      *>      The buffer from which data will be written to the file **
175      *>      must be supplied as "arg2". The size of that buffer, **
176      *>      in bytes, will define the "byte-count" value supplied **
177      *>      CBL_WRITE_FILE subroutine. The buffer data will be **
178      *>      written to the file-offset position defined by the **
179      *>      SCB-Offset-NUM value. You may specify "arg2" either **
180      *>      as an actual alphanumeric data item or as an alpha- **
181      *>      numeric literal. **
182      *> **
183      *>      If the file-offset value (SCB-Offset-NUM) is greater **
184      *>      than the size of the file, a "no more data" return code **
185      *>      will be passed back in SCB-Return-CD and the buffer **
186      *>      will have been set to SPACES. **
187      *> **
188      *>      At the conclusion of a successful SCB-Func-WRITE-BOOL **
189      *>      operation, the value of SCB-Offset-NUM will have been **
190      *>      automatically incremented by the byte-count size of **
191      *>      "arg2". **
192      *> **
193      *> SCB-Func-READ-Delim-BOOL **
194      *> **
195      *>      SCB-Func-READ-Delim-BOOL behaves like the SCB-FUNC- **
196      *>      READ function, with the following behavioral dif- **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

```

Line  Statement
=====
197     *>      ferences:                **
198     *>                **
199     *>      1. When data is read from the file, only that data read **
200     *>          up to BUT NOT INCLUDING an end-of-line delimiter **
201     *>          sequence (either a LF or CRLF) will be retained in **
202     *>          the buffer - the remainder of the buffer from the **
203     *>          end-of-line sequence onward will be reset to SPACES. **
204     *>          The file-offset value (SCB-Offset-NUM) will be in- **
205     *>          cremented ONLY by the amount of data transferred up **
206     *>          to AND INCLUDING the end-of-line sequence.          **
207     *>                **
208     *>      2. When data is read from the file and an end-of-line **
209     *>          delimiter sequence (either a LF or a CRLF) cannot be **
210     *>          found within the buffer, the assumption is made that **
211     *>          the record is too long to fit within the buffer. In **
212     *>          these instances, an SCB-Return-CD value of 02 will **
213     *>          be returned and the SCB-Offset-NUM value will be **
214     *>          incremented past the next end-of-line sequence in **
215     *>          the file (this will involve at least one additional **
216     *>          call to CBL_READ_FILE to locate that eol sequence, **
217     *>          but any additional such reads will be done internal- **
218     *>          ly to STREAMIO and will be entirely transparent to **
219     *>          the caller of STREAMIO.                                **
220     *>                **
221     *>      DO NOT USE the Streamio-READ-Delim function if the **
222     *>          possibility exists that linefeed (X"0A") or carriage- **
223     *>          return (X"0D") characters could exist as actual data **
224     *>          characters in the file.                                **
225     *>                **
226     *>      SCB-Func-WRITE-Delim-BOOL                                **
227     *>                **
228     *>      SCB-Func-WRITE-Delim-BOOL acts like the Streamio- **
229     *>          FUNC-WRITE function, with the following difference: **
230     *>                **
231     *>      After the specified data is written to the file, an **
232     *>          end-of-line sequence will also be written to the file. **
233     *>          The file-offset value (SCB-Value) will be incremented **
234     *>          by the byte-count size of the data PLUS the size of the **
235     *>          end-of-line sequence. One of two possible end-of-line **
236     *>          sequences must be specified using the value of SCB- **
237     *>          Delimter-Mode.                                          **
238     *>                **
239     *>-----**
240     *>      SCB-Delimiter-Mode-CD                                    **
241     *>-----**
242     *>                **
243     *>      This data item is needed only when issuing the Streamio- **
244     *>          FUNC-WRITE-Delim function. In those circumstances, this **
245     *>          item defines what end-of-line delimiter sequence is to be **

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 5

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 6

```

=====
246     *> written:                                     **
247     *>                                             **
248     *> If SCB-Delim-Unix-BOOL is true, a linefeed character will **
249     *> be written.                                   **
250     *>                                             **
251     *> If SCB-Delim-Windows-BOOL is true, a carriage-return and **
252     *> linefeed sequence will be written.           **
253     *>                                             **
254     *>-----**
255     *> SCB-Offset-NUM                                **
256     *>-----**
257     *>                                             **
258     *> This data item specifies the next relative byte number with- **
259     *> in the file where the next read or write will start.     **
260     *>                                             **
261     *> SCB-Offset-NUM is automatically set to 0 (the first byte) **
262     *> when the file is opened, and is automatically incremented as **
263     *> the file is read or written via STREAMIO.         **
264     *>                                             **
265     *> You may also manually set this value as desired before any **
266     *> call to STREAMIO.                                   **
267     *>                                             **
268     *>-----**
269     *> SCB-Error-Routine-PTR                          **
270     *>-----**
271     *>                                             **
272     *> To specify a general error-handling routine for handling **
273     *> STREAMIO failures, Create the routine and define an entry- **
274     *> name for it via the ENTRY statement. Then use the following **
275     *> to set that routine up as the error handler:         **
276     *>                                             **
277     *>     SET SCB-Error-Routine-PTR TO ENTRY "entry-name" **
278     *>                                             **
279     *> To "turn off" the error-routine:                   **
280     *>                                             **
281     *>     SET SCB-Error-Routine-PTR TO NULL              **
282     *>                                             **
283     *> If a fatal error occurs (any error not marked with a ">" in **
284     *> the SCB-Return-CD discussion), the error routine you spe- **
285     *> cified (if any) will be set up as an exit routine via the **
286     *> CBL_EXIT_PROC subroutine; the STREAMIO routine will then is- **
287     *> sue a STOP RUN to intentionally trigger your error routine. **
288     *> You will not be able to recover your program once your error **
289     *> routine triggers. If you wish to be able to recover from **
290     *> fatal STREAMIO errors, you should NOT use the SCB-Error- **
291     *> Routine feature but instead you should explicitly test the **
292     *> SCB-Return-CD value after every call to STREAMIO.     **
293     *>                                             **
294     *> A default error routine is defined by the "STREAMIOError.cpy" **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 6

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 7

```

=====
295     *> copybook.                                     **
296     *>                                             **
297     *>-----**
298     *> SCB-Return-CD                                 **
299     *>-----**
300     *>                                             **
301     *> The following are the possible SCB-Return-CD values. The **
302     *> ones marked with a ">" will NOT trigger an error-routine, if **
303     *> one is currently registered via SCB-Error-Routine-PTR. **
304     *>                                             **
305     *> 12 I/O error writing to file                   **
306     *> 11 File does not exist                       **
307     *> 10 File already OPEN or already CLOSEd      **
308     *> > 02 READ-Delim was truncated                **
309     *> > 01 No more data is available from the current **
310     *>      SCB-Offset-NUM                          **
311     *> > 00 OK - the operation was successful        **
312     *> -1 Invalid SCB-Function-CD                   **
313     *> -2 Invalid SCB-Mode-CD                       **
314     *> -3 CBL_XXXXX_FILE routine rejected operation **
315     *> -4 Invalid delimiter mode specified (Not U/W) **
316     *>                                             **
317     *>-----**
318     *> SCB-Filename-TXT                             **
319     *>-----**
320     *>                                             **
321     *> This is the name of the file you wish to access. **
322     *>                                             **
323     *> If you are planning on reading the file, the file MUST exist **
324     *> at the time the SCB-Func-OPEN-BOOL is executed. **
325     *>                                             **
326     *> If you are planning on writing to the file, the file need **
327     *> exist when the SCB-Func-OPEN-BOOL is issued.  **
328     *>                                             **
329     *> In general, the contents of SCB-Filename-TXT should re- **
330     *> flect the complete path to the file as well as the name of **
331     *> the file itself, unless the file is contained in whatever **
332     *> directory is current at the time the SCB-Func-OPEN-BOOL is **
333     *> executed.                                       **
334     *>                                             **
335     *> The following special values may be used for **
336     *> SCB-Filename-TXT:                             **
337     *>                                             **
338     *> SPACES If the filename is SPACES, a filename will be created **
339     *>      automatically for you in whatever directory is de- **
340     *>      fined by the TEMP environment variable. If there IS **
341     *>      no TEMP variable defined, the "/tmp" folder will be **
342     *>      assumed. The filename will be STREAMIO-nnnnnnnn.dat **
343     *>      where "nnnnnnnn" is a random number.      **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 7

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cb1

Line Statement

Page: 8

```

=====
344     *>
345     *> .      If you specify only a dot (period) as the filename, **
346     *>      the behavior will be the same as with a value of **
347     *>      SPACES except there will be no ".dat" at the end of **
348     *>      the generated filename. **
349     *>
350     *> .ext  If you specify a filename extension prefixed with a **
351     *>      dot (period), the behavior will be the same as if a **
352     *>      value of SPACES were specified, except that the given **
353     *>      extension will be used instead of ".dat". Note that **
354     *>      if you are using a Unix/Cygwin implementation of **
355     *>      OpenCOBOL and you'd like to specify a hidden file in **
356     *>      the current directory as the SCB-Filename-TXT, you **
357     *>      MUST code the filename as "./.xxxxx" to avoid having **
358     *>      it treated as this special name. **
359     *>
360     *>*****
361     ENVIRONMENT DIVISION.
362     CONFIGURATION SECTION.
363     REPOSITORY.
364         FUNCTION ALL INTRINSIC.
365     DATA DIVISION.
366     WORKING-STORAGE SECTION.
367         01 WS-Access-Mode-CD                PIC X(1) COMP-X.
368         01 WS-Arg-Length-NUM                PIC X(4) COMP-X.
369         01 WS-Buffer-TXT                    PIC X(256).
370         01 WS-Delim-Buffer-TXT              PIC X(2).
371         01 WS-Env-Temp-TXT                  PIC X(256).
372         01 WS-Slash-CHR                     PIC X(1).
373         01 WS-Tally-NUM                      USAGE BINARY-LONG.
374         01 WS-8-Digit-NUM                   PIC 9(8).
375         01 WS-256-Byte-TXT                  PIC X(256).
376     LINKAGE SECTION.
377         01 L-StreamIO-Control-Block-TXT.
378         COPY STREAMIOcb
379             REPLACING LEADING ==SCB== BY ==L-SCB==.
05 L-SCB-Handle-NUM PIC X(4) COMP-X.
05 L-SCB-Mode-CD PIC X(1).
88 L-SCB-MODE-Input-BOOL VALUE 'I' 'i'.
88 L-SCB-MODE-Output-BOOL VALUE 'O' 'o'.
88 L-SCB-MODE-Both-BOOL VALUE 'B' 'b'.
05 L-SCB-Function-CD PIC X(2).
88 L-SCB-Func-CLOSE-BOOL VALUE 'C' 'c'.
88 L-SCB-Func-DELETE-BOOL VALUE 'D' 'd'.
88 L-SCB-Func-OPEN-BOOL VALUE 'O' 'o'.
88 L-SCB-Func-READ-BOOL VALUE 'R' 'r'.
88 L-SCB-Func-READ-Delim-BOOL VALUE 'RD' 'rd'
'rD' 'Rd'.
88 L-SCB-Func-WRITE-BOOL VALUE 'W' 'w'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 8

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 9

```

=====
88 L-SCB-Func-WRITE-Delim-BOOL VALUE 'WD' 'wd'
   'wD' 'Wd'.
05 L-SCB-Delimiter-Mode-CD PIC X(1).
88 L-SCB-DELIM-Unix-BOOL VALUE 'U' 'u'.
88 L-SCB-DELIM-Windows-BOOL VALUE 'W' 'w'.
05 L-SCB-Offset-NUM PIC X(8) COMP-X.
05 L-SCB-Error-Routine-PTR USAGE PROGRAM-POINTER.
05 L-SCB-Error-Routine-NUM REDEFINES L-SCB-Error-Routine-PTR
   USAGE BINARY-LONG.
05 L-SCB-Return-CD USAGE BINARY-LONG.
05 L-SCB-Filename-TXT PIC X(256).
380 01 L-Arg2-TXT PIC X ANY LENGTH.
381 PROCEDURE DIVISION USING L-StreamIO-Control-Block-TXT,
382 L-Arg2-TXT.
383 000-Main SECTION.
384 MOVE 00 TO L-SCB-Return-CD
385 EVALUATE TRUE
386 WHEN L-SCB-Func-CLOSE-BOOL
387 PERFORM 030-Validate-Handle-NonZero
388 PERFORM 200-CLOSE
389 WHEN L-SCB-Func-DELETE-BOOL
390 CALL "CBL_DELETE_FILE" USING L-SCB-Filename-TXT
391 WHEN L-SCB-Func-OPEN-BOOL
392 PERFORM 020-Validate-Handle-Zero
393 PERFORM 100-OPEN
394 WHEN L-SCB-Func-READ-BOOL
395 PERFORM 030-Validate-Handle-NonZero
396 PERFORM 400-READ
397 WHEN L-SCB-Func-READ-Delim-BOOL
398 PERFORM 030-Validate-Handle-NonZero
399 PERFORM 500-READ-Delim
400 WHEN L-SCB-Func-WRITE-BOOL
401 PERFORM 030-Validate-Handle-NonZero
402 PERFORM 300-WRITE
403 WHEN L-SCB-Func-WRITE-Delim-BOOL
404 EVALUATE TRUE
405 WHEN L-SCB-Delim-Unix-BOOL
406 PERFORM 030-Validate-Handle-NonZero
407 PERFORM 300-WRITE
408 MOVE 1 TO WS-Arg-Length-NUM
409 MOVE X"0A" TO WS-Delim-Buffer-TXT
410 WHEN L-SCB-Delim-Windows-BOOL
411 PERFORM 030-Validate-Handle-NonZero
412 PERFORM 300-WRITE
413 MOVE 2 TO WS-Arg-Length-NUM
414 MOVE X"0DOA" TO WS-Delim-Buffer-TXT
415 WHEN OTHER
416 MOVE -4 TO L-SCB-Return-CD
417 PERFORM 099-ERROR-Return
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 9

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 10

```

=====
418          END-EVALUATE
419          CALL "CBL_WRITE_FILE" USING L-SCB-Handle-NUM
420                                     L-SCB-Offset-NUM
421                                     WS-Arg-Length-NUM
422                                     0
423                                     WS-Delim-Buffer-TXT
424          PERFORM 040-Check-WRITE-SCB-Return-CD
425          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
426          WHEN OTHER
427              MOVE -1 TO L-SCB-Return-CD
428              PERFORM 099-ERROR-Return
429          END-EVALUATE
430          GOBACK
431          .
432          020-Validate-Handle-Zero SECTION.
433              IF L-SCB-Handle-NUM NOT = ZERO
434                  MOVE 10 TO L-SCB-Return-CD
435                  PERFORM 099-ERROR-Return
436              END-IF
437              .
438          030-Validate-Handle-NonZero SECTION.
439              IF L-SCB-Handle-NUM = ZERO
440                  MOVE 10 TO L-SCB-Return-CD
441                  PERFORM 099-ERROR-Return
442              END-IF
443              .
444          040-Check-WRITE-SCB-Return-CD SECTION.
445              IF RETURN-CODE < 0
446                  MOVE -3 TO L-SCB-Return-CD
447                  PERFORM 099-ERROR-Return
448              END-IF
449              IF RETURN-CODE = 30
450                  MOVE 12 TO L-SCB-Return-CD
451                  PERFORM 099-ERROR-Return
452              END-IF
453              MOVE 00 TO L-SCB-Return-CD
454              .
455          050-Check-READ-SCB-Return-CD SECTION.
456              IF RETURN-CODE < 0
457                  MOVE -3 TO L-SCB-Return-CD
458                  PERFORM 099-ERROR-Return
459              END-IF
460              IF RETURN-CODE = 10
461                  MOVE 01 TO L-SCB-Return-CD
462                  GOBACK
463              END-IF
464              MOVE 00 TO L-SCB-Return-CD
465              .
466          060-Identify-TEMP SECTION.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 10

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 11

```

=====
467      ACCEPT WS-Env-Temp-TXT FROM ENVIRONMENT "TEMP"
468      EVALUATE TRUE
469          WHEN WS-Env-Temp-TXT (1:1) = "/"
470              MOVE "/" TO WS-Slash-CHR
471          WHEN WS-Env-Temp-TXT (2:1) = ":"
472              MOVE "\" TO WS-Slash-CHR
473          WHEN OTHER
474              MOVE "/tmp" TO WS-Env-Temp-TXT
475              MOVE "/" TO WS-Slash-CHR
476      END-EVALUATE
477      .
478      099-ERROR-Return SECTION.
479          IF L-SCB-Error-Routine-NUM NOT = 0
480              CALL "CBL_EXIT_PROC" USING 0, L-SCB-Error-Routine-PTR
481              STOP RUN
482          END-IF
483          GOBACK
484      .
485      100-OPEN SECTION.
486          IF (L-SCB-Mode-Input-BOOL OR L-SCB-Mode-Both-BOOL)
487          AND (L-SCB-Filename-TXT = SPACES OR LOW-VALUES)
488              MOVE 11 TO L-SCB-Return-CD
489              PERFORM 099-ERROR-Return
490          END-IF
491          EVALUATE TRUE
492              WHEN L-SCB-Filename-TXT = SPACES OR LOW-VALUES
493                  PERFORM 060-Identify-TEMP
494                  MOVE SPACES TO L-SCB-Filename-TXT
495                  COMPUTE
496                      WS-8-Digit-NUM =
497                      RANDOM(SECONDS-PAST-MIDNIGHT) * 100000000
498                  END-COMPUTE
499                  STRING
500                      TRIM(WS-Env-Temp-TXT,TRAILING)
501                      WS-Slash-CHR
502                      "STREAMIO-"
503                      WS-8-Digit-NUM
504                      ".dat"
505                      DELIMITED BY SIZE
506                      INTO L-SCB-Filename-TXT
507              WHEN L-SCB-Filename-TXT(1:1) = "."
508                  PERFORM 060-Identify-TEMP
509                  IF L-SCB-Filename-TXT(2:1) = SPACE
510                      MOVE SPACES TO WS-256-Byte-TXT
511                  ELSE
512                      MOVE L-SCB-Filename-TXT TO WS-256-Byte-TXT
513                  END-IF
514              MOVE SPACES TO L-SCB-Filename-TXT
515              COMPUTE WS-8-Digit-NUM =
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 11

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 12

```

=====
516             RANDOM(SECONDS-PAST-MIDNIGHT) * 100000000
517             STRING
518             TRIM(WS-Env-Temp-TXT,TRAILING)
519             WS-Slash-CHR
520             "STREAMIO-"
521             WS-8-Digit-NUM
522             TRIM(WS-256-Byte-TXT,TRAILING)
523             DELIMITED BY SIZE
524             INTO L-SCB-Filename-TXT
525             END-EVALUATE
526             EVALUATE TRUE
527             WHEN L-SCB-Mode-Input-BOOL
528             MOVE 1 TO WS-Access-Mode-CD
529             WHEN L-SCB-Mode-Output-BOOL
530             MOVE 2 TO WS-Access-Mode-CD
531             WHEN L-SCB-Mode-Both-BOOL
532             MOVE 3 TO WS-Access-Mode-CD
533             WHEN OTHER
534             MOVE -2 TO L-SCB-Return-CD
535             PERFORM 099-ERROR-Return
536             END-EVALUATE
537             CALL "CBL_OPEN_FILE" USING TRIM(L-SCB-Filename-TXT,TRAILING)
538             WS-Access-Mode-CD
539             0
540             0
541             L-SCB-Handle-NUM
542             IF RETURN-CODE = 35
543             MOVE 11 TO L-SCB-Return-CD
544             PERFORM 099-ERROR-Return
545             END-IF
546             IF RETURN-CODE < 0
547             MOVE -2 TO L-SCB-Return-CD
548             PERFORM 099-ERROR-Return
549             END-IF
550             MOVE 00 TO L-SCB-Return-CD
551             MOVE 0 TO L-SCB-Offset-NUM
552             .
553             200-CLOSE SECTION.
554             CALL "CBL_CLOSE_FILE" USING L-SCB-Handle-NUM
555             IF RETURN-CODE < 0
556             MOVE -2 TO L-SCB-Return-CD
557             PERFORM 099-ERROR-Return
558             END-IF
559             MOVE 00 TO L-SCB-Return-CD
560             MOVE 0 TO L-SCB-Handle-NUM
561             .
562             300-WRITE SECTION.
563             CALL "C$PARAMSIZE" USING 2
564             MOVE RETURN-CODE TO WS-Arg-Length-NUM
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 12

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cb1

Line Statement Page: 13

```

=====
565          CALL "CBL_WRITE_FILE" USING L-SCB-Handle-NUM
566                                     L-SCB-Offset-NUM
567                                     WS-Arg-Length-NUM
568                                     0
569                                     L-Arg2-TXT
570          PERFORM 040-Check-WRITE-SCB-Return-CD
571          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
572          .
573          400-READ SECTION.
574          CALL "C$PARAMSIZE" USING 2
575          MOVE RETURN-CODE TO WS-Arg-Length-NUM
576          MOVE SPACES TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
577          CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
578                                     L-SCB-Offset-NUM
579                                     WS-Arg-Length-NUM
580                                     0
581                                     L-Arg2-TXT
582          PERFORM 050-Check-READ-SCB-Return-CD
583          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
584          .
585          500-READ-Delim SECTION.
586          CALL "C$PARAMSIZE" USING 2
587          MOVE RETURN-CODE TO WS-Arg-Length-NUM
588          MOVE SPACES TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
589          CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
590                                     L-SCB-Offset-NUM
591                                     WS-Arg-Length-NUM
592                                     0
593                                     L-Arg2-TXT
594          PERFORM 050-Check-READ-SCB-Return-CD
595          MOVE 0 TO WS-Tally-NUM
596          INSPECT L-Arg2-TXT(1:WS-Arg-Length-NUM)
597             TALLYING WS-Tally-NUM FOR ALL X"OA"
598          IF WS-Tally-NUM = 0 *> No LF found - return truncated data and position past n
ext LF (if any)
599             IF L-Arg2-TXT(WS-Arg-Length-NUM:1) = X"OD"
600                 MOVE SPACE TO L-Arg2-TXT(WS-Arg-Length-NUM:1)
601             END-IF
602          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
603          MOVE 02 TO L-SCB-Return-CD
604          MOVE 256 TO WS-Arg-Length-NUM
605          PERFORM UNTIL 0 = 1
606             MOVE SPACES TO WS-Buffer-TXT
607             CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
608                                     L-SCB-Offset-NUM
609                                     WS-Arg-Length-NUM
610                                     0
611                                     WS-Buffer-TXT
612          IF RETURN-CODE < 0
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 13

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 14

```

=====
613             MOVE -3 TO L-SCB-Return-CD
614             PERFORM 099-ERROR-Return
615             END-IF
616             IF RETURN-CODE = 10
617                 GOBACK
618             END-IF
619             MOVE 0 TO WS-Tally-NUM
620             INSPECT WS-Buffer-TXT
621                 TALLYING WS-Tally-NUM FOR ALL X"OA"
622             IF WS-Tally-NUM = 0
623                 ADD 256 TO L-SCB-Offset-NUM
624             ELSE
625                 MOVE 0 TO WS-Tally-NUM
626                 INSPECT WS-Buffer-TXT
627                     TALLYING WS-Tally-NUM
628                     FOR CHARACTERS BEFORE INITIAL X"OA"
629                 ADD WS-Tally-NUM, 1 TO L-SCB-Offset-NUM
630                 GOBACK
631             END-IF
632             END-PERFORM
633             ELSE             *> There is (at least) one LF in the buffer
634                 MOVE 0 TO WS-Tally-NUM
635                 INSPECT L-Arg2-TXT(1:WS-Arg-Length-NUM)
636                     TALLYING WS-Tally-NUM
637                     FOR CHARACTERS BEFORE INITIAL X"OA"
638                 ADD WS-Tally-NUM, 1 TO L-SCB-Offset-NUM
639                 IF WS-Tally-NUM > 1
640                     IF L-Arg2-TXT(WS-Tally-NUM:1) = X"OD"
641                         COMPUTE WS-Arg-Length-NUM =
642                             WS-Arg-Length-NUM
643                             - WS-Tally-NUM
644                             + 1
645                     ELSE
646                         COMPUTE WS-Arg-Length-NUM =
647                             WS-Arg-Length-NUM
648                             - WS-Tally-NUM
649                         ADD 1 TO WS-Tally-NUM
650                     END-IF
651                 MOVE SPACES
652                     TO L-Arg2-TXT(WS-Tally-NUM:WS-Arg-Length-NUM)
653                 ELSE
654                     MOVE SPACES
655                     TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
656                 END-IF
657             END-IF
658             .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 14

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cb1

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 15		
STREAMIO	000-Main	383	PROCEDURE				
STREAMIO	020-Validate-Handle-Zero	432	PROCEDURE	392			
STREAMIO	030-Validate-Handle-NonZero	438	PROCEDURE	387	395	398	
				401	406	411	
STREAMIO	040-Check-WRITE-SCB-Return-CD	444	PROCEDURE	424	570		
STREAMIO	050-Check-READ-SCB-Return-CD	455	PROCEDURE	582	594		
STREAMIO	060-Identify-TEMP	466	PROCEDURE	493	508		
STREAMIO	099-ERROR-Return	478	PROCEDURE	417	428	435	
				441	447	451	
				458	489	535	
				544	548	557	
				614			
STREAMIO	100-OPEN	485	PROCEDURE	393			
STREAMIO	200-CLOSE	553	PROCEDURE	388			
STREAMIO	300-WRITE	562	PROCEDURE	402	407	412	
STREAMIO	400-READ	573	PROCEDURE	396			
STREAMIO	500-READ-Delim	585	PROCEDURE	399			
STREAMIO	L-Arg2-TXT	380	LINKAGE	382	569C	576*	
				581C	588*	593C	
				599	600*	640	
				652*	655*		
STREAMIO	L-SCB-DELIM-Unix-BOOL	379	[STREAMIOcb]	405			
STREAMIO	L-SCB-DELIM-Windows-BOOL	379	[STREAMIOcb]	410			
STREAMIO	L-SCB-Delimiter-Mode-CD	379	[STREAMIOcb]				
STREAMIO	L-SCB-Error-Routine-NUM	379	[STREAMIOcb]	479			
STREAMIO	L-SCB-Error-Routine-PTR	379	[STREAMIOcb]	379	480C		
STREAMIO	L-SCB-Filename-TXT	379	[STREAMIOcb]	390C	487	492	
				494*	506*	507	
				509	512	514*	
				524*	537C		
STREAMIO	L-SCB-Func-CLOSE-BOOL	379	[STREAMIOcb]	386			
STREAMIO	L-SCB-Func-DELETE-BOOL	379	[STREAMIOcb]	389			
STREAMIO	L-SCB-Func-OPEN-BOOL	379	[STREAMIOcb]	391			
STREAMIO	L-SCB-Func-READ-BOOL	379	[STREAMIOcb]	394			
STREAMIO	L-SCB-Func-READ-Delim-BOOL	379	[STREAMIOcb]	397			
STREAMIO	L-SCB-Func-WRITE-BOOL	379	[STREAMIOcb]	400			
STREAMIO	L-SCB-Func-WRITE-Delim-BOOL	379	[STREAMIOcb]	403			
STREAMIO	L-SCB-Function-CD	379	[STREAMIOcb]				
STREAMIO	L-SCB-Handle-NUM	379	[STREAMIOcb]	419C	433	439	
				541C	554C	560*	
				565C	577C	589C	
				607C			
STREAMIO	L-SCB-MODE-Both-BOOL	379	[STREAMIOcb]	486	531		
STREAMIO	L-SCB-Mode-CD	379	[STREAMIOcb]				
STREAMIO	L-SCB-MODE-Input-BOOL	379	[STREAMIOcb]	486	527		
STREAMIO	L-SCB-MODE-Output-BOOL	379	[STREAMIOcb]	529			
STREAMIO	L-SCB-Offset-NUM	379	[STREAMIOcb]	420C	425*	551*	
				566C	571*	578C	
				583*	590C	602*	

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 15

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing				2014/03/27		
		C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cb1				
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 16	
=====	=====	=====	=====	=====	=====	=====
				608C	623*	629*
				638*		
STREAMIO	L-SCB-Return-CD	379	[STREAMIOcb]	384*	416*	427*
				434*	440*	446*
				450*	453*	457*
				461*	464*	488*
				534*	543*	547*
				550*	556*	559*
				603*	613*	
STREAMIO	L-StreamIO-Control-Block-TXT	377	LINKAGE	381		
STREAMIO	RETURN-CODE		PROCEDURE	445	449	456
				460	542	546
				555	564	575
				587	612	616
STREAMIO	WS-256-Byte-TXT	375	WORKING-STORAGE	510*	512*	522
STREAMIO	WS-8-Digit-NUM	374	WORKING-STORAGE	496*	503	515*
				521		
STREAMIO	WS-Access-Mode-CD	367	WORKING-STORAGE	528*	530*	532*
				538C		
STREAMIO	WS-Arg-Length-NUM	368	WORKING-STORAGE	408*	413*	421C
				425	564*	567C
				571	575*	576
				579C	583	587*
				588	591C	596
				599	600	602
				604*	609C	635
				641*	642	646*
				647	652	655
STREAMIO	WS-Buffer-TXT	369	WORKING-STORAGE	606*	611C	
STREAMIO	WS-Delim-Buffer-TXT	370	WORKING-STORAGE	409*	414*	423C
STREAMIO	WS-Env-Temp-TXT	371	WORKING-STORAGE	467*	469	471
				474*	500	518
STREAMIO	WS-Slash-CHR	372	WORKING-STORAGE	470*	472*	475*
				501	519	
STREAMIO	WS-Tally-NUM	373	WORKING-STORAGE	595*	597*	598
				619*	621*	622
				625*	627*	629
				634*	636*	638
				639	640	643
				648	649*	652

7. GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled “History”, Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled “History” in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work. In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly

and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C) year your name.  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the GNU Free Documentation License, Version 1.3  
or any later version published by the Free Software Foundation;  
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover  
Texts. A copy of the license is included in the section entitled ‘‘GNU  
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with  
the Front-Cover Texts being list, and with the Back-Cover Texts  
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

